

Warewashing Small Double Skin GW, electronic, cold rinse, drain pump & rinse aid dispenser,30b/h-no plug

ITEM #	
MODEL #	
NAME #	
SIS #	_
AIA #	_



402222 (ESICP3)

Glasswasher (small), with double skin, electronic control, cold rinse, built-in drain pump and rinse aid dispenser, 3 cycles, 30b/h no plug (400V/3N)

Short Form Specification

Item No.

Unit shall be Electrolux Professional green&clean Glasswasher type hot water rinsing using rack dimension of 400*400mm. Electrical characteristics to be 400 volts three phase 50Hz operation. Washing performance is ensured by a powerful wash pump, revolving washing spray arms both from bottom and top. Rinse temperature and pressure guaranteed by built in pressure boiler. Three automatic cycles of 120/300/120 seconds suitable for glasses and small plates/ saucer. Third cycle having cold rinse after hot rinse phase provides hygiene glasses and cold enough to handle. Double skin counter-balance door. Large door opening of 290mm for washing tall glasses. Double skin cabinet. Pressed tank with round corners. 304 stainless steel construction to include door, frame, wash tank, tank filter, wash arms and rinse arms. Electronic control with temperature display. The unit shall include drain pump and rinse aid dispenser pump and is equipped with electric cable.

Main Features

- Built-in rinse aid dispenser with automatic initial and continuous cycle loading for perfect result while minimizing service and maintenance needs.
- Low noise level.
- Built-in pressure boiler designed to raise incoming water to a guaranteed minimum temperature of 82° C for sanitizing rinse. No external boiler is required.
- Maximum capacity of 30 racks per hour.
- Washing system endowed with rotating washing arms from both top and bottom, high powered wash pump and large capacity wash tank guarantee professional washing.
- Easy service access to main components without moving the unit.
- Optional rinse booster pump available to be installed on site.
- Incorporated Soft Start feature to offer additional protection to more delicate items.
- Equipped with drain pump for easy and quick installation without opening the machine.
- Extra program to cold rinse beer and wine glasses providing sanitized glasses, cool enough to handle.
- New electronic control panel for easy setup of the working parameters and self diagnosis.
- 120/300/120 seconds cycle, the third cycle includes cold rinse.

Construction

- Completely closed on the back by a cover plate.
- Unit to feature rinse aid dispenser pump.
- Wash/rinse arms and nozzles in stainless steel.
- Finished in top quality stainless steel with double skinned construction to aid durability and reduce noise.
- Internal components (arms and filter) are easy extractable.
- Large tank filter collects the soil to keep the wash water clean for a longer time and have better washing performance.
- Deep drawn pressed wash tank with fully rounded corners, sloped towards the drain to prevent dirt buildup, provides fast drainage in just a few minutes. With no welding points the pressed tank offers a guaranteed water tight solution.
- 304 AISI stainless steel front panel, load bearing frame, wash tank, tank filter, wash and rinse arms.

Sustainability



 Insulated double skin door construction preserves heat inside the tank to lower energy consumption and the noise. Counter-balance mechanism minimizes impact when opening and closing.

APPROVAL:





Included Accessories

• 1 of Stainless steel tank filter	PNC 864003
• 1 of Square basket for glasses 400x400x150mm	PNC 864470

0412
0413
0430
4017
4050
4051
4242
4367
4461 🗖
4469
7016
7033
7048
7052
7054
7055
7056
7057
7058
7060
7061 🗖
7062




















CWII Cold Water inlet 1 (cleaning)

Drain

ΕI Electrical inlet (power) EO

Electrical Outlet WI Water inlet

Rinse aid connection



Electric

Supply voltage:

402222 (ESICP3) 400 V/3N ph/50 Hz

Default Installed Power: 4.8 kW 4,5 kW Boiler heating elements: 0,8 kW Tank heating elements: Wash pump size: 0.3 kW

Water:

Pressure, bar min/max: 1.8-3 bar Drain line size: 27mm Washing tank capacity (It): 6 Boiler Capacity (It): Incoming water line size: G 3/4"

Key Information:

Baskets per hour*: 30

Working cycles time (sec.): 120/300/120 Wash temperature: 55-65°C Cell dimensions - width: 400 mm Cell dimensions - depth: 400 mm Cell dimensions - height: 290 mm Rinse temperature: 80-90 °C External dimensions, Width: 460 mm External dimensions, Depth: 565 mm External dimensions, Height: 715 mm Net weight: 37 kg Shipping weight: 43 kg Shipping height: 870 mm Shipping width: 680 mm Shipping depth: 520 mm Shipping volume: 0.31 m³

Sustainability

Water supply temperature*: 10-55 °C

Water consumption per cycle

(It): 2.3 Noise level: 69 dBA









