

Warewashing Undercounter, atmospheric boiler, double skin, drain pump, det&rinse aid disp, 720d/h - Cafè line

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



502720 (ELAIIGCL)

Undercounter Dishwasher with atmospheric boiler, double skin, built-in drain pump, detergent and rinse aid dispensers, 1 phase, 720d/h - Café line

Short Form Specification

Item No.

Unit shall be Electrolux Professional green&clean Cafè-line undercountertype hot water rinsing dishmachine using rack dimension of 500*500mm. Electrical characteristics to be 230 volts single phase 50Hz operation, convertible to three phase on-site. Washing performance is ensure by a powerful wash pump, large capacity wash tank, upper and lower revolving spray arms. Soft start wash pump to avoid accidental breakage of crystal wares. Constant rinse temperature and pressure guaranteed by built-in atmospheric boiler and rinse booster pump. Uses 2.5 liters of clean water per final rinse. Powerful boiler heater ensures high productivity even with cold water supply. Three automatic cycles for different types of wares. Double skin insulated, counter-balance door. Double skin cabinet. Pressed wash tank with round corners. 304 AISI stainless steel construction to include door, external panels, frame, wash tank, tank filters, wash arms and rinse arms. The unit shall include drain pump, detergent and rinse aid dispenser pumps and is equipped with electric cable. Delivered small castors for easily moving the machine around.

Main Features

- Incorporated Soft Start feature to offer additional protection to more delicate items.
- Washing system endowed with rotating washing arms, high powered wash pump and large capacity boiler for professional washing.
- 4 second (variable) pause after washing and before rinsing ensures that no drops of unclean water will fall on the clean items at the end of the rinsing cycle.
- Fully automatic self-cleaning cycle avoids the risk of bacteria proliferation.
- Simple control panel with digital display allows onsite personalization of washing and rinsing cycle times and temperatures as well as precise rinse aid and detergent quantities to suit customer's needs.
- Simple service from the front.
- IPx4 water protection.
- Digital read-out keeps operator informed as to temperatures.
- State-of-the-art electronic controls with built-in programming, self-diagnostics for serviceability and automatic interior self-cleaning cycle.
- Unique temperature interlock guarantees required temperatures in both the wash and final rinse in case of emergency cold water feeding.
- Constant temperature of 84 °C thoughout the rinsing cycle regardless of the network's water pressure and temperature.
- Double skinned insulated wall ensures a low noise level and a reduction in heat loss from the machine.
- High efficiency air gap (class A) in water inlet circuit to avoid water being siphoned back into the network as a result of a sudden drop in main pressures.
- Low noise level.
- Washing capacity of 40 baskets or 720 dishes per hour.
- Slanted wash arms to avoid detergent-filled wash water dropping on clean dishes after the rinsing phase, thus guaranteeing ideal washing results.
- Built-in atmospheric boiler sized to raise incoming water to 84 °C minimum for sanitizing rinse. No external booster is required.
- Solid double skinned counter-balance door with hurt-free handle fully in stainless steel.
- An effective rinse system uses only 2,5 litres of clean hot water per basket for lower running costs.
- Built-in rinse aid and detergent dispenser with automatic initial and continuous cycle loading for perfect result while minimizing service and maintenance needs.
- Three phase or single phase electrical connection, convertible on-site.

Construction

- Unit to feature smooth surfaces to facilitate cleaning.
- 304 stainless steel boiler with higher welding protection to increase resistance to corrosion.
- PVC water supply hose with metal connections

APPROVAL:





Warewashing Undercounter, atmospheric boiler, double skin, drain pump, det&rinse aid disp, 720d/h - Cafè

resistant to high water pressure.

- Completely closed on the back by a cover plate.
- Element protection from dry fire and low water.
- Interchangeable wash/rinse arms screw out for simple clean up.
- The boiler drain facilitates the evacuation of stagnant water after long periods of inactivity to ensure a higher level of hygiene.
- Incorporated drain pump to control water level in wash tank draining.
- Large deep drawn wash tank and internal wash area with round corners and no pipes to avoid dirt built-up.
- Revolving Stainless steel wash/rinse arms above and below the basket.
- Large tank filter collects the soil to keep the wash water clean for a longer time and have better washing performance.
- Front panel, door, wash tank, tank filters, wash arms and rinse arms made in heavy duty anti-corrosive 304 AISI stainless steel.
- 4 rollers under the machine to allow it to be easily extracted for cleaning.

Sustainability

- Pre-arrangement for HACCP system implementation and Energy Management device.
- Unit to feature drain pump, rinse aid and detergent dispenser pumps.

Included Accessories

 2 of Yellow cutlery container 	PNC 864242
 1 of Basket for 18 dinner plates - yellow 	PNC 867002
• 1 of Basket for 48 small cups or 24	PNC 867007

Optional Accessories		
• 121t external manual water softener	PNC 860412	
• 8lt external automatic water softener	PNC 860413	
• Stand for undercounter dishwasher	PNC 860418	
• 20lt external manual water softener	PNC 860430	
 Kit 4 castors for double skin undercounter dishwashers 	PNC 864008	
 Kit 4 flanged feet for undecounter dishwashers 	PNC 864009	
 Filter for partial demineralization 	PNC 864017	
 Kit to measure total and partial water hardness 	PNC 864050	
 Yellow cutlery container 	PNC 864242	
 Filter for total demineralization 	PNC 864367	
 External reverse osmosis filter for single tank Dishwashers with atmosphere boiler and Ovens 	PNC 864388	
 Pressure reducer for single tank dishwasher 	PNC 864461	
 Connectivity kit for Undercounter Dishwashers and Pot Washers (ECAP) 	PNC 864479	
 Half size basket universal 	PNC 864527	
 Half size basket for plates 	PNC 864528	
 Half size basket for glasses 	PNC 864529	
		_

 Basket for 18 dinner plates - yellow Basket for 5 trays 530x325 mm - red, for 	PNC 867002 PNC 867006	
undercounter (ťop level), utensil dishwashers, hood type, rack type		
Basket for 48 small cups or 24 cups - blue	PNC 867007	
Wire basket for 12 plates up to 320 mm	PNC 867014	
 Cover rack for small and light items (500x500 baskets) 	PNC 867016	
 Basket for long stem wine glasses 	PNC 867019	
 Basket for 16 vertical glasses (h 70 mm - diam 100 mm) - blue 	PNC 867023	
 Basket semi-professional 500x500x190mm 	PNC 867024	



yellow



• Kit 4 plastic boxes for cutlery -











PNC 865574 🔲








Drain ΕI

Electrical inlet (power) EO **Electrical Outlet**

HWI Hot water inlet Detergent connection

Rinse aid connection



Electric

Supply voltage:

502720 (ELAIIGCL) 230 V/1 ph/50 Hz Convertible to: 400V 3N~; 230V 3~

Default Installed Power: 6.85 kW Boiler heating elements: 6 kW Tank heating elements: 2 kW Wash pump size: 0.736 kW

Water:

Pressure, bar min/max: 0.5-7 bar Drain line size: 20.5mm

7 - 102 psi (0.5 - 7 bar) Inlet Water supply pressure:

Washing tank capacity (It): 23 Boiler Capacity (It): 12

Key Information:

Baskets per hour*: 40 Dishes per hour: 720

Working cycles time (sec.): 90/120/240 Wash temperature: 55-65°C Cell dimensions - width: 500 mm Cell dimensions - depth: 500 mm Cell dimensions - height: 335 mm Rinse temperature: 84 °C External dimensions, Width: 600 mm External dimensions, Depth: 615 mm

External dimensions, Height:

Packaging size 740x670x1020 mm

820 mm

(WxDxH):

Sustainability

Water supply temperature*: 50 °C

Water consumption per cycle

2.5 Noise level: 61 dBA











