

Warewashing Electric Personal Protective Equipment (PPE) Washer with electronic control, drain pump, detergent dispenser, high opening - Fire Brigade

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



506063 (EPPWEHGFB)

Electric Personal Protective Equipment (PPE) Washer with electronic control, drain pump, detergent dispenser, high opening - Fire Brigade

Short Form Specification

Item No.

304 AISI stainless steel front and side panels, wash tank, tank filter and wash and rinse arms. Double skinned insulated door divided in 2 parts with 180° frontal opening. N. 4 washing cycles. Built-in atmospheric, insulated water boiler (10,5 kW), 18-liter capacity, combined with rinse booster pump guarantee a constant hot rinse temperature of 60°C. Boiler with 304 welding for protection against corrosion. Wash Safe Control assures the correct water temperature and pressure during the rinse phase to guarantee a perfect rinsing performance independent from the water pressure in the network (min. 0,5 bar). High efficiency air gap (class A) in water inlet circuit to avoid water being syphoned back into the network as a result of a sudden drop in mains pressure.

Fault auto-diagnosis system. Self-cleaning cycle. Drain pump, rinse aid and detergent dispenser included.

Pre-arrangements for connection to an Energy Management device and to an automatic detergent dispenser.

Cell dimensions mm670x710x710h.

For front-feed loading, IPX5 water protection. Supplied with: n. 1 basket in stainless steel.

Main Features

- Industrial cleaning machine to wash and sanitize protective personal equipments in steel, composite, rubber, fabric, plastic etc. from grease, residues of combustion gases, toxins etc. in just few minutes to save time and minimize contamination
- Door divided in two parts with 180° frontal opening for a better and easier load.
- Fault auto-diagnosis system. Self-cleaning cycle.
 Drain pump and detergent dispenser included.
- Pre-arrangements for connection to an automatic detergent dispenser.
- IPX5 water protection.
- Low noise level.
- Simple service from the front.

Construction

- 304 AISI stainless steel front and side panels, wash tank, tank filter and wash and rinse arms.
- Equipped with side washing arms in addition to upper and lower wash arms.
- Supplied with: n. 1 basket in stainless steel.

Included Accessories

• 1 of Reinforced stainless steel basket for pot&pan, 688mm


Optional Accessories

Filter for total demineralization
 Filter for partial demineralization
 Kit to measure total and partial water hardness
 Filter for total demineralization
 Reinforced stainless steel basket for pot&pan, 688mm
 PNC 864017 □ PNC 864050 □
 PNC 864367 □ PNC 864394 □

APPROVAL:








 D
 =
 Drain

 EI
 =
 Electrical inlet (power)

 EO
 =
 Electrical Outlet

 HWI
 =
 Hot water inlet

 XD
 =
 Detergent connection



Electric

Front

Side

Top

Supply voltage: 400 V/3N ph/50 Hz Electrical power, max: 20 kW

Default Installed Power: 13 kW
Wash pump power: 2.5 kW

Water:

Pressure, min-max: 0.5-7 bar

Washing cycle electrical

elements: 7 kW

Hot rinse cycle duration

(sec.):

ISO 9001; ISO 14001

Water supply temperature*: 50 °C Washing tank capacity (It): 95 Boiler Capacity (It): 18

Key Information:

Rinsing water consumption

(per cycle): 7 lt

Washing cycle temperature: $55-65 \, ^{\circ}\text{C}$ Hot rinse cycle temperature: $60 \, ^{\circ}\text{C}$

 N° of working cycles: 4 (180/360/540/inf)

670 mm Cell dimensions - width: 710 mm Cell dimensions - depth: 740 mm Cell dimensions - height: External dimensions, Width: 876 mm 900 mm External dimensions, Depth: 1991 mm External dimensions, Height: Net weight: 216 kg Shipping weight: 255 kg Shipping height: 2230 mm Shipping width: 1030 mm Shipping depth: 1070 mm Shipping volume: 2.46 m³

