

	MODEL #
PROFESSIONAL	NAME #
Warewashing Large pre-wash zone for green&clean	SIS #
multi-rinse Rack Type with Energy	AIA #
Saving Device, ZERO LIME	
535037 (NLPWEEW) Lorge pre-wash zone for greened clean Nulli Rinser Kack Type Dishwasher with Ereg yo Soving Device, WRASK Watermark approval	 Main Features Deep drawn pressed tank with fully rounded corners, sloped towards the drain to prevent dirt build-up, provides fast drainage in just a few minutes. With no welding points the pressed tank offers a guaranteed water tight solution. Manual process of pre-wash spraying replaced by automatic prewash module before the main wash section. Pre-wash section uses cold water so food remains are not "baked" onto the plates in order to have better pre-wash performance. Large counter balanced inspection door allows unrestricted all-round access to the internal area. Door is insulated with injected foam. This adds strength as well as reduces noise and heat loss. IP25 protection against water jets, solid objects and small animals (larger than 6 mm). Built-in drain valve in the tanks allows automatic dump and fill to refresh the water in the tank without any interruption of the washing process. Automatic drain, clean and sanitize cycles featured as standard. The internal chamber, including the internal door is completely cleaned or sanitized avoiding bacteria proliferation for maximum hygiene and reducing manual work/time for operator. The feeding direction can be either left to right or right to left as it's reversible on site. Adjustable feet for full access underneath the machine for cleaning. Mall main components made in heavy duty anticorrosive 304 type stainless steel: internal chamber, external, front and side panels, pre-wash arms and rack transportation system. Sustaincollity The unit must be connected with Electrolux Professional green&clean multi-rinse rack type dishwasher with Energy Saving Device and ZERO LIME device. Multi-stage advanced filtering system removes soil from the pre-wash water providing cleaner water thus ensuring better washing performances. Multi-stage advanced filtering system removes soil fr
APPROVAL:	l

ITEM #

Electrolux PROFESSIONAL

Warewashing Large pre-wash zone for green&clean multirinse Rack Type with Energy Saving Device, ZERO LIME



Electric

Pre-wash tank heating eleme during sanitation cycle.	nts are activated only
Supply voltage:	380-415 V/3N ph/50 Hz
Pre-wash tank heating elements:	14 kW
Default Installed Power:	15.5 kW
Pre-wash pump size:	1.5 kW
Water:	

Pre-wash tank size:

Key Information:

For transportation purpose only, the depth can be reduced to 795mm by removing the door handle. Reference norm used to measure the noise: IEC60335-2-58 annex AA.

ICCOUSSE 2 SO UNITER AA.	
Height with door open:	2095 mm
Charging hole size (width):	530 mm
External dimensions, Width:	890 mm
External dimensions, Depth:	825 mm
External dimensions, Height:	1785 mm
Charging hole size (height):	490 mm
Net weight:	163 kg
Shipping weight:	168 kg
Shipping height:	2030 mm
Shipping width:	1030 mm
Shipping depth:	910 mm
Shipping volume:	1.9 m³
Pre-wash temperature:	10 - 40 °C

Sustainability

Noise level:

<62 dBA

Warewashing Large pre-wash zone for green&clean multi-rinse Rack Type with Energy Saving Device, ZERO LIME The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.