

# Soft Served Capri Soft Ice Cream Dispenser, 1 flavour, electronical control & touch panel, 290cones/h-pump

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA#	



560061 (CAP114MPA3PH)

Soft ice cream dispenser with 8 I tank capacity and 1,95 I cylinder volume, 1 flavour, electromechanical control, countertop, hourly production: 280 cones (75 gr), pump version

560063 (CAP114DPA3PH)

Soft ice cream dispenser with 8 I tank capacity and 1,95 I cylinder volume, 1 flavour, electronical control and touch screen panel, countertop, hourly production: 290 cones (75 gr), pump version, R452A

### **Main Features**

- Countertop appliance with pump delivers soft ice cream and frozen yogurt, single-flavor equipment.
- Thanks to the pump feeding system, the equipment incorporates more air - high overrun - and therefore the dispensed ice cream is lighter and softer. High overrun means higher profit.
- Digital control with touch screen. (only for 560063)
- The machine is equipped with tank agitator and stainless steel drip tray.
- Equipped with a 8 liters tank capacity and dispenses up to 290 cones/h (75 gr cones). (only for 560063)
- Equipped with a 81 liters tank capacity and dispenses up to 280 cones/h (75 gr cones). (only for 560061)


#### Construction


- Air-cooled version requires no water connections that means low operating costs and easy installation.
- Environmentally friendly: R452a as refrigerant gas. (only for 560063)
- Electromechanical control. (only for 560061)


APPROVAL:











## **Electric**

Supply voltage:

560061 (CAP114MPA3PH) 380-400 V/3N ph/50 Hz 560063 (CAP114DPA3PH) 380-400 V/3N ph/50 Hz 2 kW

Electrical power max.:

### **Key Information:**

External dimensions, Width:

560061 (CAP114MPA3PH) 465 mm 560063 (CAP114DPA3PH) 475 mm

External dimensions, Depth:

560061 (CAP114MPA3PH) 831 mm 560063 (CAP114DPA3PH) 600 mm 791 mm External dimensions, Height: Net weight: 120 kg

Freezing cylinder capacity:

560061 (CAP114MPA3PH) 1.95 I 560063 (CAP114DPA3PH) 195 I Preparation system: Pump N° of hoppers/grinders: Hopper capacity:

Plug type: IEC/EN 60309-1/2

### **Refrigeration Data**

Operating temperature min.: Operating temperature max.: 36 °C

### Sustainability

R452A Refrigerant type: Refrigerant weight: 780 g

