

### Soft Served Portofino Soft Ice Cream Dispenser, 2 flavours+1mix, electr.control&touch panel, 500cones/h-gravity

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



#### 560074 (POR214DGA3PH)

Soft ice cream dispenser with 2x12 I tank capacity and 1,95 I cylinder volume, 2 flavours + 1 mix, electronical control and touch screen panel, countertop, hourly production: 500 cones (75 gr), gravity version, R452A

# **Short Form Specification**

#### Item No.

Soft ice cream and frozen yogurt dispenser with 2x12 I tank capacity and 1,95 I cylinder volume, 2 flavours + 1 mix, hourly production: 500 cones (75 gr). Digital control and touch screen panel. It is a countertop appliance with gravity system. The tank agitator and the stainless steel drip tray are included as standard. R452a as refrigerant gas. Air-cooled version: requires no water connections that means less operating costs and it is easy to install.

### **Main Features**

- The machine is equipped with tank agitator and stainless steel drip tray.
- Digital control with touch screen.
- It delivers soft ice cream and frozen yogurt.
- The machine is equipped with two tanks of 12 liters capacity and dispenses 500 cones/h (75gr cones).
- The gravity machine is extremely easy to use, clean and maintain. Ice cream has a strong and very intense flavor.
- Countertop appliance with gravity system delivers soft ice cream and frozen yogurt, two-flavor equipment.


### Construction


- Environmentally friendly: R452a as refrigerant gas.
- Air-cooled version requires no water connections that means low operating costs and easy installation.


#### APPROVAL:











### Electric

Supply voltage:

**560074 (POR214DGA3PH)** 380-400 V/3N ph/50 Hz

Electrical power max.: 4.5 kW

**Key Information:** 

External dimensions, Width: 572 mm
External dimensions, Depth: 875 mm
External dimensions, Height: 931 mm
Net weight: 201 kg
Freezing cylinder capacity: 1.95 |
Preparation system: Gravity
N° of hoppers/grinders: 2
Hopper capacity: 12 |

**Plug type:** IEC/EN 60309-1/2

## **Refrigeration Data**

Operating temperature min.: 20  $^{\circ}$ C Operating temperature max.: 40  $^{\circ}$ C

### Sustainability

**Refrigerant type:** R452A **Refrigerant weight:** 1100 g

