

Soft Served Roma Soft Ice Cream Dispenser, 2 flavours+1mix, electr.control&touch panel, 550cones/h-gravity

ITEM #	
MODEL #	
NAME #	
SIS #	_
AIA #	_



560078 (ROM218DGA3PH)

Soft ice cream dispenser with 2x13 I tank capacity and 1,95 I cylinder volume, 2 flavours + 1 mix, electronical control and touch screen panel, free standing, hourly production: 550 cones (75 gr), gravity version, R452A

Short Form Specification

Item No.

Soft ice cream dispenser with 2x13 I tank capacity and 1,95 I cylinder volume, 2 flavours + 1 mix, hourly capacity: 550 cones/ h (75gr cones). Digital control and touch screen panel, free standing with gravity version. Tank agitator and drip tray are included as standard. Air-cooled version: requires no water connections that means less operating costs and it is easy to install. Environmentally friendly: R452a as refrigerant gas.

Main Features

- Digital control with touch screen.
- The machine is equipped with two tanks of 13 liters capacity and dispenses 550 cones/h (75gr cones).
- The machine is equipped with tank agitator and stainless steel drip tray.
- It delivers soft ice cream and frozen yogurt.
- Free-standing appliance, two-flavors equipment with gravity feeding system.
- The gravity machine is extremely easy to use, clean and maintain. Ice cream has a strong and very intense flavor.


Construction


- Air-cooled version requires no water connections that means low operating costs and easy installation.
- Environmentally friendly: R452a as refrigerant gas.


APPROVAL:











Electric

Supply voltage:

560078 (ROM218DGA3PH) 380-400 V/3N ph/50 Hz

Electrical power max.: 5.1 kW

Key Information:

External dimensions, Width: 571 mm
External dimensions, Depth: 834 mm
External dimensions, Height: 1528 mm
Net weight: 221 kg
Freezing cylinder capacity: 1.95 |
Preparation system: Gravity
N° of hoppers/grinders: 2
Hopper capacity: 13 |

Plug type: IEC/EN 60309-1/2

Refrigeration Data

Operating temperature min.: 20 °C Operating temperature max.: 40 °C

Sustainability

Side

Refrigerant type: R452A

