



# Cooking Range Line thermaline 90 Full Module Electric Fry Top, Ribbed Plate, 1 Side - Marine USPHS only M2M

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_

**589919**  
**(HCHNBBHODM)** Electric Fry Top with ribbed Scratch Resistant NitroChrome3 cooking plate, 2 zones, one-side operated with splashback - Marine USPHS (only M2M)

## Short Form Specification

### Item No.

Unit constructed according to DIN 18860\_2 with 20 mm drop nose top and 120 mm recessed plinth. Internal frame for heavy duty sturdiness in stainless steel. 3mm top with 3 mm reinforcement in 1.4301 (AISI 304). Cooking surface in patented Nitro Chrome3 Scratch resistant cooking surface with non-stick finishing for optimum grilling results. Powerblock heating system for optimal temperature distribution. Large drain hole allows draining of cooking juices into a large collector. Overheat protection switches off the supply in case of overheating. Standby function saves energy and quickly recovers maximum power. Metal knobs with embedded hygienic "soft-touch" grip enable easier handling and cleaning. IPX6 water resistant certification. Configuration: One-side operated top.

## Main Features

- Overheat protection: the temperature sensor switches off the supply in case of overheating.
- All major components may be easily accessed from the front.
- Choice of one or two heating zones. An indicator lamp shows operating state of each zone.
- Large drain hole on cooking surface permits the draining of residual cooking juices into a large collector placed under the cooking surface.
- Stainless steel high splash guards on the rear and sides of cooking surface.
- Units have separate controls for each half module of the cooking surface.
- Metal knobs with embedded hygienic "soft-touch" grip for easier handling and cleaning. The special design of the controls prevents infiltration of liquids or soil into vital components.
- Powerblock heating system for optimal temperature distribution.
- IPX6 water protection.

## Construction

- Internal frame for heavy duty sturdiness in 1.4301 (AISI 304).
- Cooking surface to be completely smooth or completely ribbed.
- 3mm top with 3 mm reinforcement in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860\_2 with 20 mm drop nose top and 120 mm recessed plinth.
- Cooking surface in patented Nitro Chrome3 Scratch resistant cooking surface thanks to a special treatment of the chromium plate.

## Sustainability



- Standby function for energy saving and fast recovery of maximum power.

## Optional Accessories

- Scraper for ribbed plates PNC 913120
- Portioning shelf 1000x65mm - Marine USPHS (only M2M) PNC 913713

## Recommended Detergents

- C41 HI-TEMP RAPID DEGREASER, 1 pack of six 1 lt. bottles (trigger incl.) PNC 0S2292

APPROVAL: \_\_\_\_\_



Experience the Excellence  
[www.electroluxprofessional.com](http://www.electroluxprofessional.com)

**Electric**

Supply voltage: 440 V/3 ph/60 Hz  
 Total Watts: 15.3 kW

**Key Information:**


Cooking Surface Depth: 615 mm  
 Cooking Surface Width: 700 mm  
 Working Temperature MIN: 80 °C  
 Working Temperature MAX: 280 °C  
 External dimensions, Width: 800 mm  
 External dimensions, Depth: 900 mm  
 External dimensions, Height: 250 mm  
 Net weight: 120 kg  
 Configuration: One-Side Operated;Top  
 Cooking surface type: Ribbed  
 Anti-scratch NitroChrome3

Cooking surface - material:


**Sustainability**

Current consumption: 20 Amps

Front



Side



EI = Electrical inlet (power)  
 EQ = Equipotential screw

Top

