

# LiberoPro Flat Induction 1 Phase, mono zone, drop in

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA#	
71171	



600876 (E1HDEDOMCS)

Plug-in Induction Mono Zone Cook Top, drop-in

# **Short Form Specification**

#### Item No.

Plug-in 1 Phase induction mono zone cooktop designed for drop-in installation, entirely constructed in AISI 304 stainless steel. Sealed heavy duty glass-ceramic cooking surface, 4 mm in thickness. Glass touch display on top for maximum visibility with power settings and timer. 2-color user interface (white and red) for better readability. Lock function stops your settings to be accidentally modified during working. Hot surface warning to prevent injuries. Automatic pan reconigtion and rapid heat trasfer directly to the pan. Suitable for pots and pans with diameter from 120 mm to 340 mm. Cord and plug included. IPx4 water protection.

#### **Main Features**

- Plug in unit designed for drop in installations.
- 2-color user interface (white and red) for better readability.
- Automatic pan detection to transfer power only when pan is present.
- Glass touch display on top for maximum visibility.
- Power level settings from 1 to 10.
- Timer function can be used to set the cooking time, switching off the zone automatically at the end of the time set.
- Suitable for pot and pan with diameter from 120 mm to 340mm.
- Self-diagnostics: an error code is displayed (Exxx) in case of dysfunction.

### Construction

- Heavy duty AISI 304 Stainless steel construction.
- Sealed heavy duty glass-ceramic cooking surface, 4 mm in thickness.
- Cord and plug included.
- IPx4 water protection.

### Sustainability



- Rapid heat transfer directly to the pan, no heat is dispersed into the environment.
- This model is compliant with Swiss Energy Efficiency Ordinance (730.02).

### **Optional Accessories**

- Kit ventilation including air conveyor for Drop-in functions

  PNC 650146 □
- Kit fixation including sponge gasket and kit assembly for Drop-in functions


  PNC 650147 □
- Stainless steel universal frying pan with stainless steel handle (diam. 200mm) suitable for induction and all other heating sources
- Universal frying pan with stainless steel handle (diam. 240mm) suitable for induction and all other heating sources
- Universal frying pan with stainless steel handle (diam. 280mm) suitable for induction and all other heating sources
- Universal frying pan with ribbed plate suitable for induction cookers
   PNC 653618 □

#### APPROVAL:





## LiberoPro Flat Induction 1 Phase, mono zone, drop in



**Electric** 

**Supply voltage:** 220-240 V/1N ph/50-60 Hz

Total Watts: 3.5 kW
Plug type: CE-SCHUKO

Minimum Circuit Ampacity

(MCA): 13A

**Key Information:** 

External dimensions, Width: 392 mm
External dimensions, Depth: 592 mm
External dimensions, Height: 127 mm
Net weight: 14.5 kg

