

Vegetable Slicer TrinityPro Combined Vegetable Slicer/ Cutter Mixer 3,6 Lt with sealed lid - Variable Speed

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____


602229 (COM36SVS)

Combined Vegetable Slicer and Cutter Mixer 3,6 Lt with stainless steel bowl, sealed lid, variable speed 500-3600 rpm, Schuko plug

Short Form Specification

Item No. _____

Combined Vegetable Slicer and Cutter Mixer with 3,6 litres, stainless steel bowl. Vegetable slicer ensures consistent cutting results thanks to the design patented lever-pusher. Constructed in a sturdy plastic material. 1,25 liters transparent half-moon hopper. Vegetables can be fed directly into the half moon hopper, a pusher presses the vegetables against the cutting discs ensuring an even cut in minimal time. 2 small hoppers for precise cuts on long vegetables dia. 55mm or 25mm. Ideal for grating, slicing/wavy slice, julienne and dicing.

Cutter Mixer transparent copolyester lid with sealed lid, scraper and central feed hole for adding products in mid-cycle. Microtoothed blade rotor. Angled blades and conical base of the bowl ensure consistent mixing. All ingredients are processed evenly and quickly thanks to a special flow generated inside the bowl.

No-volt release system prevents accidental start of the appliance. All parts in contact with food are removable and Dishwasher safe. Waterproof, easy to clean, flat, soft-touch buttons. Variable speed 500-3600 rpm. A smart speed control limits the speed when vegetable slicer attachment is installed. With Schuko plug.

Main Features

- Combined appliance with two functions: vegetable slicer and cutter mixer.
- Equipped with vegetable slicer attachment for slicing, grating, shredding (julienne) as well as dicing and French fries cutting.
- Cutter mixer and emulsifier function included, for fast chopping, mixing, mincing, griding, liquidizing and kneading.
- Equipped with half moon hopper (1,25lt capacity) and 2 small round feed chutes: Ø 25mm and Ø 55mm, for precise slicing of long shaped vegetables.
- Uniform cuts and maximised load capacity, thanks to the design patented lever-pusher.
- Large output chute for efficient ejection. Fits up to 200mm high standard kitchen containers (like GN) under the output chute.
- Continuous feed model.
- Pulse function for quick and precise slicing and grating.
- Flexibility for high quality cuts: 9-level variable speed can be adjusted according to consistency of ingredients.
- Ergonomical frontal lever, suitable for left handed and right handed operators.
- Vegetable slicer blade stops when lever pusher is lifted for operator safety.
- Optional discs and grids available of various sizes for slicing, dicing, grating and shredding (diam. 175mm).
- Automatic speed limitation according to the selected function (slicer or cutter).
- Includes 3,6 liter stainless steel bowl with micro-toothed blades rotor.
- Bowl/lid scraper included for uniform smooth results (emulsifying) and continuous working.
- All ingredients are processed evenly and quickly thanks to a special movement generated inside the bowl.
- Pulse function for coarse chopping.
- Easy to clean and waterproof control panel with flat on/off button and pulse function.
- All parts in contact with food are removable without the use of tools, completely dismountable and dishwasher safe.
- Productivity: up to 100 settings per service for vegetable slicer, up to 50 settings per service for cutter mixer function.
- ErgoCert 4-star certification for ergonomic design and ease of use.
- Transparent lid, with sealing to prevent leakage and with funnel shaped hole, to add ingredients during use.

APPROVAL: _____

Construction

- Bowl in AISI 304 stainless steel.
- Micro-toothed blades in 420 AISI stainless steel and ergonomic scraper in resistant composite material to ensure consistent mixing.
- IPX5 (IP55) waterproof, flat, touch-control panel.
- Main switch ON/OFF on the back of the appliance.
- Asynchronous industrial motor with no brushes for high reliability and quiet functioning, stainless steel motor shaft.
- Variable speed: 500 - 3600 rpm.
- Motor power: 750 Watt.
- Food safety assured in accordance to European directives and UK legislation. In addition, materials in contact with food, are BPA-free.
- Product safety conform to European directives, UK legislation and international health and safety standards.

Included Accessories



- | | |
|---|------------|
| • 1 of Ejector for Vegetable Slicer | PNC 650232 |
| • 1 of Microtoothed blade rotor for 3,6lt Cutter Mixer | PNC 650233 |
| • 1 of Stainless steel bowl for 3,6lt Cutter Mixer | PNC 650235 |
| • 1 of Scraper for 3,6lt Cutter Mixer bowl | PNC 650236 |
| • 1 of Transparent lid for 3,6lt Cutter Mixer bowl with sealing and scraper | PNC 653862 |

Optional Accessories



- | | | |
|--|------------|--------------------------|
| • Cleaning tool for 5-8-10 mm dicing grids | PNC 650110 | ☐ |
| • Transparent lid for 2,6lt Cutter Mixer bowl | PNC 650117 | ☐ |
| • Transparent lid without sealing for 3,6lt Cutter Mixer bowl (1 speed models) | PNC 650118 | ☐ |
| • Kit including 3 discs dia. 175mm (slicer 2mm, slicer 5mm, grater 3mm) | PNC 650196 | ☐ |
| • Kit including 6 discs dia. 175mm (slicer 2mm, slicer 5mm, grater 3mm, grater 7mm, slicer 10mm, grid 10x10mm) | PNC 650197 | ☐ |
| • Stainless steel grating disc 2 mm (dia. 175mm) | PNC 650198 | ☐ |
| • Stainless steel grating disc 3 mm (dia. 175mm) | PNC 650199 | ☐ |
| • Stainless steel grating disc 4 mm (dia. 175mm) | PNC 650205 | ☐ |
| • Stainless steel grating disc 7 mm (dia. 175mm) | PNC 650207 | ☐ |
| • Parmesan Disc | PNC 650208 | ☐ |
| • Stainless steel shredding disc 2 mm (dia. 175mm) | PNC 650209 | ☐ |
| • Stainless steel shredding disc 4 mm (dia. 175mm) | PNC 650210 | ☐ |
| • Stainless steel shredding disc 8 mm for French fries (dia. 175mm) | PNC 650211 | ☐ |
| • Stainless steel slicing disc 1 mm (dia. 175mm) | PNC 650213 | ☐ |
| • Stainless steel slicing disc 2 mm (dia. 175mm) | PNC 650214 | ☐ |

- | | | |
|--|------------|--------------------------|
| • Stainless steel slicing disc 3 mm (dia. 175mm) | PNC 650215 | ☐ |
| • Stainless steel slicing disc 5 mm (dia. 175mm) | PNC 650216 | ☐ |
| • Stainless steel slicing disc 6 mm (dia. 175mm) | PNC 650217 | ☐ |
| • Stainless steel wavy slicing disc 3 mm (dia. 175mm) | PNC 650218 | ☐ |
| • Stainless steel wavy slicing disc 5 mm (dia. 175mm) | PNC 650219 | ☐ |
| • Aluminum slicing disc 8 mm (dia. 175mm) | PNC 650220 | ☐ |
| • Aluminum slicing disc 10 mm (dia. 175mm) | PNC 650221 | ☐ |
| • Dicing grid 8x8 (dia 175mm) | PNC 650222 | ☐ |
| • Dicing grid 10x10 (dia 175mm) | PNC 650223 | ☐ |
| • Dicing kit 8mm (aluminum slicer 8mm, grid 8x8mm) (dia. 175mm) | PNC 650224 | ☐ |
| • Dicing kit 10mm (aluminum slicer 10mm, grid 10x10 mm) (dia. 175mm) | PNC 650225 | ☐ |
| • Microtoothed blade rotor for 2,6lt Cutter Mixer | PNC 650226 | ☐ |
| • Smooth blade rotor for 2,6lt Cutter Mixer | PNC 650227 | ☐ |
| • Stainless steel bowl for 2,6lt Cutter Mixer | PNC 650228 | ☐ |
| • Transparent copolyester bowl for 2,6lt Cutter Mixer | PNC 650229 | ☐ |
| • Scraper for 2,6lt Cutter Mixer bowl | PNC 650230 | ☐ |
| • Stainless steel bowl for 2,6lt Cutter Mixer, microtoothed rotor, lid with scraper | PNC 650231 | ☐ |
| • Ejector for Vegetable Slicer | PNC 650232 | ☐ |
| • Microtoothed blade rotor for 3,6lt Cutter Mixer | PNC 650233 | ☐ |
| • Smooth blade rotor for 3,6lt Cutter Mixer | PNC 650234 | ☐ |
| • Stainless steel bowl for 3,6lt Cutter Mixer | PNC 650235 | ☐ |
| • Scraper for 3,6lt Cutter Mixer bowl | PNC 650236 | ☐ |
| • Stainless steel slicing disc 4 mm (dia. 175mm) | PNC 650237 | ☐ |
| • Transparent bowl for 2,6lt cutter mixer, microtoothed rotor, lid with scraper | PNC 650245 | ☐ |
| • Support for 1 disc, diam. 175mm and 205mm | PNC 653632 | ☐ |
| • Transparent lid for 3,6lt Cutter Mixer bowl with sealing and scraper | PNC 653862 | ☐ |
| • Stainless steel bowl for 3,6lt Cutter Mixer, microtoothed rotor, sealed lid with scraper | PNC 653864 | ☐ |

Front





Side



EI = Electrical inlet (power)

Top



Electric

Supply voltage:	220-240 V/1N ph/50/60 Hz
Electrical power max.:	0.75 kW
Total Watts:	0.75 kW

Capacity:

Performance (up to):	150 kg/hour
Capacity:	3.6 litres

Key Information:

External dimensions, Width:	348 mm
External dimensions, Depth:	315 mm
External dimensions, Height:	527 mm
Shipping weight:	ISO 9001; ISO 14001 kg