

Coffee System

TANGO STP DUO, 2 groups full-automatic machine

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



602553 (TANGOSTP2)

Full-automatic machine, 2 groups, 440x40 ml espresso cup/hr, 2x6,5 liter steam/coffee boiler, 2x1,7 kg coffee hopper

Short Form Specification

Item No. _____

The super automatic coffee machine Tango® STP Duo is the ideal equipment for the businesses as bars, coffee shops chains, and the hospitality industry for self-service breakfast, as well as company cafeteria. The Tango® unrivaled coffee extraction quality, together with the new milk delivery system, offers the perfect equipment to ease and succeed in the preparation of all milk based specialty coffee drinks, with heated or cold milk or foamed milk with a smooth texture.

The additional milk refrigerator Tango® STP Fridge, to be ordered separately, has a full compressor system which consistently maintains cold milk temperatures, with a 4L removable container. Cleaning and maintaining the milk circuit is automatically done thanks to its efficient rinsing and cleaning program.

Distributing, heating and foaming fresh milk to create delicious hot or cold drinks with milk or foamed milk: that's the challenge met by the super automatic Tango® STP Duo with efficiency and performance.

Main Features

- 2 coffee grinders (2 x 1,7 kg coffee hoppers).
- 2 groups full-automatic machine
- 2 x 6.5 liter steam/coffee boiler.
- Auto cleaning program.
- Distributing, heating and foaming fresh milk to create delicious hot or cold drinks with milk or foamed milk: that's the challenge met by the super automatic Tango® STP Duo with efficiency and performance.
- Exclusive Pump System for Cold & Hot Milk with foam pump technology.
- Programmable water and steam.
- The additional milk refrigerator Tango® STP Fridge has a full compressor system which consistently maintains cold milk temperatures, with a 4L removable container. Cleaning and maintaining the milk circuit is automatically done thanks to its efficient rinsing and cleaning program.
- The super automatic coffee machine Tango® STP Duo is the ideal equipment for the businesses as bars, coffee shops chains, and the hospitality industry for self-service breakfast, as well as company cafeteria.
- The Tango® unrivaled coffee extraction quality, together with the new milk delivery system, offers the perfect equipment to ease and succeed in the preparation of all milk based specialty coffee drinks, with heated or cold milk or foamed milk with a smooth texture.

Construction


- LCD Touchscreen.
- PID (proportional-integral-derivative) Temperature control: a precise controller algorithm system that gives consistency and accuracy to brewing temperature management system.

Optional Accessories


- | | | |
|--|------------|--------------------------|
| • Mixed hot water outlet for TANGO ST1 and STP | PNC 871020 | <input type="checkbox"/> |
| • TANGO hotel/breakfast service kit | PNC 871022 | <input type="checkbox"/> |
| • Coffee ground direct discharge chute | PNC 871023 | <input type="checkbox"/> |
| • Side milk refrigerator with exclusive pump system integrated with 9 liter capacity for TANGO STP | PNC 871025 | <input type="checkbox"/> |
| • Raised feet kit | PNC 871041 | <input type="checkbox"/> |

APPROVAL: _____


Front



Side



Top



Electric

Supply voltage:
 602553 (TANGOSTP2) 400 V/3N ph/50 Hz
 Electrical power max.: 5.2 kW
 Plug type: Cable without plug

Water:

Cold water temperature
 (min/max): 5 / 60 °C

Key Information:

External dimensions, Width: 603 mm
 External dimensions, Depth: 629 mm
 External dimensions, Height: 833 mm
 Net weight: 130 kg
 Shipping volume: 0.69 m³

Sustainability

Current consumption: 7.5 Amps