

Standard Preparation 700 mm Cupboard Sink with 1 Bowl & 1 Door



500x500mm and 1 hinged door, 700mm

### **Short Form Specification**

#### Item No.

Made entirely from stainless steel. Inner welded frame in stainless steel. Unique connection of panels to inner frame. The 50mm high worktop in 304 AISI stainless steel, 1mm in thickness, incorporates a layer of sound deadening material and has upturned edges. Upstand (h=100mm) with 8mm rounded edge. Sound-deadened hinged door. Base panel in 304 AISI stainless steel and height-adjustable intermediate shelf. Sink bowl in 304 AISI stainless steel with overflow pipe and drain hole. Mounted on feet, adjustable in height.

| ITEM #       |   |
|--------------|---|
| MODEL #      | _ |
| NAME #       | _ |
| <u>SIS #</u> |   |
| AIA #        | _ |
|              |   |

### Main Features

- Ideal for central positioning in the kitchen, either as island installation or back to back.
- Sturdiness, stability and reliability of table accurately tested.

### Construction

- Inner welded frame in stainless steel to guarantee superior strength and stability.
- Easy access to the cupboard interior on all lengths guaranteed by the use of only 2 doors.
- Reinforced side and base panel in 304 AISI stainless steel.
- 304 AISI stainless steel feet, 200 mm high and 54 mm in diameter, adjustable by -50/+30 mm.
- 100 mm upstand with 10 mm radioused corner and 13 mm deep, designed to be used against a wall.
- 50 mm worktop in 304 AISI stainless steel, 10/10 in thickness with overflow rim along the top.
- Hinged door with sound deadening internal panels, fitted with 304 AISI stainless steel hinges on the inner sides.
- Wide range of taps are available to suit every need.

## **Optional Accessories**

- Wheel kit for cupboards, 4 PNC 855299 wheels (2 with brakes), D=1000 mm
- Elbow operated mixer tap with PNC 855322 spout 3/4", single hole
- Elbow operated mixer tap with PNC 855323 short spout 3/4", single hole
- Foot operated mixer tap (hot PNC 855328 and cold) with spout 3/4"
- Single plastic drain syphon 2 PNC 895313 " for Sinks

#### APPROVAL:

Excelence

# Electrolux PROFESSIONAL





# Key Information:

| Cabinet width:               |              |
|------------------------------|--------------|
| 132817 (MLA716PN)            | 645 mm       |
| Cabinet depth:               | 645 mm       |
| Cabinet height:              | 380 mm       |
| External dimensions, Width:  | 700 mm       |
| External dimensions, Depth:  | 700 mm       |
| External dimensions, Height: | 1000 mm      |
| Upstand Dimensions, Height:  | 100 mm       |
| Upstand Dimensions, Depth:   | 13 mm        |
| Upstand Dimensions, Radius:  | R=10         |
| Bowls number                 | 1            |
| Bowl dimensions              | 500x500xH300 |
| Number and type of doors:    | 2 Hinged     |
| Worktop thickness:           | 50 mm        |
| Net weight:                  | 40 kg        |

#### Standard Preparation 700 mm Cupboard Sink with 1 Bowl & 1 Door

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.