



Modular Cooking Range Line 700XP One Well Freestanding Gas Fryer 15 liter

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____



371070 (E7FRGD1GF0)

15-lt gas Fryer free standing
with 1 "V" shape well
(external burners), 1 basket
and lid included

Short Form Specification

Item No.

To be installed on height adjustable feet in stainless steel. Two high efficiency 7 kW burners in stainless steel. Suitable for natural gas or LPG. Deep drawn V-shaped well. Oil drains through a tap into a container under the well. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on 50mm height adjustable feet in stainless steel.
- Deep drawn V-Shaped well.
- Two high efficiency 7 kW burners in stainless steel with flame failure device attached to the outside of the well.
- Thermostatic regulation of oil temperature up to a maximum of 185 °C.
- Flame failure device on each burner.
- Overheat protection thermostat as standard on all units.
- Oil drains through a tap into a drainage container positioned under the well.
- All major compartments located in front of unit for ease of maintenance.
- Piezo spark ignition for added safety.
- Gas appliance supplied for use with natural or LPG gas, conversion jets supplied as standard.
- IPx4 water protection.
- Optional portable oil quality monitoring tool (code 9B8081) for efficient oil management.

Construction

- Interior of well with rounded corners for ease of cleaning.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Included Accessories

- 1 of Door for open base cupboard PNC 206350
- 1 of 1 full size basket for 14/15lt fryers PNC 921691

Optional Accessories

- Junction sealing kit PNC 206086 ☐
- Draught diverter, 120 mm diameter PNC 206126 ☐
- Matching ring for flue condenser, 120 mm diameter PNC 206127 ☐
- Flanged feet kit PNC 206136 ☐
- Frontal kicking strip for concrete installation, 400mm PNC 206147 ☐
- Frontal kicking strip for concrete installation, 800mm PNC 206148 ☐
- Frontal kicking strip for concrete installation, 1000mm PNC 206150 ☐

APPROVAL: _____



Experience the Excellence
www.electroluxprofessional.com

• Frontal kicking strip for concrete installation, 1200mm	PNC 206151	☐	• Deflector for floured products for 15lt fryers	PNC 921696	☐
• Frontal kicking strip for concrete installation, 1600mm	PNC 206152	☐	• Pressure regulator for gas units	PNC 927225	☐
• Frontal kicking strip, 400mm (not for refr-freezer base)	PNC 206175	☐			
• Frontal kicking strip, 800mm (not for refr-freezer base)	PNC 206176	☐			
• Frontal kicking strip, 1000mm (not for refr-freezer base)	PNC 206177	☐			
• Frontal kicking strip, 1200mm (not for refr-freezer base)	PNC 206178	☐			
• Frontal kicking strip, 1600mm (not for refr-freezer base)	PNC 206179	☐			
• Kit 4 feet for concrete installation (not for 900 line free standing grill)	PNC 206210	☐			
• Sediment tray for 15lt fryers	PNC 206235	☐			
• Pair of side kicking strips	PNC 206249	☐			
• Pair of side kicking strips for concrete installation	PNC 206265	☐			
• Oil drain pipe for 15lt free standing fryer	PNC 206301	☐			
• Chimney upstand, 400mm	PNC 206303	☐			
• Right and left side handrails	PNC 206307	☐			
• Back handrail 800 mm	PNC 206308	☐			
• Flue condenser for 1/2 module, 120 mm diameter	PNC 206310	☐			
• Door for open base cupboard	PNC 206350	☐			
• Base support for feet or wheels - 400mm (700/900)	PNC 206366	☐			
• Base support for feet or wheels - 800mm (700/900)	PNC 206367	☐			
• Base support for feet or wheels - 1200mm (700/900)	PNC 206368	☐			
• Base support for feet or wheels - 1600mm (700/900)	PNC 206369	☐			
• Base support for feet or wheels - 2000mm (700/900)	PNC 206370	☐			
• Rear paneling - 600mm (700/900XP)	PNC 206373	☐			
• Rear paneling - 800mm (700/900)	PNC 206374	☐			
• Rear paneling - 1000mm (700/900)	PNC 206375	☐			
• Rear paneling - 1200mm (700/900)	PNC 206376	☐			
• Chimney grid net, 400mm (700XP/900)	PNC 206400	☐			
• Base support for feet or wheels - 600mm (700/900)	PNC 206431	☐			
• Kit G.25.3 (NI) gas nozzles for 900 fryers	PNC 206467	☐			
• 2 side covering panels for free standing appliances	PNC 216000	☐			
• 1 full size basket for 14/15lt fryers	PNC 921691	☐			
• 2 half size baskets for 14/15lt fryers	PNC 921692	☐			
• Filter for fryer oil collection basin for 7lt, 14lt, 15lt free standing fryers	PNC 921693	☐			
• Unclogging rod for 15lt fryers drainage pipe	PNC 921695	☐			

Front



Side



EQ = Equipotential screw
 G = Gas connection

Top



Gas

Gas Power:	14 kW
Standard gas delivery:	Natural Gas G20 (20mbar)
Gas Type Option:	LPG; Natural Gas
Gas Inlet:	1/2"

Key Information:

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Usable well dimensions (width):	240 mm
Usable well dimensions (height):	505 mm
Usable well dimensions (depth):	380 mm
Well capacity:	13 lt MIN; 15 lt MAX
Thermostat Range:	105 °C MIN; 185 °C MAX
Net weight:	55 kg
Shipping weight:	58 kg
Shipping height:	1140 mm
Shipping width:	460 mm
Shipping depth:	820 mm
Shipping volume:	0.43 m ³
Certification group:	N7FG