

Modular Cooking Range Line 700XP One Well Freestanding Gas Fryer 7 liter

| ITEM # | |
|---------|--|
| MODEL # | |
| NAME # | |
| SIS # | |
| AIA # | |



371068 (E7FRGD1BF0)

7-It gas Fryer free standing with 1 "V" shape well (external burners), 1 basket and lid included

Short Form Specification

Item No.

To be installed on height adjustable feet in stainless steel. High efficiency 7 kW burners in stainless steel. Suitable for natural gas or LPG. Deep drawn V-shaped well. Oil drains through a tap into a container under the well. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on 50mm height adjustable feet in stainless steel.
- Deep drawn V-Shaped well.
- High efficiency 7 kW burners in stainless steel with flame failure device attached to the outside of the well.
- Thermostatic regulation of oil temperature up to a maximum of 185 °C.
- Flame failure device on each burner.
- Overheat protection thermostat as standard on all units.
- Oil drains through a tap into a drainage container positioned under the well.
- All major compartments located in front of unit for ease of maintenance.
- Piezo spark ignition for added safety.
- Gas appliance supplied for use with natural or LPG gas, conversion jets supplied as standard.
- IPx4 water protection.
- Optional portable oil quality monitoring tool (code 9B8081) for efficient oil management.

Construction

- Interior of well with rounded corners for ease of cleaning.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Sustainability



This model is compliant with Swiss Energy Efficiency Ordinance (730.02).

Included Accessories

• 1 of Door for open base PNC 206350 cupboard

 1 of Basket for 7lt top and free PNC 921608 standing fryers

Optional Accessories

concrete installation, 400mm

Junction sealing kit
 Draught diverter, 120 mm diameter
 Matching ring for flue condenser, 120 mm diameter
 Flanged feet kit
 Frontal kicking strip for
 PNC 206126 □
 PNC 206127 □
 PNC 206136 □
 PNC 206147 □

APPROVAL:






Modular Cooking Range Line 700XP One Well Freestanding Gas Fryer 7 liter


| Frontal kicking strip for concrete installation, 800mm | PNC 206148 | | Pressure regulator for gas units | PNC 927225 | |
|---|-------------|---|----------------------------------|------------|--|
| Frontal kicking strip for concrete installation, 1000mm | PNC 206150 | | | | |
| Frontal kicking strip for concrete installation, 1200mm | PNC 206151 | | | | |
| Frontal kicking strip for concrete installation, 1600mm | PNC 206152 | | | | |
| • Frontal kicking strip, 400mm (not for refr-freezer base) | PNC 206175 | | | | |
| • Frontal kicking strip, 800mm (not for refr-freezer base) | PNC 206176 | | | | |
| Frontal kicking strip, 1000mm (not for refr-freezer base) | PNC 206177 | | | | |
| Frontal kicking strip, 1200mm (not for refr-freezer base) | PNC 206178 | | | | |
| Frontal kicking strip, 1600mm (not for refr-freezer base) | PNC 206179 | | | | |
| Kit 4 feet for concrete installation (not for 900 line free standing grill) | PNC 206210 | | | | |
| Pair of side kicking strips | PNC 206249 | | | | |
| Pair of side kicking strips for | PNC 206265 | | | | |
| concrete installation • Chimney upstand, 400mm | PNC 206303 | | | | |
| · · · · · · · · · · · · · · · · · · · | | | | | |
| Right and left side handrails | PNC 206307 | | | | |
| Back handrail 800 mm | PNC 206308 | | | | |
| Flue condenser for 1/2 module, 120 mm diameter | PNC 206310 | | | | |
| Door for open base cupboard | PNC 206350 | | | | |
| Base support for feet or wheels - 400mm (700/900) | PNC 206366 | | | | |
| Base support for feet or wheels - 800mm (700/900) | PNC 206367 | | | | |
| Base support for feet or wheels - 1200mm (700/900) | PNC 206368 | | | | |
| Base support for feet or wheels - 1600mm (700/900) | PNC 206369 | | | | |
| Base support for feet or wheels - 2000mm (700/900) | PNC 206370 | | | | |
| Rear paneling - 600mm (700/900XP) | PNC 206373 | | | | |
| Rear paneling - 800mm (700/900) | PNC 206374 | | | | |
| • Rear paneling - 1000mm (700/900) | PNC 206375 | | | | |
| • Rear paneling - 1200mm (700/900) | PNC 206376 | | | | |
| • Kit town gas nozzles (G150) for 700 | PNC 206389 | | | | |
| grill | 1110 200507 | _ | | | |
| • Chimney grid net, 400mm (700XP/900) | PNC 206400 | | | | |
| Base support for feet or wheels - 600mm (700/900) | PNC 206431 | | | | |
| Kit G.25.3 (NI) gas nozzles for 900 fryers | PNC 206467 | | | | |
| 2 side covering panels for free standing appliances | PNC 216000 | | | | |
| Basket for 7lt top and free standing fryers | PNC 921608 | | | | |
| • Filter for fryer oil collection basin for 7lt, 14lt, 15lt free standing fryers | PNC 921693 | | | | |






Modular Cooking Range Line 700XP One Well Freestanding Gas Fryer 7 liter





EQ = Equipotential screw
G = Gas connection



Gas

Gas Power:

371068 (E7FRGD1BF0) 7 kW

Standard gas delivery: Natural Gas G20 (20mbar)

Gas Type Option: LPG; Natural Gas

Gas Inlet: 1/2"

LPG Gas Pressure: 11" w.c. (27.7 mbar)

Key Information:

Usable well dimensions

(width): 240 mm

Usable well dimensions

(height): 235 mm

Usable well dimensions

(depth): 380 mm

Well capacity: 5.5 It MIN; 7 It MAX
Thermostat Range: 105 °C MIN; 185 °C MAX

Net weight:40 kgShipping weight:48 kgShipping height:1120 mmShipping width:460 mmShipping depth:820 mmShipping volume:0.42 m³

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat

insulation fitted.

Certification group: N7FG