

# Modular Cooking Range Line 700XP Half Module Freestanding Gas Char-Grill

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



371237 (E7GRGDGCFU)

Half module gas Grill free standing

# **Short Form Specification**

### Item No.

To be installed on height adjustable feet in stainless steel. High efficiency 8 kW stainless steel gas burners with flame failure device, protected by deflection trays. Suitable for natural gas or LPG. Cooking surface grids in enameled cast iron, easily removable for cleaning. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

## **Main Features**

- Stainless steel burners with flame failure device.
- Burners are protected by deflection trays to prevent fat dripping on them.
- Stainless steel high splash guard on the rear and sides can be easily removed for cleaning and is dishwasher-safe.
- Unit delivered with four 50 mm legs in stainless steel as standard (all round Stainless steel kick plates as option).
- The low temperature of the external panels allow to work in safety.
- Cooking grids made in highly resistant enameled cast iron for easy cleaning.

#### Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- IPx4 water protection.

APPROVAL:





# Modular Cooking Range Line 700XP Half Module Freestanding Gas Char-Grill

Included Accessories		
• 1 of Scraper for free standing grills	PNC 206422	
Optional Accessories		
<ul> <li>Junction sealing kit</li> </ul>	PNC 206086	
<ul> <li>Draught diverter, 120 mm diameter</li> </ul>	PNC 206126	
<ul> <li>Matching ring for flue condenser, 120 mm diameter</li> </ul>	PNC 206127	
<ul> <li>Kit 4 wheels - 2 swivelling with brake - it is mandatory to install Base support and wheels</li> </ul>		
<ul> <li>Flanged feet kit</li> </ul>	PNC 206136	
<ul> <li>Frontal kicking strip for concrete installation, 400mm</li> </ul>	PNC 206147	
<ul> <li>Frontal kicking strip for concrete installation, 800mm</li> </ul>	PNC 206148	
<ul> <li>Frontal kicking strip for concrete installation, 1000mm</li> </ul>	PNC 206150	
<ul> <li>Frontal kicking strip for concrete installation, 1200mm</li> </ul>	PNC 206151	
<ul> <li>Frontal kicking strip for concrete installation, 1600mm</li> </ul>	PNC 206152	
<ul> <li>Frontal kicking strip, 400mm (not for refr-freezer base)</li> </ul>	PNC 206175	
<ul> <li>Frontal kicking strip, 800mm (not for refr-freezer base)</li> </ul>	PNC 206176	
• Frontal kicking strip, 1000mm (not for refr-freezer base)	PNC 206177	
• Frontal kicking strip, 1200mm (not for refr-freezer base)	PNC 206178	
• Frontal kicking strip, 1600mm (not for refr-freezer base)	PNC 206179	
<ul> <li>Kit 4 feet for concrete installation (not for 900 line free standing grill)</li> </ul>	PNC 206210	
<ul> <li>Pair of side kicking strips</li> </ul>	PNC 206249	
<ul> <li>Pair of side kicking strips for concrete installation</li> </ul>	PNC 206265	
<ul> <li>Chimney upstand, 400mm</li> </ul>	PNC 206303	
<ul> <li>Right and left side handrails</li> </ul>	PNC 206307	
<ul> <li>Back handrail 800 mm</li> </ul>	PNC 206308	
<ul> <li>Flue condenser for 1/2 module, 120 mm diameter</li> </ul>	PNC 206310	
Base support for feet or wheels - 400mm (700/900)	PNC 206366	
Base support for feet or wheels - 800mm (700/900)	PNC 206367	
Base support for feet or wheels - 1200mm (700/900)	PNC 206368	
Base support for feet or wheels - 1600mm (700/900)	PNC 206369	
Base support for feet or wheels - 2000mm (700/900)	PNC 206370	
• Rear paneling - 600mm (700/900XP)	PNC 206373	
• Rear paneling - 800mm (700/900)	PNC 206374	
• Rear paneling - 1000mm (700/900)	PNC 206375	
• Rear paneling - 1200mm (700/900)	PNC 206376	
<ul> <li>4 wheels, 2 swivelling with brake (700/900). It is mandatory to install with base supports for feet/wheels</li> </ul>	PNC 206382	
<ul><li>UK</li><li>Kit town gas nozzles (G150) for 700</li></ul>	PNC 206389	


<ul> <li>Stainless steel grids for free standing wide grills (700XP)</li> </ul>	PNC 206414	
Stainless steel grids with drain shape for free standing wide top grills (700XP)	PNC 206415	
<ul> <li>Scraper for grids with drainage channels - top grills</li> </ul>	PNC 206421	
<ul> <li>Scraper for free standing grills</li> </ul>	PNC 206422	
<ul> <li>Base support for feet or wheels - 600mm (700/900)</li> </ul>	PNC 206431	
• Kit G.25.3 (NI) gas nozzles for 700 and 900 gas grills (standard and HP)	PNC 206462	
• 2 side covering panels for free standing appliances	PNC 216000	
• Frontal handrail, 400mm	PNC 216046	
<ul> <li>Frontal handrail, 800mm</li> </ul>	PNC 216047	
<ul> <li>Frontal handrail, 1200mm</li> </ul>	PNC 216049	
<ul> <li>Frontal handrail, 1600mm</li> </ul>	PNC 216050	
<ul> <li>Large handrail - portioning shelf, 400mm</li> </ul>	PNC 216185	
<ul> <li>Large handrail - portioning shelf, 800mm</li> </ul>	PNC 216186	
<ul> <li>Pressure regulator for gas units</li> </ul>	PNC 927225	



grill



# Modular Cooking Range Line 700XP Half Module Freestanding Gas Char-Grill



## Gas

Gas Power:

**371237 (E7GRGDGCFU)** 8 kW

Standard gas delivery: Natural Gas G20 (20mbar)

Gas Type Option: LPG;Town
Gas Inlet: 3/4"

## **Key Information:**

Cooking surface width: 316 mm Cooking surface depth: 478 mm Net weight: 40 kg Shipping weight: 57 kg Shipping height: 1180 mm Shipping width: 460 mm Shipping depth: 810 mm Shipping volume: 0.44 m<sup>3</sup>

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat

insulation fitted.

Certification group: N7GG

