

Modular Cooking Range Line 700XP 4- Hot Round Plates Electric Boiling Top on Electric Oven - Marine

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA#	
71171	



371148 (E7ECMH4RE5)

4-Hot Plate (2,6 kW each) electric Range on electric Oven (6 kW) - marine

Short Form Specification

Item No.

To be installed on stainless steel feet with height adjustment up to 50 mm. Four 2.6 kW cast-iron hot plates hermetically sealed to the one-piece top. Stainless steel oven chamber with 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans). Ribbed oven base plate. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- The four round 2.6kW cast-iron plates are hermtically sealed to the one-piece top.
- Base compartment consists of an electric standard oven with thick oven door for heat insulation, positioned beneath the base plate.
- Electric oven to have separate thermostats for top and bottom heating elements.
- Stainless steel oven chamber with 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans).
- Ribbed enamelled steel oven base plate.
- The special design of the control knob system guarantees against water infiltration.
- IPx4 water protection.
- Oven thermostat adjustable from 100 °C to 300 °C.

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Included Accessories

 1 of GN2/1 chrome grid for static PNC 164250 oven

Optional Accessories

• Pair of side kicking strips for

concrete installation

 GN2/1 chrome grid for static oven 	PNC 164250	
Junction sealing kit	PNC 206086	
 Kit 4 wheels - 2 swivelling with brake - it is mandatory to install Base support and wheels 	PNC 206135	
 Flanged feet kit 	PNC 206136	
• Frontal kicking strip for concrete installation, 800mm	PNC 206148	
 Frontal kicking strip for concrete installation, 1200mm 	PNC 206151	
• Frontal kicking strip for concrete installation, 1600mm	PNC 206152	
• Frontal kicking strip, 800mm (not for refr-freezer base)	PNC 206176	
• Frontal kicking strip, 1000mm (not for refr-freezer base)	PNC 206177	
• Frontal kicking strip, 1200mm (not for refr-freezer base)	PNC 206178	
• Frontal kicking strip, 1600mm (not for refr-freezer base)	PNC 206179	
Kit 4 feet for concrete installation (not for 900 line free standing grill)	PNC 206210	
Pair of side kicking strips	PNC 206249	· 🗆

PNC 206265 🗆

APPROVAL:





Modular Cooking Range Line 700XP 4- Hot Round Plates Electric Boiling Top on Electric Oven - Marine

Water column with swivel arm (water column extension not included)	PNC 206289	
• Water column extension for 700 line	PNC 206291	
Right and left side handrails	PNC 206307	
Back handrail 800 mm	PNC 206308	
Back handrail 1200 mm	PNC 206309	
 Base support for feet or wheels - 800mm (700/900) 	PNC 206367	
 Base support for feet or wheels - 1200mm (700/900) 	PNC 206368	
 Base support for feet or wheels - 1600mm (700/900) 	PNC 206369	
 Base support for feet or wheels - 2000mm (700/900) 	PNC 206370	
• Rear paneling - 800mm (700/900)	PNC 206374	
• Rear paneling - 1000mm (700/900)	PNC 206375	
• Rear paneling - 1200mm (700/900)	PNC 206376	
 Chimney grid net, 400mm (700XP/900) 	PNC 206400	
 2 side covering panels for free standing appliances 	PNC 216000	
• Frontal handrail, 800mm	PNC 216047	
• Frontal handrail, 1200mm	PNC 216049	
• Frontal handrail, 1600mm	PNC 216050	
 Large handrail - portioning shelf, 800mm 	PNC 216186	





Modular Cooking Range Line 700XP 4- Hot Round Plates Electric Boiling Top on Electric Oven - Marine


Front 31 1/2 " 800 mm **.**@@@@@@ 35 3/4 " 908 mm ΕQ ΕI 1 7/8 " 48 mm 1 7/16 " 37 mm 2 3/16 27 1/16 2 3/16 " 56 mm 688 mm 56 mm

Side


Front Plates dimensions:

Back Plates dimensions:

Waterproof index:



EI = Electrical inlet (power)
EQ = Equipotential screw





Electric 400 V/3 ph/50/60 Hz Supply voltage: Electrical power, max: 16.4 kW **Key Information:** Oven Heat Input: 6 kW Oven working Temperature: 100 °C MIN; 300 °C MAX **Oven Cavity Dimensions** (width): 540 mm **Oven Cavity Dimensions** 300 mm (height): Oven Cavity Dimensions 650 mm (depth): External dimensions, Width: 800 mm External dimensions, Depth: 730 mm External dimensions, Height: 850 mm Net weight: 80 kg Certification group: N7CE1 Front Plates Power: 2.6 - 2.6 kW **Back Plates Power:** 2.6 - 2.6 kW

Ø 230 Ø 230

Ø 230 Ø 230

IPX4

Modular Cooking Range Line 700XP 4- Hot Round Plates Electric Boiling Top on Electric Overne