

Modular Cooking Range Line 700XP 4- Hot Round Plates Electric Boiling Top on Electric Oven - Marine

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA#	
71171	



371148 (E7ECMH4RE5)

4-Hot Plate (2,6 kW each) electric Range on electric Oven (6 kW) - marine

Short Form Specification

Item No.

To be installed on stainless steel feet with height adjustment up to 50 mm. Four 2.6 kW cast-iron hot plates hermetically sealed to the one-piece top. Stainless steel oven chamber with 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans). Ribbed oven base plate. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- The four round 2.6kW cast-iron plates are hermtically sealed to the one-piece top.
- Base compartment consists of an electric standard oven with thick oven door for heat insulation, positioned beneath the base plate.
- Electric oven to have separate thermostats for top and bottom heating elements.
- Stainless steel oven chamber with 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans).
- Ribbed enamelled steel oven base plate.
- The special design of the control knob system guarantees against water infiltration.
- IPx4 water protection.
- Oven thermostat adjustable from 100 °C to 300 °C.

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Included Accessories

 1 of GN2/1 chrome grid for static PNC 164250 oven

Optional Accessories

• Pair of side kicking strips for

concrete installation

 GN2/1 chrome grid for static oven 	PNC 164250	
Junction sealing kit	PNC 206086	
 Kit 4 wheels - 2 swivelling with brake - it is mandatory to install Base support and wheels 	PNC 206135	
 Flanged feet kit 	PNC 206136	
• Frontal kicking strip for concrete installation, 800mm	PNC 206148	
 Frontal kicking strip for concrete installation, 1200mm 	PNC 206151	
• Frontal kicking strip for concrete installation, 1600mm	PNC 206152	
• Frontal kicking strip, 800mm (not for refr-freezer base)	PNC 206176	
• Frontal kicking strip, 1000mm (not for refr-freezer base)	PNC 206177	
• Frontal kicking strip, 1200mm (not for refr-freezer base)	PNC 206178	
• Frontal kicking strip, 1600mm (not for refr-freezer base)	PNC 206179	
Kit 4 feet for concrete installation (not for 900 line free standing grill)	PNC 206210	
Pair of side kicking strips	PNC 206249	· 🗆

PNC 206265 🗆

APPROVAL:





Modular Cooking Range Line 700XP 4- Hot Round Plates Electric Boiling Top on Electric Oven - Marine

•	Water column with swivel arm (water column extension not included)	PNC 206289	
•	Water column extension for 700 line	PNC 206291	
•	Right and left side handrails	PNC 206307	
•	Back handrail 800 mm	PNC 206308	
•	Back handrail 1200 mm	PNC 206309	
•	Base support for feet or wheels - 800mm (700/900)	PNC 206367	
•	Base support for feet or wheels - 1200mm (700/900)	PNC 206368	
•	Base support for feet or wheels - 1600mm (700/900)	PNC 206369	
•	Base support for feet or wheels - 2000mm (700/900)	PNC 206370	
•	Rear paneling - 800mm (700/900)	PNC 206374	
•	Rear paneling - 1000mm (700/900)	PNC 206375	
•	Rear paneling - 1200mm (700/900)	PNC 206376	
•	Chimney grid net, 400mm (700XP/900)	PNC 206400	
•	2 side covering panels for free standing appliances	PNC 216000	
•	Frontal handrail, 800mm	PNC 216047	
•	Frontal handrail, 1200mm	PNC 216049	
•	Frontal handrail, 1600mm	PNC 216050	
•	Large handrail - portioning shelf, 800mm	PNC 216186	





Modular Cooking Range Line 700XP 4- Hot Round Plates Electric Boiling Top on Electric Oven - Marine

Front 31 1/2 " 800 mm **.**@@@@@@ 35 3/4 " 908 mm ΕQ ΕI 1 7/8 " 48 mm 1 7/16 " 37 mm 2 3/16 27 1/16 2 3/16 " 56 mm 688 mm 56 mm


Side

Back Plates dimensions:

Waterproof index:

28 mm 28 3/4 " 730 mm E 33 1/2 " 820 ΈI 13 1/16 " 5 7/8 1 150 mm 332 mm EQ 20 3/16 " 3 9/16 " 20 1/16 " 3 15/16 " 90 mm 510 mm 100 mm 27 9/16 " 43 11/16

EI = Electrical inlet (power)
EQ = Equipotential screw





Electric 400 V/3 ph/50/60 Hz Supply voltage: Electrical power, max: 16.4 kW **Key Information:** Oven Heat Input: 6 kW Oven working Temperature: 100 °C MIN; 300 °C MAX **Oven Cavity Dimensions** (width): 540 mm **Oven Cavity Dimensions** 300 mm (height): Oven Cavity Dimensions 650 mm (depth): External dimensions, Width: 800 mm External dimensions, Depth: 730 mm External dimensions, Height: 850 mm Net weight: 80 kg Certification group: N7CE1 Front Plates Power: 2.6 - 2.6 kW **Back Plates Power:** 2.6 - 2.6 kW Front Plates dimensions: Ø 230 Ø 230

Ø 230 Ø 230

IPX4

Modular Cooking Range Line 700XP 4- Hot Round Plates Electric Boiling Top on Electric Overi-