

Modular Cooking Range Line 700XP 4-Hot Square Plates Electric Boiling Top Electric Oven - Marine

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



371150 (E7ECMH4QE5)

4-Hot Square Plate (2,6 kW each) electric Range on electric Oven (6 kW) - marine

Short Form Specification

Item No.

To be installed on stainless steel feet with height adjustment up to 50 mm. Four 2.6 kW square cast-iron hot plates hermetically sealed to the one-piece top. Stainless steel oven chamber with 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans). Ribbed oven base plate. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- The four 2.6kW cast-iron square plates are hermtically sealed to the one-piece top.
- Base compartment consists of an electric standard oven with thick oven door for heat insulation, positioned beneath the base plate.
- Electric oven to have separate thermostats for top and bottom heating elements.
- Stainless steel oven chamber with 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans).
- Ribbed enamelled steel oven base plate.
- The special design of the control knob system guarantees against water infiltration.
- IPx4 water protection.
- Oven thermostat adjustable from 100 °C to 300 °C.

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Included Accessories

• 1 of GN2/1 chrome grid for static PNC 164250

Optional Accessories

for refr-freezer base)

for refr-freezer base)

GN2/1 chrome grid for static oven	PNC 164250 🗖
 Junction sealing kit 	PNC 206086 🗖
 Kit 4 wheels - 2 swivelling with brake - it is mandatory to insta Base support and wheels 	PNC 206135 🗖
 Flanged feet kit 	PNC 206136 🚨
 Frontal kicking strip for concret installation, 800mm 	e PNC 206148 🗆
 Frontal kicking strip for concret installation, 1200mm 	e PNC 206151 🗖
 Frontal kicking strip for concret installation, 1600mm 	e PNC 206152 🗖
• 2 cast iron plate bars for electr cooking top	ic PNC 206168 🗖
• Frontal kicking strip, 800mm (no for refr-freezer base)	ot PNC 206176 🗅
• Frontal kicking strip, 1000mm (r for refr-freezer base)	not PNC 206177 🗅
• Frontal kicking strip, 1200mm (n	not PNC 206178 🔲

• Frontal kicking strip, 1600mm (not PNC 206179 🚨

APPROVAL:





Modular Cooking Range Line 700XP 4-Hot Square Plates Electric Boiling Top Electric Oven - Marine


Kit 4 feet for concrete installation	PNC 206210	П
(not for 900 line free standing grill)		
 Pair of side kicking strips 	PNC 206249	
Pair of side kicking strips for concrete installation	PNC 206265	
Water column with swivel arm (water)	PNC 206289	П
column extension not included)	FINC 200209	_
• Water column extension for 700 line	PNC 206291	
 Right and left side handrails 	PNC 206307	
Back handrail 800 mm	PNC 206308	
• Base support for feet or wheels - 800mm (700/900)	PNC 206367	
• Base support for feet or wheels - 1200mm (700/900)	PNC 206368	
 Base support for feet or wheels - 1600mm (700/900) 	PNC 206369	
 Base support for feet or wheels - 2000mm (700/900) 	PNC 206370	
• Rear paneling - 800mm (700/900)	PNC 206374	
• Rear paneling - 1000mm (700/900)	PNC 206375	
• Rear paneling - 1200mm (700/900)	PNC 206376	
 Chimney grid net, 400mm (700XP/900) 	PNC 206400	
 2 side covering panels for free standing appliances 	PNC 216000	
• Frontal handrail, 800mm	PNC 216047	
• Frontal handrail, 1200mm	PNC 216049	
• Frontal handrail, 1600mm	PNC 216050	
 Large handrail - portioning shelf, 800mm 	PNC 216186	
 Full size basket (220x350x240) for pasta cookers - 700XP and EMPower 	PNC 921611	






Modular Cooking Range Line 700XP 4-Hot Square Plates Electric Boiling Top Electric Oven - Marine

Front 31 1/2 " 800 mm ₩₩ **@** 908 mm 35 3/4 ΕQ EI 1 7/8 ' 48 mm 1 7/16 " 37 mm 2 3/16 27 1/16 " 3/16 " 56 mm 688 mm 56 mm Side



Electrical inlet (power)

EQ



Electric

Supply voltage: 400 V/3 ph/50/60 Hz

Electrical power, max: 16.4 kW

Key Information:

Oven Heat Input: 6 kW

Oven working Temperature: 100 °C MIN; 300 °C MAX

Oven Cavity Dimensions

(width): 540 mm

Oven Cavity Dimensions

(height): 300 mm

Oven Cavity Dimensions

(depth):650 mmExternal dimensions, Width:800 mmExternal dimensions, Depth:730 mmExternal dimensions, Height:850 mm

External dimensions, Height:
Net weight:
Certification group:

Front Plates Power:
Back Plates Power:
Front Plates dimensions:
Back Plates dimensions:

2.6 - 2.6 kW 2.6 - 2.6 kW 230x230 230x230 230x230 230x230

80 kg

N7CE1

Waterproof index: IPX4

