

Modular Cooking Range Line 700XP 4-Burner Gas Range on Electric Oven

TEM #	
MODEL #	
NAME #	
SIS #	
AIA#	



371003 (E7GCGH4CE0)

4-Burner (5,5 kW each) gas Range on electric Oven (6 kW)

371125 (E7GCGH4CEN)

4-Burner (5,5 kW each) gas Range on electric Oven (6 kW)

Short Form Specification

Item No.

To be installed on stainless steel feet with height adjustment up to 50 mm. High efficiency flower flame burners with flame regulator and protected pilot light. Flame failure device as standard on burners to protect against accidental extinguishing. Stainless steel oven chamber with 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans). Ribbed oven base plate. Exterior panels in stainless steel with Scotch Brite finish. Pan supports in heavy duty cast iron. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to have stainless steel feet with height adjustment up to 50 mm.
- The four 5.5 kW high efficiency flower flame burners allow the flame to adapt to different size pans.
- Gas appliance supplied for use with natural or LPG gas, conversion jets supplied as standard.
- Large sized pan support in cast iron (stainless steel as option) with long center fins to allow the use of the largest down to the smallest pans.
- Pan supports in cast iron are washable in a dishwasher.
- Burners to feature flame regulator.
- Flame failure device on each burner protects against gas leakage when accidental extinguishing of the flame occurs.
- Protected pilot light.
- Base compartment consists of an electric standard oven positioned beneath the base plate. Stainless steel oven chamber to have 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans) and ribbed enamelled steel base plate.
- Oven thermostat adjustable from 140 °C to 300 °C.
- Double skinned door with pressed internal panel for heat insulation.
- IPx4 water protection.
- Control knobs provide smooth, continuous rotation from min to max power level.

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Included Accessories

• 1 of GN2/1 chrome grid for PNC 164250 static oven

Optional Accessories

- GN2/1 chrome grid for static oven
 NC 164250 □
 NC 204084 □
- Junction sealing kit
 Draught diverter, 150 mm diameter
 PNC 206086 □
 PNC 206132 □
- Matching ring for flue PNC 206133 ☐ condenser, 150 mm diameter

APPROVAL:





Modular Cooking Range Line 700XP 4-Burner Gas Range on Electric Oven


 Kit 4 wheels - 2 swivelling with brake - it is mandatory to install 	PNC 206135		gas range (only for 371003)	PNC 206387	
Base support and wheels	PNC 206136		 Chimney grid net, 500mm (700XP/900) 	PNC 206402	
Flanged feet kit Frankel kieling abuin fan aan avake			·	PNC 206460	
Frontal kicking strip for concrete installation, 800mm	PNC 206148		top and - freestanding on oven - gas cookers	1110 200 100	_
 Frontal kicking strip for concrete installation, 1000mm 	PNC 206150		• 2 side covering panels for free	PNC 216000	
 Frontal kicking strip for concrete installation, 1200mm 	PNC 206151		·	PNC 216047	
 Frontal kicking strip for concrete installation, 1600mm 	PNC 206152		•	PNC 216049 PNC 216050	
 Frontal kicking strip, 800mm (not for refr-freezer base) 	PNC 206176		, , , , , , , , , , , , , , , , , , ,	PNC 216186	
 Frontal kicking strip, 1000mm (not for refr-freezer base) 	PNC 206177		Stainless steel universal frying pan with stainless steel handle (diam.	PNC 653596	
 Frontal kicking strip, 1200mm (not for refr-freezer base) 	PNC 206178		200mm) suitable for induction and all other heating sources (only for		
 Frontal kicking strip, 1600mm (not for refr-freezer base) 	PNC 206179		371125)	PNC 653598	
Kit 4 feet for concrete installation (not for 900 line free standing grill)	PNC 206210		steel handle (diam. 280mm) suitable for induction and all other heating		
Flue condenser for 1 module, 150 mm diameter	PNC 206246		sources (only for 371003)		
Pair of side kicking strips	PNC 206249				
<u> </u>	PNC 206260				
 Single burner smooth plate for direct cooking - fits frontal burners only 	PNC 200200	_			
 Single burner ribbed plate for direct cooking- fits frontal burners only 	PNC 206261				
 Single burner radiant plate for pan support 	PNC 206264				
 Pair of side kicking strips for concrete installation 	PNC 206265				
 Water column with swivel arm (water column extension not included) 	PNC 206289				
• Water column extension for 700 line	PNC 206291				
 Stainless steel double grid for 2 burners 	PNC 206297				
 Chimney upstand, 800mm 	PNC 206304				
 Right and left side handrails 	PNC 206307				
Back handrail 800 mm	PNC 206308				
 Wok pan support for open burners (700/900) 	PNC 206363				
 Base support for feet or wheels - 400mm (700/900) (only for 371125) 	PNC 206366				
 Base support for feet or wheels - 800mm (700/900) 	PNC 206367				
Base support for feet or wheels - 1200mm (700/900)	PNC 206368				
Base support for feet or wheels - 1600mm (700/900)	PNC 206369				
Base support for feet or wheels - 2000mm (700/900)	PNC 206370				
• Rear paneling - 800mm (700/900)	PNC 206374				
• Rear paneling - 1000mm (700/900)	PNC 206375				
• Rear paneling - 1200mm (700/900)	PNC 206376				






Modular Cooking Range Line 700XP 4-Burner Gas Range on Electric Oven

Front 31 1/2 " 800 mm 000000003/4 " 908 mm 35 2 3/16 " 27 1/16 2 3/16 " 56 mm 688 mm 56 mm



Electrical inlet (power) Gas connection



Electric

Supply voltage:

371003 (E7GCGH4CE0) 380-400 V/3 ph/50-60 Hz 371125 (E7GCGH4CEN) 230 V/3 ph/50-60 Hz

Electrical power max.: 6 kW 6 kW **Total Watts:**

Predisposed for:

Gas

Side

Top

Gas Power: 22 kW

Standard gas delivery: Natural Gas G20 (20mbar)

Gas Type Option: LPG:Town Gas Inlet: 1/2"

Key Information:

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

6 kW Oven Heat Input:

Oven working Temperature: 140 °C MIN; 300 °C MAX

Oven Cavity Dimensions

540 mm

Oven Cavity Dimensions

(height): 300 mm

Oven Cavity Dimensions (depth):

External dimensions, Width: 800 mm External dimensions, Depth: 730 mm External dimensions, Height: 850 mm

Net weight:

371003 (E7GCGH4CE0) 88 kg 371125 (E7GCGH4CEN) 80 kg

Shipping weight:

371003 (E7GCGH4CE0) 102 kg 371125 (E7GCGH4CEN) 103 kg

Shipping height:

371003 (E7GCGH4CE0) 1080 mm 371125 (E7GCGH4CEN) 1140 mm Shipping width: 820 mm Shipping depth:

Shipping volume:

860 mm

N7CG

650 mm

371003 (E7GCGH4CE0) 0.76 m³ 371125 (E7GCGH4CEN) 0.8 m³ 5.5 - 5.5 kW Front Burners Power: **Back Burners Power:** 5.5 - 5.5 kW

Certification group: **Back Burners Dimension -**

Ø60 Ø60

Front Burners Dimension -

Ø60 Ø60 mm

Modular Cooking Range Line 700XP 4-Burner Gas Range on Electric Oven