



Electrolux
PROFESSIONAL

Modular Cooking Range Line 700XP 4-Burner Gas Range on Electric Oven

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



371003 (E7GCGH4CE0)

4-Burner (5,5 kW each) gas
Range on electric Oven (6
kW)

371125 (E7GCGH4CEN)

4-Burner (5,5 kW each) gas
Range on electric Oven (6
kW)

Short Form Specification

Item No. _____

To be installed on stainless steel feet with height adjustment up to 50 mm. High efficiency flower flame burners with flame regulator and protected pilot light. Flame failure device as standard on burners to protect against accidental extinguishing. Stainless steel oven chamber with 3 levels of runners to accommodate 2/1 GN shelves (2 steam pans). Ribbed oven base plate. Exterior panels in stainless steel with Scotch Brite finish. Pan supports in heavy duty cast iron. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to have stainless steel feet with height adjustment up to 50 mm.
- The four 5.5 kW high efficiency flower flame burners allow the flame to adapt to different size pans.
- Gas appliance supplied for use with natural or LPG gas, conversion jets supplied as standard.
- Large sized pan support in cast iron (stainless steel as option) with long center fins to allow the use of the largest down to the smallest pans.
- Pan supports in cast iron are washable in a dishwasher.
- Burners to feature flame regulator.
- Flame failure device on each burner protects against gas leakage when accidental extinguishing of the flame occurs.
- Protected pilot light.
- Base compartment consists of an electric standard oven positioned beneath the base plate. Stainless steel oven chamber to have 3 levels of runners to accommodate 2/1 GN shelves (2 steam pans) and ribbed enamelled steel base plate.
- Oven thermostat adjustable from 140 °C to 300 °C.
- Double skinned door with pressed internal panel for heat insulation.
- IPx4 water protection.
- Control knobs provide smooth, continuous rotation from min to max power level.

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Included Accessories

- 1 of GN2/1 chrome grid for static oven PNC 164250

Optional Accessories

- GN2/1 chrome grid for static oven PNC 164250 ☐
- Junction sealing kit PNC 206086 ☐
- Draught diverter, 150 mm diameter PNC 206132 ☐
- Matching ring for flue condenser, 150 mm diameter PNC 206133 ☐

APPROVAL: _____



Experience the Excellence
www.electroluxprofessional.com


• Kit 4 wheels - 2 swivelling with brake - it is mandatory to install Base support and wheels	PNC 206135	☐	• Kit town gas nozzles (G150) for 700 gas range (only for 371003)	PNC 206387	☐
• Flanged feet kit	PNC 206136	☐	• Chimney grid net, 500mm (700XP/900)	PNC 206402	☐
• Frontal kicking strip for concrete installation, 800mm	PNC 206148	☐	• Kit G.25.3 (NI) gas nozzles for 700 top and - freestanding on oven - gas cookers	PNC 206460	☐
• Frontal kicking strip for concrete installation, 1000mm	PNC 206150	☐	• 2 side covering panels for free standing appliances	PNC 216000	☐
• Frontal kicking strip for concrete installation, 1200mm	PNC 206151	☐	• Frontal handrail, 800mm	PNC 216047	☐
• Frontal kicking strip for concrete installation, 1600mm	PNC 206152	☐	• Frontal handrail, 1200mm	PNC 216049	☐
• Frontal kicking strip, 800mm (not for refr-freezer base)	PNC 206176	☐	• Frontal handrail, 1600mm	PNC 216050	☐
• Frontal kicking strip, 1000mm (not for refr-freezer base)	PNC 206177	☐	• Large handrail - portioning shelf, 800mm	PNC 216186	☐
• Frontal kicking strip, 1200mm (not for refr-freezer base)	PNC 206178	☐	• Stainless steel universal frying pan with stainless steel handle (diam. 200mm) suitable for induction and all other heating sources (only for 371125)	PNC 653596	☐
• Frontal kicking strip, 1600mm (not for refr-freezer base)	PNC 206179	☐	• Universal frying pan with stainless steel handle (diam. 280mm) suitable for induction and all other heating sources (only for 371003)	PNC 653598	☐
• Kit 4 feet for concrete installation (not for 900 line free standing grill)	PNC 206210	☐			
• Flue condenser for 1 module, 150 mm diameter	PNC 206246	☐			
• Pair of side kicking strips	PNC 206249	☐			
• Single burner smooth plate for direct cooking - fits frontal burners only	PNC 206260	☐			
• Single burner ribbed plate for direct cooking- fits frontal burners only	PNC 206261	☐			
• Single burner radiant plate for pan support	PNC 206264	☐			
• Pair of side kicking strips for concrete installation	PNC 206265	☐			
• Water column with swivel arm (water column extension not included)	PNC 206289	☐			
• Water column extension for 700 line	PNC 206291	☐			
• Stainless steel double grid for 2 burners	PNC 206297	☐			
• Chimney upstand, 800mm	PNC 206304	☐			
• Right and left side handrails	PNC 206307	☐			
• Back handrail 800 mm	PNC 206308	☐			
• Wok pan support for open burners (700/900)	PNC 206363	☐			
• Base support for feet or wheels - 400mm (700/900) (only for 371125)	PNC 206366	☐			
• Base support for feet or wheels - 800mm (700/900)	PNC 206367	☐			
• Base support for feet or wheels - 1200mm (700/900)	PNC 206368	☐			
• Base support for feet or wheels - 1600mm (700/900)	PNC 206369	☐			
• Base support for feet or wheels - 2000mm (700/900)	PNC 206370	☐			
• Rear paneling - 800mm (700/900)	PNC 206374	☐			
• Rear paneling - 1000mm (700/900)	PNC 206375	☐			
• Rear paneling - 1200mm (700/900)	PNC 206376	☐			




Electrolux
PROFESSIONAL

Modular Cooking Range Line 700XP 4-Burner Gas Range on Electric Oven

Front




Side



EI = Electrical inlet (power)
G = Gas connection

Top



Electric

Supply voltage:

371003 (E7GCGH4CE0)	380-400 V/3 ph/50-60 Hz
371125 (E7GCGH4CEN)	230 V/3 ph/50-60 Hz

Predisposed for:

Electrical power, max:	6 kW
Total Watts:	6 kW

Gas

Gas Power:	22 kW
Standard gas delivery:	Natural Gas G20 (20mbar)
Gas Type Option:	LPG;Town
Gas Inlet:	1/2"

Key Information:

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Oven Heat Input:	6 kW
Oven working Temperature:	140 °C MIN; 300 °C MAX
Oven Cavity Dimensions (width):	540 mm
Oven Cavity Dimensions (height):	300 mm
Oven Cavity Dimensions (depth):	650 mm
External dimensions, Width:	800 mm
External dimensions, Depth:	730 mm
External dimensions, Height:	850 mm
Net weight:	

371003 (E7GCGH4CE0)	88 kg
371125 (E7GCGH4CEN)	80 kg

Shipping weight:

371003 (E7GCGH4CE0)	102 kg
371125 (E7GCGH4CEN)	103 kg

Shipping height:

371003 (E7GCGH4CE0)	1080 mm
371125 (E7GCGH4CEN)	1140 mm

Shipping width:

371003 (E7GCGH4CE0)	820 mm
371125 (E7GCGH4CEN)	860 mm

Shipping volume:

371003 (E7GCGH4CE0)	0.76 m ³
371125 (E7GCGH4CEN)	0.8 m ³

Front Burners Power:

371003 (E7GCGH4CE0)	5.5 - 5.5 kW
371125 (E7GCGH4CEN)	5.5 - 5.5 kW

Back Burners Power:

371003 (E7GCGH4CE0)	5.5 - 5.5 kW
371125 (E7GCGH4CEN)	5.5 - 5.5 kW

Certification group:

371003 (E7GCGH4CE0)	N7CG
371125 (E7GCGH4CEN)	N7CG

Back Burners Dimension - mm

371003 (E7GCGH4CE0)	Ø 60 Ø 60
371125 (E7GCGH4CEN)	Ø 60 Ø 60

Front Burners Dimension - mm

371003 (E7GCGH4CE0)	Ø 60 Ø 60
371125 (E7GCGH4CEN)	Ø 60 Ø 60



Modular Cooking Range Line
700XP 4-Burner Gas Range on Electric Oven

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2025.10.21