

Modular Cooking Range Line 700XP Freestanding Gas Boiling Pan 60lt direct heat

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



371271 (E7BSGHDNF0)

60-It direct gas Boiling Pan

Short Form Specification

Item No.

To be installed on height adjustable feet in stainless steel. Suitable for natural gas or LPG. Robust burners in stainless steel with flame failure device and protected pilot light. Thermostatic temperature control for power regulation allowing precise temperature cooking. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Discharge tube and tap are very easy to clean from outside.
- Ergonomic: the depth of the vessel facilitates stirring the food, also the most delicate food.
- Kettle is suitable to cook, sauté or poach all kinds of produce.
- Large capacity food tap enables safe and effortless discharging of contents.
- No overshooting of cooking temperatures, fast reaction.
- Smooth large surfaces, easy access for cleaning.
- Solenoid valve to refill with hot and cold water.
- Unit to have stainless steel feet with height adjustment up to 50 mm.
- Produce is uniformly heated in the base and side walls of the kettle by a direct heating system.
- Sides of vessel with satin finishing for easy cleaning.

Construction

- Robust burners in stainless steel with flame failure device, protected pilot light and optimized combustion.
- One piece pressed 1.5 mm work top in Stainless steel.
- IPx4 water protection.
- The tanks are welded in two parts, the side band is in AISI 304, bottom is in ASI 316L, lids are in AISI 304.

Sustainability



- Closed heating system no waste of energy.
- Firmly fitting cover to reduce cooking time and save energy costs.

Optional Accessories

•	Junction sealing kit	PNC 206086	
•	Draught diverter, 150 mm diameter	PNC 206132	
•	Matching ring for flue condenser, 150 mm diameter	PNC 206133	
•	Kit 4 wheels - 2 swivelling with brake - it is mandatory to install Base support and wheels	PNC 206135	
•	Flanged feet kit	PNC 206136	
•	Frontal kicking strip for concrete installation, 400mm	PNC 206147	
•	Frontal kicking strip for concrete installation, 800mm	PNC 206148	
•	Frontal kicking strip for concrete installation, 1000mm	PNC 206150	
•	Frontal kicking strip for concrete installation, 1200mm	PNC 206151	
•	Frontal kicking strip for concrete installation, 1600mm	PNC 206152	
•	Frontal kicking strip, 800mm (not for refr-freezer base)	PNC 206176	
•	Frontal kicking strip, 1000mm (not for refr-freezer base)	PNC 206177	

APPROVAL:






Modular Cooking Range Line 700XP Freestanding Gas Boiling Pan 60lt direct heat


Frontal kicking strip, 1200mm (not for refr-freezer base)	PNC 206178	
Frontal kicking strip, 1600mm (not for refr-freezer base)	PNC 206179	
Kit 4 feet for concrete installation (not for 900 line free standing grill)	PNC 206210	
Flue condenser for 1 module, 150 mm diameter	PNC 206246	
Pair of side kicking strips	PNC 206249	
Pair of side kicking strips for concrete installation	PNC 206265	
Chimney upstand, 800mm	PNC 206304	
 Right and left side handrails 	PNC 206307	
Back handrail 800 mm	PNC 206308	
 Base support for feet or wheels - 400mm (700/900) 	PNC 206366	
Base support for feet or wheels - 800mm (700/900)	PNC 206367	
Base support for feet or wheels - 1200mm (700/900)	PNC 206368	
Base support for feet or wheels - 1600mm (700/900)	PNC 206369	
Base support for feet or wheels - 2000mm (700/900)	PNC 206370	
• Rear paneling - 800mm (700/900)	PNC 206374	
 Rear paneling - 1000mm (700/900) 	PNC 206375	
 Rear paneling - 1200mm (700/900) 	PNC 206376	
• 2 side covering panels for free standing appliances	PNC 216000	
• Frontal handrail, 800mm	PNC 216047	
Frontal handrail, 1200mm	PNC 216049	
Large handrail - portioning shelf, 800mm	PNC 216186	
1-section noodle basket for 60lt boiling pans	PNC 921626	
Trolley with lifting & removable tank	PNC 922403	
Measuring rod for 60 I Boiling PanPressure regulator for gas units	PNC 927000 PNC 927225	





Modular Cooking Range Line 700XP Freestanding Gas Boiling Pan 60lt direct heat






CWII Cold Water inlet 1 (cleaning)

D Drain

Electrical inlet (power) ΕI

Gas connection



HWI = Hot water inlet

Electric

Supply voltage:

371271 (E7BSGHDNF0) 230 V/1N ph/50 Hz

Total Watts: 0.1 kW

Gas

Gas Power: 14 kW

Standard gas delivery: Natural Gas G20 (20mbar)

Gas Type Option: LPG Gas Inlet: 1/2"

Water:

Side

Water drain outlet size: 1"1/2

Key Information:

60 It Pan useful capacity: Vessel (round) diameter: 420 mm Net weight: 95 kg Shipping weight: 84 kg Shipping height: 1140 mm Shipping width: 820 mm 860 mm Shipping depth: 0.8 m³ Shipping volume:

No clearance needed on rear sides of unit if wall is of non combustible type. If wall is combustible, minimum 50 mm wall clearance should be maintained.

Certification group: N7PG



Modular Cooking Range Line 700XP Freestanding Gas Boiling Pan 60lt direct heat