

Modular Cooking Range Line 700XP Freestanding Gas Boiling Pan 60It indirect heat with auto refill (60HZ)

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA #	



371275 (E7BSGHIN4x)

60-It indirect gas Boiling Pan with automatic doublejacket refilling

### **Short Form Specification**

#### Item No.

To be installed on height adjustable feet in stainless steel. Suitable for natural gas or LPG. Robust burners in stainless steel with flame failure device and protected pilot light. Temperature is controlled by a power regulator; heating elements with temperature limiter. Automatic refilling of well. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Rightangled side edges to allow flush-fitting junction between units.

#### **Main Features**

- Sides of vessel with satin finishing for easy cleaning.
- Minimum load for correct funtioning is 20 liters.

#### Construction

• The tanks are welded in two parts, the side band is in AISI 304, bottom is in ASI 316L, lids are in AISI 304.

in AISI 304, bottom is in ASI 316L, lids are in AISI 304.				
Optional Accessories				
<ul> <li>Junction sealing kit</li> </ul>	PNC 206086 🖵			
<ul> <li>Draught diverter, 150 mm diameter</li> </ul>	PNC 206132 🚨			
<ul> <li>Matching ring for flue condenser, 150 mm diameter</li> </ul>	PNC 206133 🚨			
<ul> <li>Kit 4 wheels - 2 swivelling with brake - it is mandatory to install Base support and wheels</li> </ul>	PNC 206135 🗅			
Flanged feet kit	PNC 206136 🛚			
<ul> <li>Frontal kicking strip for concrete installation, 400mm</li> </ul>	PNC 206147 🚨			
<ul> <li>Frontal kicking strip for concrete installation, 800mm</li> </ul>	PNC 206148 🚨			
<ul> <li>Frontal kicking strip for concrete installation, 1000mm</li> </ul>	PNC 206150 🚨			
• Frontal kicking strip for concrete installation, 1200mm	PNC 206151 🚨			
• Frontal kicking strip for concrete installation, 1600mm	PNC 206152 🚨			
• Frontal kicking strip, 800mm (not for refr-freezer base)	PNC 206176 🚨			
• Frontal kicking strip, 1000mm (not for refr-freezer base)	PNC 206177 🚨			
• Frontal kicking strip, 1200mm (not for refr-freezer base)	PNC 206178 🚨			
• Frontal kicking strip, 1600mm (not for refr-freezer base)	PNC 206179 🚨			
Kit 4 feet for concrete installation (not for 900 line free standing grill)	PNC 206210 🚨			
• Flue condenser for 1 module, 150 mm diameter	PNC 206246 □			
<ul> <li>Pair of side kicking strips</li> </ul>	PNC 206249 🗖			
<ul> <li>Pair of side kicking strips for concrete installation</li> </ul>	PNC 206265 □			
<ul> <li>Right and left side handrails</li> </ul>	PNC 206307 🗖			
Back handrail 800 mm	PNC 206308 □			
<ul> <li>Base support for feet or wheels - 400mm (700/900)</li> </ul>	PNC 206366 □			
<ul> <li>Base support for feet or wheels - 800mm (700/900)</li> </ul>	PNC 206367 □			
• Base support for feet or wheels - 1200mm (700/900)	PNC 206368 □			
• Base support for feet or wheels - 1600mm (700/900)	PNC 206369 □			
• Base support for feet or wheels - 2000mm (700/900)	PNC 206370 □			
• Rear paneling - 800mm (700/900)	PNC 206374 🚨			

#### APPROVAL:






# Modular Cooking Range Line 700XP Freestanding Gas Boiling Pan 60It indirect heat with auto refill (60HZ)


<ul> <li>Rear paneling - 1000mm (700/900)</li> <li>Rear paneling - 1200mm (700/900)</li> <li>2 side covering panels for free standing</li> </ul>	PNC 206375 PNC 206376 PNC 216000	
<ul> <li>appliances</li> <li>Frontal handrail, 800mm</li> <li>Frontal handrail, 1200mm</li> <li>Large handrail - portioning shelf,</li> </ul>	PNC 216047 PNC 216049 PNC 216186	
<ul> <li>800mm</li> <li>1-section noodle basket for 60lt boiling pans</li> </ul>	PNC 921626	<u> </u>
<ul> <li>Trolley with lifting &amp; removable tank</li> <li>Measuring rod for 60   Boiling Pan</li> <li>Pressure regulator for gas units</li> </ul>	PNC 922403 PNC 927000 PNC 927225	





## Modular Cooking Range Line 700XP Freestanding Gas Boiling Pan 60lt indirect heat with auto refill (60HZ)






CWII Cold Water inlet 1 (cleaning)

D Drain ΕI

Electrical inlet (power)

Gas connection



HWI

Hot water inlet

**Electric** 

Supply voltage:

371275 (E7BSGHIN4x) 230 V/1N ph/60 Hz

**Total Watts:** 0.1 kW

Gas

Front

Side

Gas Power: 14 kW

Standard gas delivery: Natural Gas G20 (20mbar)

Gas Type Option: LPG Gas Inlet: 1/2"

Water:

Water drain outlet size: 1"1/2

**Key Information:** 

60 It Pan useful capacity: Vessel (round) diameter: 420 mm Net weight: 100 kg Shipping weight: 115 kg Shipping height: 1140 mm 900 mm Shipping width: 920 mm Shipping depth: 0.94 m<sup>3</sup> Shipping volume:

No clearance needed on rear sides of unit if wall is of non combustible type. If wall is combustible, minimum 50 mm wall clearance should be maintained.

Certification group: N7PG

