

Modular Cooking Range Line 700XP Gas Solid Top on Gas Oven with 2 Burners and Cupboard

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



371010 (E7STGL3010)

Full module gas Solid Top (7 kW) with 2 Burners (5,5 kW each) on gas Oven and open Cupboard (6 kW)

Short Form Specification

Item No.

High efficiency 7 kW central burner, flame failure device and protected pilot light. Suitable for natural gas or LPG. Large cooking surface with different heating zones. Large flat cooking surface made in cast iron allows for the use of a number of various sized pots and pans, all easily moved across the surface without lifting. Stainless steel oven chamber with 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans). Two high efficiency 5,5 kW flower flame burners with continuous power regulation and protected pilot light interchangeable on site. Flame failure device as standard on burners to protect against accidental extinguishing. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Gas heated, 7 kW central burner, solid top.
- Durable cast iron cooking plate, easy to clean.
- The center of the plate can reach a maximum temperature of 500 °C while decreasing outwards.
- Central burner with optimized combustion, flame failure device and protected pilot light.
- Temperature gradients to satisfy different cooking needs, provided over the whole plate thanks to the temperature fine-tuning by zone.
- Various sizes of pans can be used at the same time due to large surface area with no intermediate sectors.
- Pans can easily be moved from one area to another without lifting.
- Base compartment consists of a gas heated standard oven with stainless steel burners and self stabilizing flame positioned beneath the base plate. Stainless steel oven chamber to have 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans) and ribbed enamelled steel base plate.
- Oven thermostat adjustable from 110 °C to 270 °C.
- Burners with optimized combustion interchangeable on site.
- Flame failure device on each burner protects against gas leakage when accidental extinguishing of the flame occurs.
- Cupboard compartment for storage of pots, pans, sheet pans etc.
- All major compartments located in front of unit for ease of maintenance.

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- IPx4 water protection.

Included Accessories

 1 of GN2/1 chrome grid for static oven

PNC 164250

Optional Accessories

GN2/1 chrome grid for static PNC 164250 ☐ oven

Junction sealing kit PNC 206086 □

APPROVAL:






Modular Cooking Range Line 700XP Gas Solid Top on Gas Oven with 2 Burners and Cupboard


• Draught diverter, 150 mm diameter	PNC 206132		• 2 side covering panels for free	PNC 216000
 Matching ring for flue condenser, 150 mm diameter 	PNC 206133		standing appliances • Frontal handrail, 1200mm	PNC 216049
 Kit 4 wheels - 2 swivelling with brake - it is mandatory to install Base support and wheels 	PNC 206135		Frontal handrail, 1600mmPressure regulator for gas units	PNC 216050 PNC 927225
Flanged feet kit	PNC 206136			
Frontal kicking strip for concrete installation, 1200mm	PNC 206151			
 Frontal kicking strip for concrete installation, 1600mm 	PNC 206152			
 Frontal kicking strip, 1200mm (not for refr-freezer base) 	PNC 206178			
 Frontal kicking strip, 1600mm (not for refr-freezer base) 	PNC 206179			
 Kit 4 feet for concrete installation (not for 900 line free standing grill) 	PNC 206210			
 2 supports with side runners for 4 GN 1/1 containers for open base cupboards (multifunctional cookers, solid top and gas ranges with cupboard) 	PNC 206244			
• Flue condenser for 1 module, 150 mm diameter	PNC 206246			
 Pair of side kicking strips 	PNC 206249			
 Electric heating kit for cupboards 	PNC 206259			
Single burner smooth plate for direct cooking - fits frontal burners only	PNC 206260			
Single burner ribbed plate for direct cooking- fits frontal burners only	PNC 206261			
 Single burner radiant plate for pan support 	PNC 206264			
 Pair of side kicking strips for concrete installation 	PNC 206265			
 Water column with swivel arm (water column extension not included) 	PNC 206289			
• Water column extension for 700 line				
 Stainless steel double grid for 2 burners 	PNC 206297			
 Chimney upstand, 1200mm 	PNC 206306			
Right and left side handrails	PNC 206307			
Energy saving device for pasta cookers	PNC 206344	_		
Door for open base cupboard	PNC 206350			
• Wok pan support for open burners (700/900)	PNC 206363			
 Base support for feet or wheels - 1200mm (700/900) 	PNC 206368			
Base support for feet or wheels - 1600mm (700/900)	PNC 206369	_		
Base support for feet or wheels - 2000mm (700/900)	PNC 206370			
• Rear paneling - 1200mm (700/900)	PNC 206376			
 Kit town gas nozzles (G150) for 700 solid top and burner 	PNC 206388			






Modular Cooking Range Line 700XP Gas Solid Top on Gas Oven with 2 Burners and Cupboard





EQ

Equipotential screw Gas connection



Gas

Gas Power: 24 kW

Standard gas delivery: Natural Gas G20 (20mbar)

Gas Type Option: LPG 1/2" Gas Inlet:

Key Information:

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat

insulation fitted.

110 °C MIN; 270 °C MAX Oven working Temperature:

Oven Cavity Dimensions

(width): 540 mm

Oven Cavity Dimensions (height): 300 mm

Oven Cavity Dimensions

(depth): 650 mm External dimensions, Width: 1200 mm External dimensions, Depth: 730 mm 850 mm

External dimensions, Height: **Storage Cavity Dimensions**

(width):

330 mm **Storage Cavity Dimensions**

(height):

Storage Cavity Dimensions

640 mm (depth): 140 kg Net weight: Shipping weight: 149 kg Shipping height: 1140 mm Shipping width: 820 mm Shipping depth: 1300 mm Shipping volume: 1.22 m³ Front Burners Power: 5.5 - kW

Certification group: N7TG **Back Burners Dimension -**

Back Burners Power:

Front Burners Dimension -

Solid top usable surface

(width):

Solid top usable surface

(depth):

690 mm 595 mm

5.5 - 0 kW

Ø 60

Ø 60

420 mm



Modular Cooking Range Line 700XP Gas Solid Top on Gas Oven with 2 Burners and Cupboard