

400 Line 400lt Line Refrigerator 1 Door - Stainless steel with wheels and UK plug

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____


725081 (R04PVF4CC)

 1-door Refrigerator 400lt,
 0+10°C, stainless steel,
 ventilated, on wheels, R134a,
 60Hz - UK plug

725082 (R04PVF4LCC)

 1-door refrigerator 400lt,
 0+10°C, stainless steel,
 ventilated, on wheels, left
 hinged, R134a, 60Hz - UK
 plug

Short Form Specification

Item No.

Exterior in stainless steel. Interior in white High Impact Polystyrene with rounded corners and 45mm thick insulation. Right hinged full door with lock, reversible on-site. Built-in refrigeration unit; ventilated operating mode; automatic defrost and evaporation of defrost water; digital control and temperature display. For ambient temperatures up to 43 °C. HCFC, CFC and HFC free insulation and R134a refrigerant gas. Supplied with n. 4 grids mm600x400, PE coated. Equipped with UK plug.

Main Features

- Digital control panel allowing the easy and precise setting and control of the internal temperature.
- Shelf runners are thermoformed and are incorporated in the internal structure to be easily cleanable.
- Model requires only 1 phase 230V supply and can be plugged straight into an existing power socket.
- Very quiet operation.
- Whole interior cell with rounded corners is white thermoformed polystyrene, which is impact resistant.
- No joints whatsoever to eliminate dirt traps.
- Simple refrigeration system easily accessible from the rear of the units.
- Fan assisted cooling for even temperature distribution.
- Model equipped with roll-bond plate that has a plate installed in the internal backside of the unit equipped with a special thermostat to avoid ice formation.
- Connectivity ready for real time access to connected appliances from remote and data monitoring (requires optional accessory).

Construction

- Developed and produced in ISO 9001 and ISO 14001 certified factory.
- Mounted on wheels.
- All models in range are finished in top quality materials to aid durability.
- Delivered with UK plug.
- Refrigerant type: R134a.

Included Accessories

- 2 of Pair of grids for 400lt refrigerator, white PNC 880292

Optional Accessories

- Pair of grids for 400lt refrigerator, white PNC 880292
- Kit of wheels for 400lt refrigerators PNC 880348
- Pvc container with false bottom for 400lt PNC 881072

APPROVAL: _____

Electric

Supply voltage:	
725081 (R04PVF4CC)	220-230 V/1 ph/60 Hz
725082 (R04PVF4LCC)	220-230 V/1 ph/60 Hz
Electrical power max.:	
725081 (R04PVF4CC)	0.15 kW
725082 (R04PVF4LCC)	0.22 kW

Key Information:

Gross capacity:	400 lt
Door hinges:	
725081 (R04PVF4CC)	Right Side
725082 (R04PVF4LCC)	Left Side
External dimensions, Width:	700 mm
External dimensions, Depth with Doors Open:	1310 mm
External dimensions, Height:	1755 mm
Number and type of grids (included):	4 - 600x400
Type of external material:	Stainless Steel
External door material:	Stainless Steel

Refrigeration Data

Control type:	Digital
Compressor power:	
725081 (R04PVF4CC)	1/6 hp
Refrigeration power at evaporation temperature:	
725081 (R04PVF4CC)	-10 °C
725082 (R04PVF4LCC)	-12 °C
Operating temperature min.:	0 °C
Operating temperature max.:	10 °C
Operating mode:	Ventilated
Cooling unit:	Built-In
Defrost type:	Automatic (air)

Sustainability

Noise level:	55 dBA
Refrigerant type:	R134a
Refrigeration power:	
725081 (R04PVF4CC)	352 W
725082 (R04PVF4LCC)	306 W
Refrigerant weight:	
725081 (R04PVF4CC)	210 g
725082 (R04PVF4LCC)	240 g