

## 400 Line

### 400lt Line Freezer 1 Door - Stainless steel with wheels and UK plug

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_


**725083 (R04FSF4CC)**

1-door Freezer 400lt, -15-24° C (R290), stainless steel with wheels, R404a, 60Hz - UK plug

**725084 (R04FSF4LCC)**

1-door Freezer 400lt, -15-24° C (R290), stainless steel with wheels, R404a, left hinged, 60Hz UK plug

### Short Form Specification

**Item No.** \_\_\_\_\_

Exterior in stainless steel. Interior in white High Impact Polystyrene with rounded corners and 45mm thick insulation. Right hinged full door with lock and heated frame, reversible on-site. Built-in refrigeration unit; manual defrost; digital control and temperature display; multiple evaporating grids. For ambient temperatures up to 38 °C. HCFC, CFC and HFC free insulation and R404a refrigerant gas.

Supplied with n. 4 evaporating grids. Equipped with UK plug.

### Main Features

- Digital control panel allowing the easy and precise setting and control of the internal temperature.
- Shelf runners are thermoformed and are incorporated in the internal structure to be easily cleanable.
- Suitable for use in ambient temperatures of up to 38 °C.
- Model requires only 1 phase 230V supply and can be plugged straight into an existing power socket.
- Very quiet operation.
- Whole interior cell with rounded corners is white thermoformed polystyrene, which is impact resistant.
- No joints whatsoever to eliminate dirt traps.
- Simple refrigeration system easily accessible from the rear of the units.
- Connectivity ready for real time access to connected appliances from remote and data monitoring (requires optional accessory).

### Construction

- Developed and produced in ISO 9001 and ISO 14001 certified factory.
- Mounted on wheels.
- All models in range are finished in top quality materials to aid durability.
- Delivered with UK plug.
- Refrigerant type: R404a.

### Optional Accessories

- Kit of wheels for 400lt refrigerators PNC 880348
- Pvc container with false bottom for 400lt PNC 881072

**APPROVAL:** \_\_\_\_\_

**Electric****Supply voltage:**

725083 (R04FSF4CC) 220-230 V/1 ph/60 Hz

725084 (R04FSF4LCC) 220-230 V/1 ph/60 Hz

**Electrical power max.:** 0.8 kW**Key Information:****Gross capacity:** 400 lt**Door hinges:**

725083 (R04FSF4CC) Right Side

725084 (R04FSF4LCC) Left Side

**External dimensions, Width:** 700 mm**External dimensions, Depth with Doors Open:** 1310 mm**External dimensions, Height:** 1755 mm**Number and type of grids (included):** 4 - 600x400**Type of external material:** Stainless Steel**External door material:** Stainless Steel**Refrigeration Data****Control type:** Digital**Compressor power:****Refrigeration power at evaporation temperature:** -29 °C**Operating temperature min.:** -24 °C**Operating temperature max.:** -15 °C**Operating mode:** Static**Cooling unit:** Built-In**Defrost type:** Manual**Sustainability****Noise level:** 56 dBA**Refrigerant type:** R404A**Refrigeration power:** 881 W**Refrigerant weight:** 240 g