

## Digital Cabinets

### Roll-in Compact Refrigerator 750 lt - 1 door - remote

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_


**725097 (RI075R1FR)**

 1-door Roll-in Refrigerator  
 750lt, 0+10°C, AISI 304,  
 remote

#### Short Form Specification

**Item No.** \_\_\_\_\_

External and internal in AISI 304 stainless steel. Insulation thickness mm60. Right hinged full door with lock. Bottom door gasket adjustable. Pre-arranged for remote refrigeration unit (non included); ventilated operating mode; digital control; evaporator; automatic defrost; external digital temperature display; high/low humidity switch. Operating temperature 0+10°C. For ambient temperatures up to 43 °C.

#### Main Features

- Excellent space optimisation thanks to the compact dimensions (footprint 0.56m²).
- Ventilated cooling for optimal temperature distribution.
- Lift-up control panel to better access main components.
- Digital control panel with temperature display.
- Connectivity ready for real time access to connected appliances from remote and data monitoring (requires optional accessory).
- Large digital white-digit display with humidity selection button (3 preset level), internal temperature display and setting, manual activation of defrost cycle and turbo frost cycle (to rapidly cool warm loads).
- The operating temperature can be adjusted from 0 to +10 °C to suit both meat and dairy storage requirements.
- Automatic defrost and automatic evaporation of defrost water.
- One full door.
- Suitable for all kinds of 18 shelves GN 1/1 trolleys, designed to fit the 18 shelves GN 2/1 trolley available as optional accessory.
- Complies with main international certification bodies and is CE marked.
- Inner side protectors to protect the internal walls.
- Adjustable bottom door gasket.
- Simple cooling unit easily accessible from the rear of the appliance.
- Tropicalized unit.

**APPROVAL:** \_\_\_\_\_

## Construction

- Evaporator and fan are placed outside the cell to provide the maximum storage capacity.
- Lockable door.
- Evaporator cover is easily removable for service.
- Developed and produced in ISO 9001 and ISO 14001 certified factory.
- Remote compressor to suit operating conditions.
- Electrical connection: 220-240V-single phase 50HZ or 220-240V-single phase 60HZ.
- Interior cell and external panel are constructed in 304 AISI stainless steel.
- External panels are in AISI 304 stainless steel for higher level of hygiene.

## Sustainability



- Finished in top quality materials to ensure durability.
- CFC and HCFC-free insulation.
- Cabinet fitted with up to 60 mm thickness of Cyclopentane insulation for best insulating performance (thermal conductivity: 0,020 W/m\*K). CFC and HCFC-free insulation.

## Optional Accessories


- Trolley 18x2/1GN for roll-in 750lt PNC 881521 ☐




**Electrolux**  
PROFESSIONAL

## Digital Cabinets Roll-in Compact Refrigerator 750 lt - 1 door - remote

Front




Side



EI = Electrical inlet (power)  
RI = Refrigerant Inlet  
RO = Refrigerant Outlet

Top



### Electric

Supply voltage: 220-240 V/1 ph/50/60 Hz

### Key Information:

#### Door hinges:

External dimensions, Width: 750 mm  
External dimensions, Depth: 816 mm  
External dimensions, Height: 2101 mm  
Number and type of doors: 1 Full  
External side panels: 304 AISI  
External top panels: Galvanized Steel  
External door material: 304 AISI  
Internal panels material: 304 AISI

### Refrigeration Data

Control type: Digital  
Operating temperature max.: 10 °C  
Refrigeration type: R134a;R513A;R426A  
Suggested refrigeration power: 580 W  
Condition at evaporation temperature: -10 °C  
Condition at condensation temperature: 55 °C  
Condition at ambient temperature: 43 °C  
Connection pipes (remote) - outlet: 9.8 mm  
Connection pipes (remote) - inlet: 6 mm

### ISO Certificates

ISO Standards: ISO 9001; ISO 14001; ISO 45001; ISO 50001



Digital Cabinets  
Roll-in Compact Refrigerator 750 lt - 1 door - remote

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2025.06.24