

Digital Cabinets

Roll-in Refrigerator 1600 lt - 1 door - remote

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____


725101 (RI16R1FR)

 1-door Roll-in Refrigerator
 1600lt, 0/+10°C, AISI 304,
 remote

Short Form Specification

Item No. _____

External and internal in AISI 304 stainless steel. Insulation thickness mm75. Reversible right hinged full door with lock, 60mm thick insulation. Bottom door gasket adjustable. Universal shock protectors on all sides. Remote refrigeration unit; ventilated operating mode. Digital control panel; temperature display; humidity control; hidden evaporator; automatic defrost and automatic evaporation of defrost water. Evaporator probe optimizes defrost cycle. Operating temperature 0/+10°C at 43°C ambient temperature. CFC and HCFC free insulation. Compatible with trolleys (mm820x1015x1840h).

Main Features

- Ventilated cooling for optimal temperature distribution.
- Lift-up control panel to better access main components.
- Digital control panel with temperature display.
- Large digital white-digit display with humidity selection button (3 preset level), internal temperature display and setting, manual activation of defrost cycle and turbo frost cycle (to rapidly cool warm loads).
- The operating temperature can be adjusted from 0 to +10 °C to suit both meat and dairy storage requirements.
- Automatic defrost and automatic evaporation of defrost water.
- One full door.
- Complies with main international certification bodies and is CE marked.
- Plug-in installation: 1 phase, 220/240V supply.
- Universal shock-protectors on all sides.
- Adjustable bottom door gasket.
- Simple cooling unit easily accessible from the rear of the appliance.
- Tropicalized unit.

APPROVAL: _____

Construction

- Evaporator and fan are placed outside the cell to provide the maximum storage capacity.
- Lockable door.
- Evaporator cover is easily removable for service.
- Developed and produced in ISO 9001 and ISO 14001 certified factory.
- Remote compressor to suit operating conditions.
- Interior cell and external panel are constructed in 304 AISI stainless steel.
- External panels are in AISI 304 stainless steel for higher level of hygiene.
- The whole interior cell is constructed of AISI 304 stainless steel with rounded corners for a better cleanability.

- Banquet trolley with rack holding 116 PNC 922764 ☐
 plates for 20 GN 2/1 oven and blast
 chiller freezer, 66mm pitch

User Interface & Data Management

- Connectivity ready for real time access to connected appliances from remote and data monitoring (requires optional accessory).

Sustainability




- Finished in top quality materials to ensure durability.
- CFC and HCFC-free insulation.
- 75 mm thick insulation, with cyclopentane injection for long-term insulation and energy saving.


Optional Accessories

- Trolley with tray rack, 15 GN 1/1, PNC 922683 ☐
 84mm pitch
- Trolley with tray rack, 15 GN 2/1, PNC 922686 ☐
 84mm pitch
- Trolley with tray rack, 20 GN 1/1, PNC 922753 ☐
 63mm pitch
- Trolley with tray rack, 16 GN 1/1, PNC 922754 ☐
 80mm pitch
- Banquet trolley with rack holding 54 PNC 922756 ☐
 plates for 20 GN 1/1 oven and blast
 chiller freezer, 74mm pitch
- Trolley with tray rack 20 GN 2/1, PNC 922757 ☐
 63mm pitch
- Trolley with tray rack, 16 GN 2/1, PNC 922758 ☐
 80mm pitch
- Banquet trolley with rack holding 92 PNC 922760 ☐
 plates for 20 GN 2/1 oven and blast
 chiller freezer, 85mm pitch
- Bakery/pastry trolley with rack PNC 922761 ☐
 holding 600x400mm grids for 20 GN
 1/1 oven and blast chiller freezer,
 80mm pitch (16 runners)
- Bakery/pastry trolley with rack PNC 922762 ☐
 holding 400x600mm grids for 20
 GN 2/1 oven and blast chiller
 freezer, 80mm pitch (16 runners)
- Banquet trolley with rack holding 45 PNC 922763 ☐
 plates for 20 GN 1/1 oven and blast
 chiller freezer, 90mm pitch

Front




Side



EI = Electrical inlet (power)
 RI = Refrigerant Inlet
 RO = Refrigerant Outlet

Top



Electric

Supply voltage: 220-240 V/1 ph/50/60 Hz

Key Information:

Door hinges:

External dimensions, Width: 1021 mm
 External dimensions, Depth: 1175 mm
 External dimensions, Height: 2273 mm
 Number and type of doors: 1 Full
 External side panels: 304 AISI
 External top panels: 304 AISI
 External door material: 304 AISI
 Internal panels material: 304 AISI

Refrigeration Data

Control type: Digital
 Operating temperature max.: 10 °C
 Refrigeration type: R134a;R513A;R426A
 Suggested refrigeration power: 1380 W
 Condition at evaporation temperature: 0 °C
 Condition at condensation temperature: 55 °C
 Condition at ambient temperature: 32 °C
 Connection pipes (remote) - outlet: 9.5 mm
 Connection pipes (remote) - inlet: 6 mm

ISO Certificates

ISO Standards: ISO 9001; ISO 14001; ISO 45001; ISO 50001