



## Digital Cabinets Roll-Through Refrigerator 1600 lt - 1 Full, 1 Glass door

ITEM #  
MODEL #  
NAME #  
SIS #  
AIA #



725103 (RI16R2FGT)

1-full and 1-glass door Roll-in  
Pass-through Refrigerator  
1600lt, +2+10°C, AISI 304,  
R290

### Main Features

- Ventilated cooling for optimal temperature distribution.
- Lift-up control panel to better access main components.
- Interior light and lockable door.
- Digital control panel with temperature display.
- The operating temperature can be adjusted from +2 to +10°C to suit both meat and dairy storage requirements.
- Automatic defrost and automatic evaporation of defrost water.
- One full door and one glass door.
- Complies with main international certification bodies and is CE marked.
- Plug-in installation: 1 phase, 220/240V supply.
- Inner side protectors to protect the internal walls.
- Right hinged glass door.
- Adjustable bottom door gasket.
- Simple cooling unit easily accessible from the rear of the appliance.
- Tropicalized unit.

### Short Form Specification

#### Item No.

External and internal in AISI 304 stainless steel. Body insulation thickness mm75. N. 1 full door and N. 1 glass door with heated frame and internal lighting. Built-in refrigeration unit; ventilated operating mode; digital control; automatic defrost; external digital temperature display. Operating temperature +2+10°C. For ambient temperatures up to 43 °C. CFC and HCFC free. R290 gas in refrigeration circuit.

#### APPROVAL:



Experience the Excellence  
[www.electroluxprofessional.com](http://www.electroluxprofessional.com)

## Construction

- Evaporator and fan are placed outside the cell to provide the maximum storage capacity.
- Lockable door.
- Evaporator cover is easily removable for service.
- Developed and produced in ISO 9001 and ISO 14001 certified factory.
- Built-in compressor to suit operating conditions.
- Interior cell and external panel are constructed in 304 AISI stainless steel.
- External panels are in AISI 304 stainless steel for higher level of hygiene.
- The whole interior cell is constructed of AISI 304 stainless steel with rounded corners for a better cleanability.




## User Interface & Data Management

- Connectivity ready for real time access to connected appliances from remote and data monitoring (requires optional accessory).
- Large digital white-digit display with humidity selection button (3 preset level), internal temperature display and setting, manual activation of defrost cycle and turbo frost cycle (to rapidly cool warm loads).

## Sustainability



- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- Finished in top quality materials to ensure durability.
- CFC and HCFC-free insulation.
- 75 mm thick insulation, with cyclopentane injection for long-term insulation and energy saving.


**Front**

**Side**

**Top**
**Electric**
**Supply voltage:** 220-240 V/1 ph/50 Hz

**Key Information:**
**Built-in Compressor and Refrigeration Unit**
**Door hinges:**
**External dimensions, Width:** 1021 mm

**External dimensions, Depth:** 1249 mm

**External dimensions, Height:** 2272 mm

**Number and type of doors:** 2 Full;Glass

**External side panels:** 304 AISI

**External top panels:** 304 AISI

**Glass;Stainless Steel AISI**
**External door material:** 304 - Din 1.4301

**Internal panels material:** 304 AISI

**Refrigeration Data**
**Operating temperature min.:** 2 °C

**Operating temperature max.:** 10 °C

**Compressor power:**
**ISO Certificates**
**ISO Standards:** ISO 9001; ISO 14001; ISO 45001; ISO 50001

**Sustainability**
**Refrigerant type:** R290

**Refrigeration power:** 546 W

**Refrigerant weight (unit 1):** 150 g