

ecostore Premium 2 Half Door Dual Digital Refrigerator, 670lt (-2/-2) - Remote

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA #	



727259 (ESP72HDRR)

Eco Store Premium Dual Refrigerator-670 It 2 half doors (-2/-2°C)- Remote -230 V/1N/50Hz

Short Form Specification

Item No.

Two half door refrigerator entirely constructed in 304 AISI stainless steel with bottom panel in anti-corrosive material. Large digital white-digit display with cabinet temperature display and setting, and possibility to select the desired levels of humidity, HACCP-compliant control with glarms and history, Frost Watch Control to defrost only when required with automatic evaporation of defrost water. Optiflow: back to front forced air flow and removable air conveyors provides even temperature distribution and fast cooling in any conditions. Fitted with 75 mm-thick cyclopentane insulating foam, On-site reversible door features lock and door microswitch to switch off the fan when the door is opened. Hidden evaporator to avarantee higher storage capacity and less corrosion problems. Remote refrigeration unit; ventilated operation; Internal LED light. Dual operating temperature: -2/+10°C -2/+10°C. CFC and HCFC free. R134a gas in refrigeration circuit. Supplied with n. 4x2/1GN Rilsan coated grids and n. 4 sets of 2 stainless steel grid runners. Prearranged to fit RS485 port to facilitate connection to a remote computer and integrated **HACCP** systems

Main Features

- Right hinged two 1/2 door with heated frame.
- Large storage area suitable to contain 2/1 GN grids or shelves on anti-tilt runners.
- Optiflow: back to front forced air flow and removable air conveyors provide even temperature distribution and fast cooling in any conditions.
- Dual temperature type: -2 +10 °C/-2 +10 °C.
- Cabinet fitted with up to 75 mm thickness of cyclopentane insulation for best insulating performance with 100% environmental protection (thermal conductivity: 0,020 W/m* K).
- 60 mm-thick insulation covering the evaporator can be easily removed with a single operation.
- Prearranged to fit RS485 port to facilitate connection to a remote computer and integrated HACCP systems.
- Operating temperature can be adjusted from -2 to +10 °C to suit different food storage requirements.
- Performance guaranteed at ambient temperatures of +40°C (Climatic class 5).
- Internal structure with 44 charging positions available to host grids, ensuring higher net capacity and a greater storage space.
- Possibility to select 3 different levels of humidity according with the type of food stored inside.
- Tropicalized unit.

Construction

- Constructed from the highest quality AISI 304 Stainless steel.
- Interior base with rounded corners, pressed from a single sheet.
- The rounded internal corners, the easily removable runners, grids and air conveyors allow for ease of cleaning and high hygiene standards.
- Stainless steel runners and supports easily disassembled.
- Anti-corrosion bottom material avoids any damage that may be caused to the cabinet by aggressive detergents employed to clean the floors.
- Easy access to the main components for maintenance.
- Lockable door.
- Refrigerant type: R134a.
- Remote refrigeration unit.

User Interface & Data Management

• Connectivity ready for real time access to





ecostore Premium 2 Half Door Dual Digital Refrigerator, 670lt (-2/-2) - Remote

connected appliances from remote and data monitoring (requires optional accessory).

- Large digital white-digit display with cabinet temperature display and setting, activation of turbo frost cycle (to rapidly cool warm loads) and possibility to activate manually the defrost cycle.
- Large digital white-digit display with cabinet temperature display and setting, and possibility to select the desired levels of humidity. Bluetooth technology included allows to keep HACCP historical data and download them through the app.
- Electrolux Professional Fridge Control APP makes the life easier for our customers:
 - Monitor safety of preservation process thanks to HACCP data & alarms for precise control
 - Save time and easy data management having the possibility to send the HACCP information in excel format directly to e-mail address
 - Quick operations: set the cabinet temperature/humidity/turbocooling and set date/hour

Sustainability



- CFC and HCFC-free insulation.
- Interior LED light to save energy and for best internal visibility.
- Door switch stops the fan when door is opened to avoid cold air exiting the cell, thus saving energy.
- Removable triple-chamber balloon magnetic gasket to improve insulation and reduce energy consumption and ease of cleaning.
- Improved defrost and evaporator fan management defrost type changes with temperature set-point: electric below +2°C while air convection defrost above +2°C, thus saving energy.
- Frost Watch Control: fully automatic defrost starts only when ice is actually building-up in the evaporator and adapt the defrosting duration to guarantee perfect ice removal while optimizing energy efficiency consumption.
- Automatic evaporation of the defrosting water by hot gas on the top for energy saving.
- Cleaning-free condenser: the structure of the wire frame condenser prevents dust and grease accumulation thus avoiding periodical cleaning operations and reducing energy consumption.
- Cabinet certified as Class A in heavy duty working conditions (40°C-40% humidity) based on European Ecodesign directive.
- The label complies with the delegated regulation (UE) 2015/1094 of the commission of 5th may 2015.

PNC 881020

Included Accessories

• 4 of 2/1GN grey rilsan grid with 2


runners					
Optional Accessories					
 Spacer for 670 lt and 1430 lt refrigerated cabinets 	PNC 880248				
 Pedal opening for cabinets 	PNC 880324				
 1/1GN plastic container with false bottom 	PNC 880705				
• 2/1GN grey rilsan grid	PNC 881004				
• 2/1GN aisi 304 stainless steel grid	PNC 881016				
• 2/1GN 304 AISI stainless steel grid with 2 runners	PNC 881018				

•	Set of 2 stainless steel runners for 670/1430lt refrigerators and freezers	PNC 881021	
•	2/1GN pvc container with lid and 2 runners	PNC 881039	
•	2/1GN perforated shelf	PNC 881042	
•	1/1GN rilsan steel wire basket h=150mm	PNC 881043	
•	2/1GN grey rilsan basket+2 runners h=150mm	PNC 881047	






ecostore Premium 2 Half Door Dual Digital Refrigerator, 670lt (-2/-2) - Remote



827 219 ΕI Ħ 707 1544 110-165 D 163 73



Electric

Front

Side

Top

Supply voltage: 220-240 V/1 ph/50/60 Hz

40; 30 mm

R134a;R513A

Electrical power, max: 0.28 kW

Capacity:

Number and type of grids

(included): 4 - GN 2/1

Key Information:

Door hinges:

External dimensions, Width: 710 mm External dimensions, Depth: 835 mm

External dimensions, Depth

Number of positions & pitch:

with Doors Open: 1480 mm External dimensions, Height: 2050 mm Number and type of doors: 2x1/2 Full Type of external material: **304 AISI** Type of internal material: **304 AISI** Internal panels material: **304 AISI**

670 It Gross capacity:

Refrigeration Data

Second Unit Refrigerant R134a type:

Suggested refrigeration 358 W power: (second unit): Control type: Digital

Refrigeration type: Suggested refrigeration

358 W

Condition at evaporation

temperature: -10 °C

Condition at condensation 55 °C temperature:

Condition at ambient 32 °C temperature:

Connection pipes (remote) -

9.5 mm outlet:

Connection pipes (remote) -

inlet:

*Note:

ISO Certificates

ISO 9001; ISO 14001; ISO ISO Standards:

6 mm

45001; ISO 50001

Sustainability

Refrigerant type: R134a



Electrical inlet (power)

Refriaerant Inlet Refrigerant Outlet

RI





