

160 Line Freezer Counter 160 lt - undercounter, UK Plug, R600a

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____


727796 (RUCF16W1C6)

 1-door Undercounter
Freezer 160lt, -15-20°C,
prepainted white, R600a -
UK plug

727797 (RUCF16X1C6)

 1-door Undercounter
Freezer 160lt, -15-20°C,
prepainted grey with
stainless steel door, R600a -
UK plug

Short Form Specification

Item No. _____

White painted reversible door with lock. Top in white ABS. White painted external sides. Interior in white High Impact Polystyrene with 55mm insulation. Inner cell with rounded corners. Door with removable "balloon" gasket. Built-in refrigeration unit; static operating mode; manual defrost; electronic control; external digital temperature display. Temperature range -20°/-15°C at 43 °C ambient temperature. CFC and HCFC free insulation. R600a gas in refrigeration circuit. Gas in foam: Cyclopentane. IP23 protection. Supplied with n.3 rilsan grids. UK plug.

Main Features

- Very quiet operation: noise level less than 45 dB (A).
- Shelf runners are thermoformed and are incorporated in the internal structure to be easily cleanable.
- Compact cooling unit easily accesible from the rear of the appliance.
- Model requires only 1 phase 230V supply and can be plugged straight into an existing power socket.
- Digital temperature display and simple electromechanical control panel.
- Simple control panel.
- Manual defrost.
- Adjustable temperature range from -15°C to -20°C to suit all storage requirements.

Construction

- Interior cell is completely in white High Impact Polystyrene and has no joints to eliminate dirt traps.
- IP23 protection index.
- Developed and produced in ISO 9001 and ISO 14001 certified factory.
- Reversible door.
- Lockable door.
- Delivered with UK plug.
- CFC and HCFC free (ecological refrigerant type: R600a).

Sustainability



- CFC and HCFC-free insulation.

Optional Accessories

- Rear wheel kit for 160lt for freestanding refrigerator and freezer PNC 880143
- 3 rilsan baskets for 160lt undercounter freezer PNC 880189

APPROVAL: _____

Electric

Supply voltage:

727796 (RUCF16W1C6) 220-240 V/1 ph/50 Hz

727797 (RUCF16X1C6) 220-240 V/1 ph/50 Hz

Electrical power max.: 0.085 kW

Key Information:

Gross capacity:

727796 (RUCF16W1C6) 110 lt

727797 (RUCF16X1C6) 120 lt

N° of doors: 1

External dimensions, Width: 598 mm

External dimensions, Depth: 618 mm

External dimensions, Height: 825 mm

Height adjustment: 0/10 mm

Type of internal material: High Impact White
 Polystyrene

External side panels:

727796 (RUCF16W1C6) Prepainted white

727797 (RUCF16X1C6) Prepainted Steel

External top panels: Stainless Steel

External door material:

727796 (RUCF16W1C6) Prepainted white

727797 (RUCF16X1C6) Stainless steel antifingertip

Internal panels material: High Impact White
 Polystyrene

Internal side panels material: High Impact White
 Polystyrene

Refrigeration Data

Control type: Electronic

Refrigeration power at evaporation temperature: -30 °C

Operating temperature min.: -20 °C

Operating temperature max.: -15 °C

Operating mode: Static

Cooling unit: Built-In

Defrost type: Manual

Sustainability

Noise level: 47 dBA

Refrigerant type: R600a

Refrigeration power: 163 W

Refrigerant weight: 55 g