

ecostore Premium 2 Glass Door Digital Refrigerator, 1430lt (+2/+10) - R290



Short Form Specification

Item No.

Two full glass door refrigerator entirely constructed in 304 AISI stainless steel with bottom panel in anti-corrosive material. Digital display featuring cabinet temperature display and setting, manual activation of defrost cycle and turbo frost cycle (to rapidly cool warm loads). HACCP-compliant control with alarms and history. Frost Watch Control to defrost only when required with automatic evaporation of defrost water. Optiflow: back to front forced air flow and removable air conveyors provides even temperature distribution and fast cooling in any conditions. Fitted with 75 mm-thick cyclopentane insulating foam. Door features lock and door microswitch to switch off the fan when the door is opened. Hidden evaporator to guarantee higher storage capacity and less corrosion problems. Built-in refrigeration unit; ventilated operation; Internal LED light and internal back light. CFC and HCFC free. R290 gas in refrigeration circuit. Prearranged to fit RS485 port to facilitate connection to a remote computer and integrated HACCP systems.

APPROVAL:

ITEM #
MODEL #
NAME #
<u>SIS #</u>
AIA #

Main Features

- Large digital white-digit display with cabinet temperature display and setting, manual activation of defrost cycle, turbo frost cycle (to rapidly cool warm loads) and internal light switch.
- Large storage area suitable to contain 2/1 GN grids or shelves on anti-tilt runners.
- Optiflow: back to front forced air flow and removable air conveyors provide even temperature distribution and fast cooling in any conditions.
- The operating temperature can be adjusted from +2 to +10°C to suit both meat and dairy storage requirements.
- Performance guaranteed at ambient temperatures of +32°C.
- Cabinet fitted with up to 75 mm thickness of cyclopentane insulation for best insulating performance with 100% environmental protection (thermal conductivity: 0,020 W/m*K).
- 60 mm-thick insulation covering the evaporator can be easily removed with a single operation.
- Prearranged to fit RS485 port to facilitate connection to a remote computer and integrated HACCP systems.
- Rilsan coated grids for improved protection.
- Led lights on the door guarantee an even light in the cavity.
- Connectivity ready for real time access to connected appliances from remote and data monitoring (requires optional accessory).
- Large digital white-digit display with cabinet temperature display and setting, activation of turbo frost cycle (to rapidly cool warm loads) and possibility to activate manually the defrost cycle.
- Digital temperature display and setting +2/+10 °C.
- Internal structure with 44 charging positions available to host grids, ensuring higher net capacity and a greater storage space.
- Possibility to select 3 different levels of humidity according with the type of food stored inside.
- Large digital white-digit display with cabinet temperature display and setting, and possibility to select the desired levels of humidity. Bluetooth technology included allows to keep HACCP historical data and download them through the app.
- Electrolux Professional Fridge Control APP make the life easier for our customers:

 Monitor safety of preservation process thanks to HACCP data & alarms for precise control
 Save time and easy data management having the possibility to send the HACCP information in excel format directly to e-mail address
- Quick operations: set the cabinet temperature/ humidity/turbocooling and set date/hour
- Tropicalized unit.

Construction

- Constructed from the highest quality AISI 304 Stainless steel.
- Interior base with rounded corners, pressed from a single sheet.

Experience the Excellence www.electroluxprofessional.com

Excelence



ecostore Premium 2 Glass Door Digital Refrigerator, 1430lt (+2/+10) - R290

- The rounded internal corners, the easily removable runners, grids and air conveyors allow for ease of cleaning and high hygiene standards.
- Stainless steel runners and supports easily disassembled.
- Anti-corrosion bottom avoids any damage that may be caused to the cabinet by aggressive detergents employed to clean the floors.
- Easy access to the main components for maintenance.
- Lockable door.

Sustainability


- Frost Watch Control: fully automatic defrost starts only when ice is actually building-up in the evaporator and adapt the defrosting duration to guarantee perfect ice removal while optimizing energy efficiency consumption.
- Improved defrost and evaporator fan management defrost type changes with temperature set-point: electric below +2°C while air convection defrost above +2°C, thus saving energy.
- Door switch stops the fan when door is opened to avoid cold air exiting the cell, thus saving energy.
- CFC and HCFC-free insulation.
- R290 refrigerant to reduce green house and ozone depletion effects.
- Removable triple-chamber balloon magnetic gasket to improve insulation and reduce energy consumption and ease of cleaning.
- Cleaning-free condenser: the structure of the wire frame condenser prevents dust and grease accumulation thus avoiding periodical cleaning grease operations and reducing energy consumption.
- Automatic evaporation of the defrosting water by hot gas on the top for energy saving.
- Interior LED light to save energy and for best internal visibility.
- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- Cabinet certified as Class A in heavy duty working conditions (40°C-40% humidity) based on European Ecodesign directive.
- The label complies with the delegated regulation (UE) 2015/1094 of the commission of 5th may 2015.

Included Accessories

• 8 of 2/1GN grey rilsan grid with 2 PNC 881020 runners

Optional Accessories

- 2 stainless steel runners for refrigerated PNC 880242 cabinets - (Marine)
- Set of 8 GN1/1 PVC containers for fish PNC 880243
- Spacer for 670 lt and 1430 lt PNC 880248 refrigerated cabinets • Kit 20 pair runners and tray supports to PNC 880333 fit pastry trays (400x600mm) 1/1GN plastic container with false PNC 880705 bottom
- 2/1GN grey rilsan grid PNC 881004




- 2/IGN 304 AISI stainless steel grid with PNC 881018 2 runners
- Meat rail for 670/1430lt refrigerators PNC 881019 with 4 hooks
- 2/IGN grey rilsan grid with 2 runners PNC 881020 • Set of 2 stainless steel runners for PNC 881021
- 670/1430lt refrigerators and freezers
- PNC 881033 Pedal opening for 1430lt refrigerator
- 2/IGN pvc container with lid and 2 PNC 881039 runners
- 2/IGN perforated shelf PNC 881042
- 1/1GN rilsan steel wire basket h=150mm PNC 881043
- 2/1GN grey rilsan basket+2 runners PNC 881047 h=150mm
- Glass door protection kit for Glass Door PNC 881163 Cabinets
- 5 swivelling wheels (2 with brake), diam PNC 881294 125mm, for 1430 lt refrigerators, NOT for remote models



ecostore Premium 2 Glass Door Digital Refrigerator, 1430lt (+2/+10) - R290

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Electrolux PROFESSIONAL



ecostore Premium 2 Glass Door Digital Refrigerator, 1430lt (+2/+10) - R290

220-240 V/1 ph/50 Hz 0.29 kW
8 - GN 2/1
1037 lt 1441 mm 835 mm 1480 mm 2050 mm 2 Glass 304 AISI 304 AISI 304 AISI 304 AISI 44; 30 mm 1430 lt
Digital -10 °C 2 °C 10 °C Ventilated
ISO 9001; ISO 14001; ISO 45001; ISO 50001
R290 3 395 W E 1883kWh/year - 5kWh/24h Normal duty (cl.4)



10

1480

ecostore Premium 2 Glass Door Digital Refrigerator, 1430lt (+2/+10) - R290

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

ecostore Premium 2 Glass Door Digital Refrigerator, 1430lt (+2/+10) - R290


EU energy labelling from 1st July 2016 The European energy labelling scheme for professional


The European energy labelling scheme for professional refrigerators and freezers is based on requirements setting Minimum Energy Performance standards for commercial refrigeration cabinets sold within the EU. These requirements are designed to drive energy efficiency and environmentally friendly approach for professionals. The European energy labelling scheme will apply to all manufacturers and importers who sell and market products within the EU and it is mandatory across Europe. Important: all products which consume energy above the minimum level will not be able to be sold within the EU from 1 July 2016.

SI 2020 No. 1528.

Important: all products which consume energy above the minimum level will not be able to be sold within the EU from 1 July 2016.







ecostore Premium 2 Glass Door Digital Refrigerator, 1430lt (+2/+10) - R290



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.