

Pastry and Bakery Line 3 Door Freezer Counter, -24°/-10° C, 600X400 grid



ITEM #		
MODEL #		
NAME #		
SIS #	 	
AIA #		

- Suitable for use in ambient temperature of up to 40°C (climatic class 5).
- Completely automatic defrosting and automatic evaporation of defrost water by hot gas.
- Electronic control panel and digital display.
- Frontal access for easy maintenance.
- Internal runners removable without any tools for faster cleaning operations.
- The position of the evaporator and the design of the internal ventilation facilitate the uniformity of
- Stainless steel AISI 304 internal and external panels including back.
- Rounded internal corners for ease of cleaning.
- Adjustable feet from 140mm to 240mm.



- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC
- Insulation thickness: 60 mm to ensure effective insulation with minimum energy consumption.
- Removable triple-chamber balloon magnetic gasket to improve insulation and reduce energy consumption and ease of cleaning.

Included Accessories

9 of Pair of runners 600x400 mm PNC 880673

Optional Accessories

- Stainlees steel grid, 600x400mm PNC 728876 🗅
- 4 wheels (2 of which with brake) PNC 880669
- Door lock kit for Pastry Counter PNC 880671
- Pair of runners 600x400 mm for PNC 880673 🗅
- RS485 driver connector for PNC 880674 🛛



Pastry and Bakery Line 3 Door Freezer Counter, -24°/-10°C, 600X400 grid



Pastry and Bakery Line 3 Door Freezer Counter, -24°/-10°C, 600X400 grid



Electric

Supply voltage: Electrical power, max:	230 V/1N ph/50 Hz 0.41 kW
Key Information:	
Net Volume:	360 比
N° of doors:	3
	5
Door hinges:	
External dimensions, Width:	2006 mm
External dimensions,	2000 11111
Depth:	800 mm
External dimensions, Depth	
with Doors Open:	1280 mm
External dimensions,	
Height:	850 mm
	Stainless Steel AISI 304
Type of external material:	Scotch Brite
Type of internal material:	304 AISI
Internal side panels	
material:	304 AISI
Gross capacity:	
Type of model (EU	
Regulation. 2015/1094):	counter frozen

Refrigeration Data

Control type:	
Refrigeration power at evaporation temperature:	-30 °C
Operating temperature min.:	-24 °C
Operating temperature max.:	-10 °C

Sustainability

R290
3
D
2804kWh/year - 8kWh/24h
Heavy Duty (5)
63



Pastry and Bakery Line 3 Door Freezer Counter, -24°/-10°C, 600X400 grid

енертия •	
	PLEF3NL
A+++ A++ A+ B C D E F G	
ENERGIA · ЕНЕРГИЯ ENEPTEIA · ENERGIJA ENERGY · ENERGIE · ENERGI	2804 kWh/annum
- L 2015/1094-IV	↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓



Pastry and Bakery Line 3 Door Freezer Counter, -24°/-10°C, 600X400 grid



EU energy labelling from 1st July 2016 The European energy labelling scheme for professional refrigerators and freezers is based on requirements setting Minimum Energy Performance standards for commercial refrigeration cabinets sold within the EU. These requirements are designed to drive energy efficiency and environmentally friendly approach for professionals. The European energy labelling scheme will apply to all manufacturers and importers who sell and market products within the EU and it is mandatory across Europe. Important: all products which consume energy above the minimum level will not be able to be sold within the EU from 1 July 2016.

SI 2020 No. 1528.

Important: all products which consume energy above the minimum level will not be able to be sold within the EU from 1 July 2016.

