

Ice Makers Granular Ice, 178kg/24h, 64kg bin, water-cooled

| ITEM # | | |
|---------|--|--|
| MODEL # | | |
| NAME # | | |
| | | |
| SIS # | | |
| AIA# | | |



730290 (IGF166I64SNP)

Ice Maker, Granular Ice, 178 kg/24h, self-contained, 64kg ice collection bin included, water-cooled

Short Form Specification

Item No.

Water cooled granularice maker, self-contained with 64kg bin. Height adjustable feet. AISI 304 stainless steel exterior, food grade and internal ice container in ABS, AISI 316 evaporator ensure safe contact with ice. Fully automatic in operation and easy cleanability thanks to the automatic cleaning system. The ice making method guarantees continuous and reliable production. Electronic board controls the set parameters. Bin with internal corner for easy cleaning and it is fully insulated. Supplied with flexible water supply, drain hosed and scoop. Hydrocarbon refrigerant gas R290 for the lowest environmental impact.

Main Features

- The ice making method guarantees a continuous and reliable production.
- Easy cleanability guaranteed by an automatic system: the cleaning switch activate the circulation and the rinse of water; at the end of the cycle just swithed again to start producing ice.
- The ice-making method (crushing system) guarantees compact, hygienically pure crushed ice that is resistant to melting.
- Water consumption and productivity calculated using 15°C water temperature and 21°C ambient temperature.
- Fully automatic in operation.
- Rounded internal corners of the bin assure ease of cleaning.
- Food grade ABS interior.
- Suitable for gravity drain only.
- Bin included.
- Compliant to CE requirements for safety.

Construction

- Reliability guaranteed by the quality of the construction materials used (front, top and sides in 304 AISI stainless steel) and the sophisticated product and process technology involved.
- AISI 304 stainless steel exterior.
- AISI 316 evaporator ensures a safe contact with ice.
- Sturdy door opening system made in AISI 304 stainless steel.
- Internal ice containers in ABS.
- Supplied with flexible water supply, drain hoses and scoop.
- ON-OFF rocker switch.
- Adjustable 105-155mm feet.
- Plug as standard (schuko type).

Sustainability



- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free
- Reduced energy consumption by fully insulated storage bin.

Optional Accessories

• Drain pump kit


PNC 880690 🗖

APPROVAL:





lce Makers Granular Ice, 178kg/24h, 64kg bin, water-cooled



| Electric | |
|------------------------------|----------------------------------|
| Supply voltage: | 220-240 V/1N ph/50 Hz 0.65 kW |
| Electrical power, max: | 0.03 KVV |
| Capacity: | |
| Bin capacity: | 64 kg |
| Key Information: | |
| External dimensions, Width: | 515 mm |
| External dimensions, Depth: | 550 mm |
| External dimensions, Height: | 1460 mm |
| Net weight: | 75 kg |
| Output: | 178 kg/day |
| Sustainability | |

R290

80 g

49.4 lt/hr

Refrigerant type:

Refrigerant weight:

Water consumption:



Ice Makers Granular Ice, 178kg/24h, 64kg bin, water-cooled