

Ice Makers

Ice Cuber (22gr), 55kg/24h, 25kg bin, air-cooled

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



730304 (ICB55I25SNP)

Ice Maker, Cube (22gr), 55 kg/24h, self-contained, 25kg ice collection bin included, air-cooled

Short Form Specification

Item No. _____

Air cooled ice cube maker, self-contained with 25kg bin. Ice cube cone shape. Compact dimension and height adjustable feet. AISI 304 stainless steel exterior, food grade and internal ice container in ABS, aluminium evaporator ensure safe contact with ice. Sturdy door opening system in AISI 204 stainless steel. Fully automatic in operation and easy cleanability thanks to the automatic cleaning system. The ice making method guarantees continuous and reliable production, crystalline and hygienically pure ice cubes. Bin with internal corner for easy cleaning and it is fully insulated. Supplied with flexible water supply, drain hoses and scoop. Hydrocarbon refrigerant gas R290 for the lowest environmental impact.

Main Features

- The ice making method guarantees a continuous and reliable production.
- Easy cleanability guaranteed by an automatic system: the cleaning switch activate the circulation and the rinse of water; at the end of the cycle just swithed again to start producing ice.
- The ice-making method (spray layering) guarantees crystalline, compact, hygienically pure ice cubes that are resistant to melting.
- Water consumption and productivity calculated using 15°C water temperature and 21°C ambient temperature.
- Compact dimensions of the ice cubers make them highly suitable for any location, particularly those where space is at a premium.
- Ice cube cone shape.
- Fully automatic in operation.
- Rounded internal corners of the bin assure ease of cleaning.
- Food grade ABS interior.
- Suitable for gravity drain only.
- Bin included.
- Compliant to CE requirements for safety.
- The innovative anti-scale spray system with flexible nozzles avoids limescale deposits through small vibrations.

Construction

- Reliability guaranteed by the quality of the construction materials used (front, top and sides in 304 AISI stainless steel) and the sophisticated product and process technology involved.
- The sprayers are easy to take away, permit a simple flowing and prevent limestone formation.
- AISI 304 stainless steel exterior.
- Aluminium evaporator ensures a safe contact with ice.
- Sturdy door opening system made in AISI 304 stainless steel.
- Internal ice containers in ABS.
- Hygienical plastic spray arms removable without the use of tools.
- Supplied with flexible water supply, drain hoses and scoop.
- Easy access to the main components for maintenance.
- ON-OFF rocker switch.
- Adjustable 105-155mm feet.
- Plug as standard (schuko type).

APPROVAL: _____



Electrolux
PROFESSIONAL

Ice Makers Ice Cuber (22gr), 55kg/24h, 25kg bin, air-cooled

Sustainability



- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free.
- Reduced energy consumption by fully insulated storage bin.

Optional Accessories

- Kit of 4 small black feet, 13mm (0/+22mm) PNC 880692 ☐



Ice Makers
Ice Cuber (22gr), 55kg/24h, 25kg bin, air-cooled

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2025.05.19



Electric

Capacity:

Key Information:

Kind of cube:	Ice Cube 22 g
---------------	---------------

Water consumption: 5.9 lt/hr

Technical drawing of a rectangular box. The drawing shows a perspective view of the box. The dimensions are indicated by arrows and text: the width is 171.2 and the height is 171.2.

Rear side

Technical drawing of the rear view of the device. Dimensions are indicated in millimeters (mm):

- Top horizontal distance: 110,5
- Distance from top edge to the first horizontal slot: 87,5
- Distance from the bottom edge to the first horizontal slot: 139,2
- Distance between the two horizontal slots: 56,8
- Distance from the bottom edge to the second horizontal slot: 49,75

Connection points and labels:

- Two circular ports labeled "WQ Ø25" (Water Outlet).
- A square port labeled "WT Ø3/4" (Water Inlet).
- A label "AIR OUT" with wavy lines indicating air flow from the right side of the device.

Top

Technical drawing of a rectangular plate. The horizontal dimension is labeled 535. The vertical dimension is labeled 534,6.



2025.05.19