



**Electrolux**  
PROFESSIONAL

## Handling System for Rack Type Unloading Dishwashing Driven Curve 90° - Counterclockwise direction

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_



865246 (HSUC90CC)

Unloading curve Unit, 90°,  
Dishwasher driven, anti-  
clockwise

### Short Form Specification

Item No. \_\_\_\_\_

Constructed in 304 AISI stainless steel. Basin with sloping bottom and drain. Feeding bar. It is driven by the dishwasher. Square 40x40mm tubular leg on height-adjustable feet. Designed for 500x500mm dishwashing baskets. Knock-down delivery. Basket feed direction: anticlockwise.

### Main Features

- Dishwasher curve 90° is intended for installation between a dishwasher and a roller conveyor or manual sorting table (on the loading side).
- The curve is driven by the dishwasher as the feeding arm in the curve will be connected with the conveyor of the dishwasher.
- Available counterclockwise direction for unloading area.
- Loading curves provided with anti-jamming device to avoid rack jam.
- "Key holes" and "snap on" system reduces the number of screws needed for fast and easy installation.
- 45° cut corner to reduce space usage.
- Designed to transport 500x500 mm dishwashing baskets.

### Construction

- Three legs included.
- Stainless steel feet 50 mm adjustable in height to align the operation height between the dishwasher and table.
- AISI 304 1,2mm stainless steel basin.
- 40x40mm stainless steel tubular and square legs.
- All surfaces smooth with polished finish.
- Sloping bottom of the table grants a smooth and rapid drainage.
- Thick welded flanges for sturdy connection between the units.

APPROVAL: \_\_\_\_\_



Experience the Excellence  
[www.electroluxprofessional.com](http://www.electroluxprofessional.com)



**Electrolux**  
PROFESSIONAL

## Handling System for Rack Type Unloading Dishwashing Driven Curve 90° - Counterclockwise direction

### Optional Accessories

- Emergency stop kit for Rack Type Dishwasher (not for Basic handling system) PNC 865162 ☐

### Key Information:

External dimensions, Width:	
865246 (HSUC90CC)	850 mm
External dimensions, Depth:	850 mm
External dimensions, Height:	910 mm
Net weight:	23 kg
Height adjustment:	50/50 mm
Position to dishwasher:	Unloading
Basin material:	Stainless Steel AISI 304 - EN 1.4301



Handling System for Rack Type  
Unloading Dishwashing Driven Curve 90° - Counterclockwise direction

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2025.12.22