



Electrolux
PROFESSIONAL

Modular Cooking Range Line 900XP Half Module Electric Grill

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



391270 (E9GREDCFU)

Half module electric Grill
free standing

Short Form Specification

Item No. _____

Heating via incoloy armoured heating elements positioned under the cooking grid. Cooking surface grids in enameled cast iron, easily removable for cleaning. Includes drip tray for the collection of grease and fat. Exterior panels of unit in stainless steel with Scotch Brite finish. Extra strength worktop in heavy duty 2 mm stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Incoloy armoured heating elements positioned under the cooking grid.
- Each bank of elements has a temperature controlled thermostat.
- Power indicator light.
- Drip tray to collect residual cooking juices and fat.
- Stainless steel high splash guards on the rear and sides of cooking surface. Splash guards can be easily removed for cleaning and are dishwasher-safe.
- The special design of the control knob system guarantees against water infiltration.
- IPX5 water protection.
- Energy regulation through a control knob.
- Heating element can be tilted frontally for easy cleaning.
- Monoblock structure gives better stability and easier installation.
- The cooking surface is double-sided: one for meat and the other for fish and vegetables.
- The drawer can be filled with water to obtain vapor to cook softer food and to facilitate the cleaning of the drawer.
- The low temperature of the external panels allow to work in safety.
- Cooking grids made in highly resistant enameled cast iron for easy cleaning.

Construction

- Unit is 930 mm deep to give a larger working surface area.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- AISI 304 stainless steel worktop, 2mm thick.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Included Accessories

- 1 of Scraper for free standing grills PNC 206422

Optional Accessories

- Junction sealing kit PNC 206086 ☐
- Kit 4 wheels - 2 swivelling with brake - it is mandatory to install Base support and wheels PNC 206135 ☐
- Flanged feet kit PNC 206136 ☐
- Frontal kicking strip for concrete installation, 400mm PNC 206147 ☐
- Frontal kicking strip for concrete installation, 800mm PNC 206148 ☐

APPROVAL: _____



Experience the Excellence
www.electroluxprofessional.com

• Frontal kicking strip for concrete installation, 1000mm	PNC 206150	☐
• Frontal kicking strip for concrete installation, 1200mm	PNC 206151	☐
• Frontal kicking strip for concrete installation, 1600mm	PNC 206152	☐
• Pair of side kicking strips for concrete installation	PNC 206157	☐
• Frontal kicking strip, 400mm (not for refr-freezer base)	PNC 206175	☐
• Frontal kicking strip, 800mm (not for refr-freezer base)	PNC 206176	☐
• Frontal kicking strip, 1000mm (not for refr-freezer base)	PNC 206177	☐
• Frontal kicking strip, 1200mm (not for refr-freezer base)	PNC 206178	☐
• Frontal kicking strip, 1600mm (not for refr-freezer base)	PNC 206179	☐
• Pair of side kicking strips (not for refr-freezer base)	PNC 206180	☐
• 2 panels for service duct for single installation	PNC 206181	☐
• 2 panels for service duct for back to back installation	PNC 206202	☐
• Kit 4 feet for concrete installation (not for 900 line free standing grill)	PNC 206210	☐
• Water filling tap for free standing grills (1 per each drawer)	PNC 206280	☐
• Water column extension for 900 line	PNC 206290	☐
• Chimney upstand, 400mm	PNC 206303	☐
• Back handrail 800 mm	PNC 206308	☐
• Back handrail 1200 mm	PNC 206309	☐
• Base support for feet or wheels - 400mm (700/900)	PNC 206366	☐
• Base support for feet or wheels - 800mm (700/900)	PNC 206367	☐
• Base support for feet or wheels - 1200mm (700/900)	PNC 206368	☐
• Base support for feet or wheels - 1600mm (700/900)	PNC 206369	☐
• Base support for feet or wheels - 2000mm (700/900)	PNC 206370	☐
• Rear paneling - 600mm (700/900XP)	PNC 206373	☐
• Rear paneling - 800mm (700/900)	PNC 206374	☐
• Rear paneling - 1000mm (700/900)	PNC 206375	☐
• Rear paneling - 1200mm (700/900)	PNC 206376	☐
• Stainless steel grid with drainage channels for free standing V-shaped grills (900XP)	PNC 206409	☐
• Scraper for grids with drainage channels - top grills	PNC 206421	☐
• Scraper for free standing grills	PNC 206422	☐
• Base support for feet or wheels - 600mm (700/900)	PNC 206431	☐
• Side handrail-right/left hand (900XP)	PNC 216044	☐
• Frontal handrail, 400mm	PNC 216046	☐
• Frontal handrail, 800mm	PNC 216047	☐
• Frontal handrail, 1200mm	PNC 216049	☐
• Frontal handrail, 1600mm	PNC 216050	☐
• 2 side covering panels for free standing appliances	PNC 216134	☐
• Large handrail - portioning shelf, 400mm	PNC 216185	☐



Electrolux
PROFESSIONAL

Modular Cooking Range Line 900XP Half Module Electric Grill

- Large handrail - portioning shelf, 800mm PNC 216186 




**Modular Cooking Range Line
900XP Half Module Electric Grill**


The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2025.08.07

Front




Side



EI = Electrical inlet (power)
 EQ = Equipotential screw

Top



Electric

Supply voltage:	380-400 V/3N ph/50-60 Hz
Predisposed for:	
Electrical power, max:	7.5 kW
Total Watts:	7.5 kW

Key Information:

External dimensions, Width:	400 mm
External dimensions, Depth:	930 mm
External dimensions, Height:	850 mm
Net weight:	60 kg
Shipping weight:	74 kg
Shipping height:	1180 mm
Shipping width:	480 mm
Shipping depth:	1020 mm
Shipping volume:	0.58 m ³
Certification group:	EG91F
Cooking surface width:	316 mm
Cooking surface depth:	640 mm

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.