

# Modular Cooking Range Line 900XP Two Wells Electric Fryer 18 liter

TEM #	
MODEL #	
NAME #	
SIS #	
AIA #	



391095 (E9FREH2HF0)

18+18-It electric Fryer with 2 wells (internal heating elements), 4 half size baskets and lids included

391179 (E9FREH2HFN)

18+18-It electric Fryer with 2 wells (internal heating elements), 4 half size baskets and lids included

# **Short Form Specification**

#### Item No.

High efficiency tilting incoloy armoured heating elements (33kW) placed inside the wells. Deep drawn wells. Oil drains through a tap into a container positioned under the wells. Height adjustable feet in stainless steel. Exterior panels in stainless steel. Worktop in 20/10, stainless steel. Righangled side edges eliminate gaps and possible dirt traps between units

#### **Main Features**

- Interior of wells with seamlessly laser-welded corners for ease of cleaning.
- Swivelling incoloy armoured heating elements located inside the well can be lifted up for easier cleaning.
- Thermostatic regulation of oil temperature up to a maximum of 185 °C.
- Overheat protection thermostat as standard on all units.
- Oil drains through a tap into a drainage container positioned under the well.
- All major compartments located in front of unit for ease of maintenance.
- The special design of the control knob system guarantees against water infiltration.
- Unit delivered with four 50 mm legs in stainless steel as standard (all round Stainless steel kick plates as option).
- Supplied as standard with 4 half size baskets and 1 right and left side doors for cupboard.
- Optional portable oil quality monitoring tool (code 9B8081) for efficient oil management.

## Construction

- Unit is 930 mm deep to give a larger working surface area.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- IPX5 water resistance certification.

## **Included Accessories**

• 2 of Door for open base PNC 206350 cupboard

 2 of 2 half size baskets for 15lt PNC 927223 OptiOil and 18/23lt fryers

## Optional Accessories

Stainless steel oil filter for 18/23lt fryers
 Junction sealing kit
 Kit 4 wheels - 2 swivelling with brake - it is mandatory to install Base support and wheels

• Flanged feet kit PNC 206136 🖵

 Frontal kicking strip for concrete installation, 800mm

PNC 206148 □

 Frontal kicking strip for concrete installation, 1000mm

#### APPROVAL:






# Modular Cooking Range Line 900XP Two Wells Electric Fryer 18 liter


Frontal kicking strip for concrete installation, 1200mm	PNC 206151	
Frontal kicking strip for concrete	PNC 206152	
<ul><li>installation, 1600mm</li><li>Pair of side kicking strips for</li></ul>	PNC 206157	
<ul><li>concrete installation</li><li>Frontal kicking strip, 800mm (not for</li></ul>	PNC 206176	
refr-freezer base)		
<ul> <li>Frontal kicking strip, 1000mm (not for refr-freezer base)</li> </ul>	PNC 206177	
<ul> <li>Frontal kicking strip, 1200mm (not for refr-freezer base)</li> </ul>	PNC 206178	
<ul> <li>Frontal kicking strip, 1600mm (not for refr-freezer base)</li> </ul>	PNC 206179	
<ul> <li>Pair of side kicking strips (not for refr-freezer base)</li> </ul>	PNC 206180	
• 2 panels for service duct for single installation	PNC 206181	
• 2 panels for service duct for back to back installation	PNC 206202	
• Kit 4 feet for concrete installation (not for 900 line free standing grill)	PNC 206210	
Chimney upstand, 800mm	PNC 206304	
Back handrail 800 mm	PNC 206308	
Back handrail 1200 mm	PNC 206309	
Door for open base cupboard	PNC 206350	
Filter (inox) for fryer oil collection basin for 18lt, 23lt free standing	PNC 206359	
fryers (without oil recirculation pump)		
Base support for feet or wheels - 800mm (700/900)	PNC 206367	
Base support for feet or wheels - 1200mm (700/900)	PNC 206368	
Base support for feet or wheels - 1600mm (700/900)	PNC 206369	
Base support for feet or wheels - 2000mm (700/900)	PNC 206370	
• Rear paneling - 800mm (700/900)	PNC 206374	
• Rear paneling - 1000mm (700/900)	PNC 206375	
• Rear paneling - 1200mm (700/900)	PNC 206376	
• 2 side covering panels for free	PNC 216134	
standing appliances		
<ul> <li>2 half baskets for 18lt fryers with front hook</li> </ul>	PNC 927200	
• 1 full basket for 18lt fryers with front hook	PNC 927201	
• 2 half size baskets for 15lt OptiOil and 18/23lt fryers	PNC 927223	
• 1 full size basket for 15lt OptiOil and 18/23lt fryers	PNC 927226	






# Modular Cooking Range Line 900XP Two Wells Electric Fryer 18 liter





EI = Electrical inlet (power) EQ = Equipotential screw



## **Electric**

Front

Side

Supply voltage:

380-400 V/3N ph/50/60 Hz

391095 (E9FREH2HF0) 391179 (E9FREH2HFN)

**9FREH2HFN)** 230 V/3 ph/50/60 Hz

Predisposed for:

380-400V 3N~ 50/60Hz

**391095 (E9FREH2HF0)** 30-33kW

Total Watts: 33 kW

#### **Key Information:**

Usable well dimensions

(width): 340 mm

Usable well dimensions (height): 290 mm

Usable well dimensions

(depth): 400 mm

Well capacity: 18 It MIN; 20 It MAX
Thermostat Range: 105 °C MIN; 185 °C MAX

Net weight: 115 kg

Shipping weight:

**391095 (E9FREH2HF0)** 103 kg **391179 (E9FREH2HFN)** 105 kg

Shipping height:

**391095 (E9FREH2HF0)** 1080 mm **391179 (E9FREH2HFN)** 1120 mm **Shipping width:** 1020 mm

Shipping depth:

**391095 (E9FREH2HF0)** 880 mm **391179 (E9FREH2HFN)** 860 mm

Shipping volume:

**391095 (E9FREH2HF0)** 0.97 m<sup>3</sup> **391179 (E9FREH2HFN)** 0.98 m<sup>3</sup>

Certification group:

**391095 (E9FREH2HF0)** EFI9218 **391179 (E9FREH2HFN)** N9FE3

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

