

Modular Cooking Range Line 900XP 2-Burner Gas Boiling Top with 3mm worktop and electric ignition, 10

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA#	
AIA "	



391241 (E9GCGDTC0M)

2-Burner (10kW each) gas Boiling Top with 3mm WorkTop and electronic ignition

Short Form Specification

Item No.

To be installed on open base installations, bridging supports or cantilever systems. High efficiency flower flame burners with continuous power regulation and optimized combustion. Flame failure device as standard on burners to protect against accidental extinguishing. Electronic ignition for burners. Exterior panels of unit in stainless steel with Scotch Brite finish. Pan supports in heavy duty cast iron. Extra strength work top in heavy duty 3 mm stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features


- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- The two 10 kW high efficiency burners are available in 100 mm diameter with continuous power regulation from 2.2 kW to 10 kW.
- Gas appliance supplied for use with natural or LPG gas, conversion jets supplied as standard.
- Large sized pan support in cast iron (stainless steel as option) with long center fins to allow the use of the largest down to the smallest pans.
- Burners with optimized combustion.
- Flame failure device on each burner protects against gas leakage when accidental extinguishing of the flame occurs.
- The special design of the control knob system guarantees against water infiltration.
- IPX5 water protection.
- Suitable for countertop installation.

Construction

- Unit is 930 mm deep to give a larger working surface area.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- · Electric ignition.
- AISI 304 stainless steel worktop, 3mm thick.

APPROVAL:








Optional Accessories


optional / tecessories		
 Junction sealing kit Draught diverter, 120 mm diameter	PNC 206086 PNC 206126	
 Matching ring for flue condenser, 120 mm diameter 	PNC 206127	
 Support for bridge type installation, 800mm 	PNC 206137	
 Support for bridge type installation, 1000mm 	PNC 206138	
 Support for bridge type installation, 1200mm 	PNC 206139	
 Support for bridge type installation, 1400mm 	PNC 206140	
 Support for bridge type installation, 1600mm 	PNC 206141	
 Support for bridge type installation, 400mm 	PNC 206154	
 Single burner smooth plate for direct cooking - fits frontal burners only 	PNC 206171	
 Single burner ribbed plate for direct cooking - fits frontal burners only 	PNC 206172	
 Water column with swivel arm (water column extension not included) 	PNC 206289	
 Water column extension for 900 line 	PNC 206290	
• Stainless steel double grid for 2 burners	PNC 206298	
Chimney upstand, 400mm	PNC 206303	
Back handrail 800 mm	PNC 206308	
Back handrail 1200 mm	PNC 206309	
Flue condenser for 1/2 module, 120 mm diameter	PNC 206310	
• Wok pan support for open burners (700/900)	PNC 206363	
Kit town gas nozzles (G150) for 900 gas boiling top	PNC 206384	
 Chimney grid net, 400mm (700XP/900) 	PNC 206400	
 Side handrail-right/left hand (900XP) 	PNC 216044	
Frontal handrail, 400mm	PNC 216046	
Frontal handrail, 800mm	PNC 216047	
Frontal handrail, 1200mm	PNC 216049	
 Frontal handrail, 1600mm 	PNC 216050	
 Large handrail - portioning shelf, 400mm 	PNC 216185	
 Large handrail - portioning shelf, 800mm 	PNC 216186	
 2 side covering panels for top appliances 	PNC 216278	
 Pressure regulator for gas units 	PNC 927225	





Modular Cooking Range Line 900XP 2-Burner Gas Boiling Top with 3mm worktop and electric ignition, 10 kW





Electrical inlet (power) Gas connection

> 15/16 " 3 15/16 " 100 mm

Gas

Gas Power: 20 kW

Standard gas delivery: Natural Gas G20 (20mbar)

Gas Type Option: LPG; Natural Gas

Gas Inlet: 1/2"

Key Information:

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

External dimensions, Width: 400 mm 930 mm External dimensions, Depth: External dimensions, Height: 250 mm Net weight: 43 kg Shipping weight: 46 kg Shipping height: 540 mm Shipping width: 480 mm Shipping depth: 1040 mm Shipping volume: 0.27 m³

Front Burners Power: ISO 9001; ISO 14001 - kW


Back Burners Power: 10 - 0 kW Certification group: N9CG

Back Burners Dimension -

Ø 100 mm

Front Burners Dimension -

Ø 100 mm



Top

Modular Cooking Range Line 900XP 2-Burner Gas Boiling Top with 3mm worktop and electric ignition, ... 10 kW

