

Modular Cooking Range Line 900XP 4-Burner Gas Range on Electric Oven Town Gas

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



391195 (E9GCTH4CEM)

4-Burner (1x7,5 kW - 3x5,5 kW) gas Range on electric Oven (6 kW) - town gas

Short Form Specification

Item No.

To be installed on stainless steel feet with height adjustment up to 50 mm. High efficiency flower flame burners with continuous power regulation and optimized combustion. Flame failure device as standard on burners to protect against accidental extinguishing. Oven chamber with 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans). Ribbed, cast-iron oven base plate. Exterior panels of unit in stainless steel with Scotch Brite finish. Pan supports in heavy duty cast iron. Extra strength work top in heavy duty 2 mm stainless steel. Rightangled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on stainless steel feet with height adjustment up to 50 mm. Unit can be easily mounted on cantilever systems.
- The three 6 kW and one 10 kW high efficiency burners are available in two different sizes to suit high performing cooking requirements of the most demanding customers:
 - -60 mm burners with continuous power regulation from 1,5 to 6 kW
 - -100 mm burners with continuous power regulation from 2.2 kW to 10 kW
- Gas burners supplied for use with town gas.
- Large sized pan support in cast iron (stainless steel as option) with long center fins to allow the use of the largest down to the smallest pans.
- Burners with optimized combustion.
- Flame failure device on each burner protects against gas leakage when accidental extinguishing of the flame occurs.
- Protected pilot light.
- Base compartment consists of an electric standard oven with 40 mm thick oven door for heat insulation, positioned beneath the base plate.
- Oven chamber with 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans).
- Ribbed cast iron oven base plate.
- Oven thermostat adjustable from 110 °C to 285 °C.
- The special design of the control knob system guarantees against water infiltration.
- IPX5 water protection.

Construction

- Unit is 930 mm deep to give a larger working surface area.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- AISI 304 stainless steel worktop, 2mm thick.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Included Accessories

• 1 of GN2/1 chrome grid for static PNC 164250 oven

Optional Accessories

- ullet GN2/1 chrome grid for static oven PNC 164250 $\ \Box$
- Junction sealing kit PNC 206086 \square
- Draught diverter, 150 mm PNC 206132 ☐ diameter
- Matching ring for flue condenser, PNC 206133
 150 mm diameter

APPROVAL:





Modular Cooking Range Line 900XP 4-Burner Gas Range on Electric Oven Town Gas


•	Kit 4 wheels - 2 swivelling with brake -	PNC 206135		• Frontal handrail, 800mm	PNC 216047
	it is mandatory to install Base support and wheels			Frontal handrail, 1200mm	PNC 216049
_	Flanged feet kit	PNC 206136		• Frontal handrail, 1600mm	PNC 216050
	Frontal kicking strip for concrete	PNC 206148		 2 side covering panels for free standing appliances 	PNC 216134
·	installation, 800mm	1110 200140	_	Large handrail - portioning shelf,	PNC 216186
•	Frontal kicking strip for concrete installation, 1000mm	PNC 206150		800mm • Pressure regulator for gas units	PNC 927225
•	Frontal kicking strip for concrete installation, 1200mm	PNC 206151		Tressure regulator for gas office	1110 727223
•	Frontal kicking strip for concrete installation, 1600mm	PNC 206152			
•	Pair of side kicking strips for concrete installation	PNC 206157			
•	Single burner smooth plate for direct cooking - fits frontal burners only	PNC 206171			
•	Single burner ribbed plate for direct cooking - fits frontal burners only	PNC 206172			
•	Frontal kicking strip, 800mm (not for refr-freezer base)	PNC 206176			
	Frontal kicking strip, 1000mm (not for refr-freezer base)	PNC 206177			
•	Frontal kicking strip, 1200mm (not for refr-freezer base)	PNC 206178			
	Frontal kicking strip, 1600mm (not for refr-freezer base)	PNC 206179			
	Pair of side kicking strips (not for refr- freezer base)	PNC 206180			
	2 panels for service duct for single installation	PNC 206181	_		
	2 panels for service duct for back to back installation	PNC 206202	_		
	Kit 4 feet for concrete installation (not for 900 line free standing grill)	PNC 206210	_		
	Flue condenser for 1 module, 150 mm diameter	PNC 206246			
	Water column with swivel arm (water column extension not included)	PNC 206289			
	Water column extension for 900 line	PNC 206290			
	Stainless steel double grid for 2 burners				
	Chimney upstand, 800mm	PNC 206304			
	Back handrail 800 mm	PNC 206308			
	Back handrail 1200 mm	PNC 206309	_		
•	Filter (inox) for fryer oil collection basin for 18lt, 23lt free standing fryers (without oil recirculation pump)	PNC 206359			
•	Wok pan support for open burners (700/900)	PNC 206363			
•	Base support for feet or wheels - 800mm (700/900)	PNC 206367			
•	Base support for feet or wheels - 1200mm (700/900)	PNC 206368			
	Base support for feet or wheels - 1600mm (700/900)	PNC 206369			
	Base support for feet or wheels - 2000mm (700/900)	PNC 206370			
	Rear paneling - 800mm (700/900)	PNC 206374			
	Rear paneling - 1000mm (700/900)	PNC 206375			
	Rear paneling - 1200mm (700/900)	PNC 206376			
	Kit town gas nozzles (G150) for 900 gas boiling top				
	Chimney grid net, 400mm (700XP/900)	PNC 206400			
•	Side handrail-right/left hand (900XP)	PNC 216044			






Modular Cooking Range Line 900XP 4-Burner Gas Range on Electric Oven Town Gas

31 1/2 " 800 mm 2 3/16 " 27 1/16 " 28 mm 2 3/16 " 56 mm



El = Electrical inlet (power)

G = Gas connection



Electric

Predisposed for:

380-400V 3N~ 50/60Hz

391195 (E9GCTH4CEM) 5.5-6kW

Gas

Gas Power: 28 kW

Standard gas delivery: Natural Gas G20 (20mbar)
Gas Type Option: LPG; Natural Gas; Town

Gas Inlet: 1/2"

Key Information:

Front Burners Power: 5.5 - 5.5 kW Back Burners Power: 5.5 - 7.5 kW

Back Burners Dimension -

mm Ø 60 Ø 100

Front Burners Dimension -

mm Ø 60 Ø 60

Oven Heat Input: 6 kW

Oven working Temperature: $\,$ 110 °C MIN; 285 °C MAX

Oven Cavity Dimensions (width):

width): 575 mm

Oven Cavity Dimensions (height): 300 mm

Oven Cavity Dimensions

(depth): 700 mm

External dimensions, Width: 800 mm
External dimensions, Depth: 930 mm

External dimensions, Height: 850 mm
Net weight: 155 kg
Shipping weight: 138 kg

Shipping height: 1120 mm
Shipping width: 1020 mm
Shipping depth: 860 mm
Shipping volume: 0.98 m³

Certification group: N9CT

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Modular Cooking Range Line 900XP 4-Burner Gas Range on Electric Oven Town Gas