

Modular Cooking Range Line 900XP 4-Burner Gas Range on Gas Oven

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



391005 (E9GCGH4CG0)

4-Burner (1x10 kW, 3x6 kW) gas Range on gas Oven (8,5 kW)

Short Form Specification

Item No.

To be installed on stainless steel feet with height adjustment up to 50 mm. High efficiency flower flame burners with continuous power regulation and optimized combustion. Flame failure device as standard on burners to protect against accidental extinguishing. Oven chamber with 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans). Ribbed, cast-iron oven base plate. Exterior panels of unit in stainless steel with Scotch Brite finish. Pan supports in heavy duty cast iron. Extra strength work top in heavy duty 2 mm stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on stainless steel feet with height adjustment up to 50 mm. Unit can be easily mounted on cantilever systems.
- The three 6 kW and one 10 kW high efficiency burners are available in two different sizes to suit high performing cooking requirements of the most demanding customers:
 - -60 mm burners with continuous power regulation from 1,5 to 6 kW
 - -100 mm burners with continuous power regulation from 2.2 kW to 10 kW
- Gas appliance supplied for use with natural or LPG gas, conversion jets supplied as standard.
- Large sized pan support in cast iron (stainless steel as option) with long center fins to allow the use of the largest down to the smallest pans.
- Burners with optimized combustion.
- Flame failure device on each burner protects against gas leakage when accidental extinguishing of the flame occurs.
- Protected pilot light.
- Base compartment consists of a gas heated standard oven with stainless steel burners and self stabilizing flame positioned beneath the base plate. Oven chamber to have 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans) and ribbed cast iron base plate.
- Oven thermostat adjustable from 120 °C to 280 °C.
- 40 mm thick oven door for heat insulation.
- The special design of the control knob system guarantees against water infiltration.
- IPX5 water protection.
- Control knobs provide smooth, continuous rotation from min to max power level.

Construction

- Unit is 930 mm deep to give a larger working surface area.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- AISI 304 stainless steel worktop, 2mm thick.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Included Accessories

 1 of GN2/1 chrome grid for static oven

PNC 164250

Optional Accessories

- GN2/1 chrome grid for static PNC 164250 ☐ oven
- Junction sealing kit PNC 206086 □

APPROVAL:






Modular Cooking Range Line 900XP 4-Burner Gas Range on Gas Oven


	Draught diverter, 150 mm diameter	PNC 206132		• Base support for feet or wheels - PNC 206370 2000mm (700/900)	
•	 Matching ring for flue condenser, 150 mm diameter 	PNC 206133		• Rear paneling - 800mm (700/900) PNC 206374	
	Kit 4 wheels - 2 swivelling with	PNC 206135		• Rear paneling - 1000mm (700/900) PNC 206375	
	brake - it is mandatory to install	1110 200100	_	• Rear paneling - 1200mm (700/900) PNC 206376	
	Base support and wheels			• Kit town gas nozzles (G150) for 900 PNC 206385	
•	Flanged feet kit	PNC 206136		gas ranges on gas oven	
•	Frontal kicking strip for concrete installation, 800mm	PNC 206148		• Chimney grid net, 400mm PNC 206400 (700XP/900)	
•	Frontal kicking strip for concrete installation, 1000mm	PNC 206150		• Side handrail-right/left hand PNC 216044 (900XP)	
•	Frontal kicking strip for concrete installation, 1200mm	PNC 206151		 Frontal handrail, 800mm Frontal handrail, 1200mm PNC 216047 PNC 216049 	
•	Frontal kicking strip for concrete installation, 1600mm	PNC 206152		• Frontal handrail, 1600mm PNC 216050	
•	Pair of side kicking strips for concrete installation	PNC 206157		standing appliances	
•	Single burner radiant plate for pan support	PNC 206170		• Large handrail - portioning shelf, PNC 216185 400mm	
	Single burner smooth plate for	PNC 206171		 Large handrail - portioning shelf, PNC 216186 800mm 	
	direct cooking - fits frontal burners only			• Pressure regulator for gas units PNC 927225	
•	Single burner ribbed plate for direct cooking - fits frontal burners only	PNC 206172			
•	Frontal kicking strip, 800mm (not for refr-freezer base)	PNC 206176			
•	Frontal kicking strip, 1000mm (not for refr-freezer base)	PNC 206177			
•	Frontal kicking strip, 1200mm (not for refr-freezer base)	PNC 206178			
•	Frontal kicking strip, 1600mm (not for refr-freezer base)	PNC 206179			
•	Pair of side kicking strips (not for refr-freezer base)	PNC 206180			
•	2 panels for service duct for single installation	PNC 206181			
•	2 panels for service duct for back to back installation	PNC 206202			
•	Kit 4 feet for concrete installation (not for 900 line free standing grill)	PNC 206210			
•	Flue condenser for 1 module, 150 mm diameter	PNC 206246			
•	Water column with swivel arm (water column extension not included)	PNC 206289			
•	Water column extension for 900 line	PNC 206290			
•	Stainless steel double grid for 2 burners	PNC 206298			
•	Chimney upstand, 800mm	PNC 206304			
	Back handrail 800 mm	PNC 206308			
	Back handrail 1200 mm	PNC 206309			
	Wok pan support for open burners (700/900)	PNC 206363			
•	Base support for feet or wheels - 800mm (700/900)	PNC 206367			
•	Base support for feet or wheels - 1200mm (700/900)	PNC 206368			
•	Base support for feet or wheels -	PNC 206369			
	1600mm (700/900)			Modular Cooking Range Line	






Modular Cooking Range Line 900XP 4-Burner Gas Range on Gas







Gas

Gas Power: 36.5 kW

Standard gas delivery: Natural Gas G20 (20mbar)

Gas Type Option: LPG;Natural Gas

Gas Inlet: 1/2"

Key Information:

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Oven working Temperature: 120 °C MIN; 280 °C MAX

Oven Cavity Dimensions

(width): 575 mm

Oven Cavity Dimensions (height): 300 mm

Oven Cavity Dimensions (depth): 700 mm External dimensions, Width: 800 mm External dimensions, Depth: 930 mm External dimensions, Height: 850 mm Net weight: 115 kg Shipping weight: 137 kg Shipping height: 1080 mm Shipping width: 1020 mm Shipping depth: 860 mm Shipping volume: 0.95 m³ Front Burners Power: 6 - 6 kW

Certification group: **Back Burners Dimension -**

Back Burners Power:

Ø 60 Ø 100

6 - 10 kW

N9CG

Front Burners Dimension -

Ø60 Ø60

Modular Cooking Range Line 900XP 4-Burner Gas Range on Gas Oven

