

Modular Cooking Range Line 900XP Electric Grill Top HP 800mm

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA#	



391347 (E9GREHGS0P)

Full module electric Grill Top

Short Form Specification

Item No.

Heating via incoloy armoured heating elements positioned under the cooking grid. Cooking surface grids are easily removable for cleaning. Heating elements can be tilted. Integrated water tap. Fixed well with drain. Extra strength work top in heavy duty 2 mm stainless steel. Right-angled side edges to allow flush-fitting junction between units. WRAS compliant. 380-400 V.

Main Features

- Incoloy armoured heating elements positioned under the cooking grid.
- Each bank of elements has an independent power regulation through a control knob.
- Power indicator light.
- Heating elements tilt 90° for easy cleaning.
- Removable 2mm thick steel U-shaped grids in AISI 441 stainless steel for fast heating of cooking surface.
- Fixed well with drain to collect residual cooking juices and grease.
- Large drain protected by overflow and filter.
- Water must be added to well before operation.
- Led warning indicator to give an alarm when well is empty.
- Water filling tap with knob control.
- Removable stainless steel deflectors to recuperate heat and reduce cooking time.
- Stainless steel splash guards on sides of cooking surface. Splash guards can be easily removed for cleaning.
- Top configuration allows installation on ambient base or refrigerated/freezer base.
- Suitable for countertop installation.

Construction

- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- AISI 304 stainless steel worktop, 2mm thick.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- Unit is 930 mm deep to give a larger working surface area.

APPROVAL:






Modular Cooking Range Line 900XP Electric Grill Top HP 800mm


Included Accessories

• 1 of Scraper for HP electric grill	PNC 206436	
Optional Accessories		
Junction sealing kit	PNC 206086	
 Support for bridge type installation, 800mm 	PNC 206137	
 Support for bridge type installation, 1000mm 	PNC 206138	
• Support for bridge type installation, 1200mm	PNC 206139	
• Support for bridge type installation, 1400mm	PNC 206140	
 Support for bridge type installation, 1600mm 	PNC 206141	
 Chimney grid net, 590mm (700XP/900) 	PNC 206403	
Scraper for HP electric grill	PNC 206436	
• Drain extension for Electric grill HP	PNC 206437	
• Side handrail-right/left hand (900XP)	PNC 216044	
 Frontal handrail, 800mm 	PNC 216047	
 Frontal handrail, 1200mm 	PNC 216049	
 Frontal handrail, 1600mm 	PNC 216050	
 Large handrail - portioning shelf, 800mm 	PNC 216186	
 2 side covering panels for top appliances 	PNC 216278	




Modular Cooking Range Line 900XP Electric Grill Top HP 800mm





FΙ Electrical inlet (power) EQ Equipotential screw Water inlet



Electric

Supply voltage: 380-400 V/3N ph/50/60 Hz 380-400V 3N~ 50/60Hz

Predisposed for: 10.8-11.6kW

Electrical power, max: 11.6 kW

Key Information:

If appliance is set up either next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

External dimensions, Width: 800 mm External dimensions, Depth: 930 mm External dimensions, Height: 250 mm Net weight: 85 kg HEG9E2 Certification group: Cooking surface width: 705 mm Cooking surface depth: 598 mm









