

Modular Cooking Range Line 900XP Gas Automatic Pasta Cooker 190 litres

391115 (E9PCGL1SF0)	Automatic Pasta Cooker- direct gas 160/190lt with 1x20kg tilting baskets			
Short Form Specification				
Item No.				
High efficiency 30 kW burners. Suitable for natural gas or				

High efficiency 30 kW burners. Suitable for natural gas or LPG. Constant water level refill and water topping up. The 190 liter tank is pressed in 316-L type stainless steel and features only rounded corners. Adjustable stainless steel feet, 50 mm in height. Body and base of unit entirely in stainless steel. Heavy duty stainless steel internal frame. Insulated lid and counter-balancing springs to simplify use.

ITEM #		
MODEL #		
NAME #		
<u>SIS #</u>		
AIA #	 	 

## **Main Features**

- High productivity and quality thanks to the high thermal efficiency and automatic cooking time control.
- Water basin fitted with overflow pipe to eliminate foam.
- Large drainage tap is provided on which baskets can be placed for draining purposes.
- 190 liters water basin in 316-L AISI Stainless Steel.
- Constant water level refill.
- Automatic water topping.
- Automatic ignition when water reaches minimum level and probe with electrovalve to protect from overheating in case of water absence.
- Digital timer guarantees precise settings of cooking parameters.
- Simple and functional control panel.
- The special design of the control knob system guarantees against water infiltration.
- Elevating basket is automatically tilted at the end of the cooking cycle.
- Combustion chamber and load bearing frame in stainless steel.
- Burners in stainless steel with pilot light, safety valve and flame failure device.
- Piezo spark ignition with thermocouple for added safety.
- Heavy duty internal frame in Stainless steel and external panelling with satin finish.
- IPX5 water protection.

#### APPROVAL:



## **Optional Accessories**

<ul> <li>Draught diverter, 150 mm diameter</li> </ul>	PNC 206132	
<ul> <li>Matching ring for flue condenser, 150 mm diameter</li> </ul>	PNC 206133	
<ul> <li>Frontal kicking strip for concrete installation, 1200mm</li> </ul>	PNC 206151	
<ul> <li>Frontal kicking strip for concrete installation, 1600mm</li> </ul>	PNC 206152	
<ul> <li>Frontal kicking strip, 1200mm (not for refr-freezer base)</li> </ul>	PNC 206178	
<ul> <li>Frontal kicking strip, 1600mm (not for refr-freezer base)</li> </ul>	PNC 206179	
<ul> <li>Pair of side kicking strips (not for refr- freezer base)</li> </ul>	PNC 206180	
• Frontal kicking strip for 23lt fryers in two parts	PNC 206203	
<ul> <li>Flue condenser for 1 module, 150 mm diameter</li> </ul>	PNC 206246	
<ul> <li>Base support for feet or wheels - 1200mm (700/900)</li> </ul>	PNC 206368	
<ul> <li>Base support for feet or wheels - 1600mm (700/900)</li> </ul>	PNC 206369	
Base support for feet or wheels - 2000mm (700/900)	PNC 206370	
<ul> <li>Rear paneling - 1200mm (700/900)</li> </ul>	PNC 206376	
• 2 side covering panels for free standing appliances	PNC 216134	
Trolley with lifting & removable tank	PNC 922403	



# **Electrolux**







### Gas

Gas Power:	30 kW	
Standard gas delivery:	Natural Gas G20 (20mbar)	
Gas Type Option:	LPG;Natural Gas	
Gas Inlet:	3/4"	
Water:		
Total hardness:	5-50 ppm	
Drain "D":	2"	
Incoming Cold/hot Water		
line size:	3/4"	
Electrolux Professional recommends the use of treated		

water, based on testing of specific water conditions. Please refer to user manual for detailed water quality

### **Key Information:**

Number of wells:	1
Usable well dimensions (width):	740 mm
Usable well dimensions (height):	465 mm
Usable well dimensions	
(depth):	550 mm
Well Capacity (MAX):	190 It MAX
Net weight:	212 kg
Shipping weight:	216 kg
Shipping height:	1500 mm
Shipping width:	1300 mm
Shipping depth:	1100 mm
Shipping volume:	2.15 m³
Certification group:	GGPC20

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.



DO

26 3/4 680 m 7/8 "

G

ΈI

EQ

⊕.

9 7/16 " 240 mm

14 3/16 " 360 mn

5

D

47 1/4 1200 mn 810 mm 36 5/8 " 930 mm

Modular Cooking Range Line 900XP Gas Automatic Pasta Cooker 190 litres

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.