

Modular Cooking Range Line 900XP Gas Cylindrical Boiling Pan 150lt direct heat

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



391107 (E9BSGHDRF0)

150-It gas Boiling Pan, direct heating

Short Form Specification

Item No.

Suitable for natural gas or LPG. To be installed on cantilever systems but also incorporates fixing points for bridging. Robust burners in stainless steel with flame failure device and protected pilot light. Exterior panels of unit in stainless steel with Scotch Brite finish. Pressed well with rounded edges manufactured from AISI 316 stainless steel. Rightangled side edges to allow flush-fitting junction between units.

Main Features

- Round kettle is suitable to cook, sauté or poach all kinds of produce.
- Produce is uniformly heated in the base and side walls of the kettle by a direct heating system.
- Appliance is IPX5 water resistance certified.
- Energy regulation through a control knob.
- No overshooting of cooking temperatures, fast reaction.
- Large capacity food tap enables safe and effortless discharging of contents.
- Ergonomic: the depth of the vessel facilitates stirring the food, also the most delicate food.
- Discharge tube and tap are very easy to clean from outside.
- Solenoid valve to refill with hot and cold water.
- Smooth large surfaces, easy access for cleaning.
- The special design of the control knob system guarantees against water infiltration.

Construction

- Pressed cooking vessel and double jacket in 316 AISI Stainless steel.
- Robust burners in stainless steel with flame failure device, protected pilot light and optimized combustion.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Sustainability



 Firmly fitting cover to reduce cooking time and save energy costs.

Optional Accessories

concrete installation

•	
 Junction sealing kit 	PNC 206086 □
Draught diverter, 150 mm	PNC 206132 🗖
diameter	
 Matching ring for flue condenser, 150 mm diameter 	PNC 206133 🗖
• Kit 4 wheels - 2 swivelling with	PNC 206135 🗖
brake - it is mandatory to	
install Base support and	
wheels	
 Flanged feet kit 	PNC 206136 🖵
 Frontal kicking strip for 	PNC 206148 🖵
concrete installation, 800mm	
• Frontal kicking strip for	PNC 206150 🖵
concrete installation, 1000mm	
• Frontal kicking strip for	PNC 206151 🗖
concrete installation, 1200mm	
Frontal kicking strip for	PNC 206152 🗖
concrete installation, 1600mm	
 Pair of side kicking strips for 	PNC 206157 🗖

APPROVAL:




Modular Cooking Range Line 900XP Gas Cylindrical Boiling Pan 150lt direct heat


• Frontal kicking strip, 800mm (not for refr-freezer base)	PNC 206176	
 Frontal kicking strip, 1000mm (not for refr-freezer base) 	PNC 206177	
Frontal kicking strip, 1200mm (not for refr-freezer base)	PNC 206178	
 Frontal kicking strip, 1600mm (not for refr-freezer base) 	PNC 206179	
Pair of side kicking strips (not for refr-freezer base)	PNC 206180	
2 panels for service duct for single installation	PNC 206181	
• 2 panels for service duct for back to back installation	PNC 206202	
• Kit 4 feet for concrete installation (not for 900 line free standing grill)	PNC 206210	
• Flue condenser for 1 module, 150 mm diameter	PNC 206246	
Chimney upstand, 800mm	PNC 206304	
Base support for feet or wheels - 800mm (700/900)	PNC 206367	
Base support for feet or wheels - 1200mm (700/900)	PNC 206368	
Base support for feet or wheels - 1600mm (700/900)	PNC 206369	
Base support for feet or wheels - 2000mm (700/900)	PNC 206370	
• Rear paneling - 800mm (700/900)	PNC 206374	
• Rear paneling - 1000mm (700/900)	PNC 206375	
• Rear paneling - 1200mm (700/900)	PNC 206376	
 Chimney grid net, 400mm (700XP/900) 	PNC 206400	
• 2 side covering panels for free standing appliances	PNC 216134	
• Trolley with lifting & removable tank	PNC 922403	
• 2-section universal basket for 150lt boiling pans	PNC 925019	
Measuring rod for 150 I Boiling Pan	PNC 927002	
 Pressure regulator for gas units 	PNC 927225	





Modular Cooking Range Line 900XP Gas Cylindrical Boiling Pan 150lt direct heat






CWI1 = Cold Water inlet 1 (cleaning)

= Electrical inlet (power) = Gas connection

G = Gas connection HWI = Hot water inlet



Electric

Supply voltage:

391107 (E9BSGHDRF0) 220-230 V/1 ph/50 Hz

Total Watts: 0.1 kW

Gas

Side

Gas Power: 24 kW

Standard gas delivery: Natural Gas G20 (20mbar)

Gas Type Option: LPG; Natural Gas

Gas Inlet: 1/2"

Key Information:

Pan useful capacity: 143 lt Vessel (round) diameter: 600 mm Net weight: 98 kg Shipping weight: 113 kg Shipping height: 1120 mm Shipping width: 1110 mm Shipping depth: 860 mm Shipping volume: 1.07 m³

No clearance needed on rear sides of unit if wall is of non combustible type. If wall is combustible, minimum 50 mm wall clearance should be maintained.

Certification group: N9PDG

