# **Electrolux**

Modular Cooking Range Line 900XP Gas Pasta Cooker, 1 Well, 40 litres



### **Short Form Specification**

#### Item No.

High efficiency 16.5 kW burners. Suitable for natural gas or LPG. Constant starch removal during the cooking process. The 40 liter tank is pressed in 316-L type stainless steel to protect against corrosion. Control panel with gas cock and piezo ignition. Safety thermostat prevents the machine from working without water. Height adjustable feet in stainless steel. Exterior panels in stainless steel. Worktop in 20/10, stainless steel. Right angled side edges eliminate gaps and possible dirt traps between units.

ITEM #	
MODEL #	
NAME #	
<u>SIS #</u>	
AIA #	

#### Main Features

- In addition to cooking pasta, the appliance can be used for noodles of every kind, rice, dumplings and veaetables.
- High efficiency 16.5 kW burners in stainless steel with flame failure device and power settings for each well, located below the well.
- Water basin in 316-L type Stainless steel.
- Water basin is seamlessly welded into the top of the appliance.
- Provided with integrated drip zone on which baskets can be placed for draining purposes.
- 40 liters water basin.
- Automatic starch removal function during cooking: improved water quality over time.
- Automatic low-water level shut-off: no accidental over-heating.
- Easy-to-use control panel with gas cock and piezo ignition.
- All major compartments located in front of unit for ease of maintenance.
- Continuous water filling regulated through a manual water tap.
- Large drain with manual ball-valve for fast emptying of well.
- Thermocouple device for added safety.
- Automatic lifting system (optional accessory): 200mm wide unit with three stainless steel basket supports, holding one GN 1/3 basket each, to be placed on either or both sides of machine to provide automatic lifting for six small portion baskets (to be ordered separately). Possibility to memorize nine cooking times through digital control.
- The special design of the control knob system guarantees against water infiltration.
- One piece pressed 2 mm work top in Stainless steel.
- Unit delivered with four 50 mm legs in stainless steel as standard (all round Stainless steel kick plates as option).

### Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- IPX5 water resistance certification.

#### Sustainability

- ESD available as accessory (installed separately): energy saving device uses heat produced by water drained through the overflow to pre-heat tap-in water up to 60°C, for constant water boiling.
- EnergyControl: unique feature for fine power adjustment to control boiling level and optimize energy consumption.

#### APPROVAL:

Experience the Excellence www.electroluxprofessional.com



## Modular Cooking Range Line 900XP Gas Pasta Cooker, 1 Well, 40 litres

			Decision (200 (200) DNC 20 (275	
Included Accessories			Rear paneling - 1000mm (700/900) PNC 206375	
	PNC 206350		<ul> <li>Rear paneling - 1200mm (700/900) PNC 206376</li> <li>Support frame for 2 pasta cooker PNC 206395</li> </ul>	
• •			basket (900XP)	
Optional Accessories			• Chimney grid net, 400mm (700XP/900) PNC 206400	
Junction sealing kit     Draught diverter 120 mm diameter	PNC 206086		• 2 square baskets, left and right for 40lt PNC 206433	
<ul> <li>Draught diverter, 120 mm diameter</li> <li>Matching ring for flue condenser, 120</li> </ul>	PNC 206126 PNC 206127		pasta cooker	_
mm diameter	FINC 200127		Kit G.25.3 (NI) gas nozzles for 700 and PNC 206465     900 pasta cookers	
<ul> <li>Kit 4 wheels - 2 swivelling with brake -</li> </ul>	PNC 206135		Side handrail-right/left hand (900XP) PNC 216044	
it is mandatory to install Base support			Frontal handrail, 400mm     PNC 216046	
and wheels • Flanged feet kit	PNC 206136		Frontal handrail, 800mm     PNC 216047	
<ul> <li>Frontal kicking strip for concrete</li> </ul>	PNC 200130		Frontal handrail, 1200mm     PNC 216049	
installation, 400mm		-	• Frontal handrail, 1600mm PNC 216050	
<ul> <li>Frontal kicking strip for concrete installation, 800mm</li> </ul>	PNC 206148		<ul> <li>2 side covering panels for free standing PNC 216134 appliances</li> </ul>	
<ul> <li>Frontal kicking strip for concrete</li> </ul>	PNC 206150		Large handrail - portioning shelf, PNC 216185	
installation, 1000mm			400mm • Larae handrail - portioning shelf, PNC 216186	
<ul> <li>Frontal kicking strip for concrete installation, 1200mm</li> </ul>	PNC 206151		800mm	<b>u</b>
<ul> <li>Frontal kicking strip for concrete installation, 1600mm</li> </ul>	PNC 206152		<ul> <li>3x1/3GN baskets for 40lt pasta cookers PNC 927210</li> <li>2x1/2GN baskets for 40lt pasta cookers PNC 927211</li> </ul>	
<ul> <li>Pair of side kicking strips for concrete</li> </ul>	PNC 206157		<ul> <li>3 round baskets diam. 181mm for 40lt PNC 927212</li> </ul>	
installation		-	pasta cookers (927219 must be ordered	
<ul> <li>Frontal kicking strip, 400mm (not for refr-freezer base)</li> </ul>	PNC 206175		<ul><li>together)</li><li>6 round baskets for 40-It pasta cookers PNC 927213</li></ul>	
• Frontal kicking strip, 800mm (not for	PNC 206176		(927219 must be ordered together)	-
refr-freezer base)			1x1/1GN basket for 40lt pasta cookers PNC 927216	
<ul> <li>Frontal kicking strip, 1000mm (not for refr-freezer base)</li> </ul>	PNC 206177		Grid support for 40lt pasta cooker PNC 927219     round baskets	
<ul> <li>Frontal kicking strip, 1200mm (not for refr-freezer base)</li> </ul>	PNC 206178		Pressure regulator for gas units     PNC 927225	
<ul> <li>Frontal kicking strip, 1600mm (not for refr-freezer base)</li> </ul>	PNC 206179		Upper support frame to hold 6 round PNC 960644 baskets for 40lt pasta cookers (alternative to 927219 for 6 round	
<ul> <li>Pair of side kicking strips (not for refr- freezer base)</li> </ul>	PNC 206180		baskets)	
<ul> <li>2 panels for service duct for single installation</li> </ul>	PNC 206181			
<ul> <li>Lid and lid holder for 40lt pasta cookers</li> </ul>	PNC 206190			
<ul> <li>2 panels for service duct for back to back installation</li> </ul>	PNC 206202			
• Kit 4 feet for concrete installation (not for 900 line free standing grill)	PNC 206210			
Set of ergonomic baskets for 40lt pasta cookers	PNC 206233			
<ul> <li>1 ergonomic basket for 40lt pasta cookers</li> </ul>	PNC 206237			
<ul> <li>False bottom for 40lt pasta cooker square baskets</li> </ul>	PNC 206238			
<ul> <li>Chimney upstand, 400mm</li> </ul>	PNC 206303			
<ul> <li>Back handrail 800 mm</li> </ul>	PNC 206308			
Back handrail 1200 mm	PNC 206309			
<ul> <li>Flue condenser for 1/2 module, 120 mm diameter</li> </ul>	PNC 206310			
Energy saving device for pasta cookers				
Door for open base cupboard	PNC 206350			
<ul> <li>Automatic programmable Basket Lifting System for 40lt Pasta Cookers, 3 lifters</li> </ul>	PNC 206353			
<ul> <li>Base support for feet or wheels (lateral) for 23lt fryers, pasta cookers and refrigerated bases (900XP)</li> </ul>	PNC 206372			
• Rear paneling - 800mm (700/900)	PNC 206374			



Modular Cooking Range Line 900XP Gas Pasta Cooker, 1 Well, 40 litres

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

## **Electrolux**

## Modular Cooking Range Line 900XP Gas Pasta Cooker, 1 Well, 40 litres







#### D

#### EQ G =





Modular Cooking Range Line 900XP Gas Pasta Cooker, 1 Well, 40 litres



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

## 5-50 ppm

Natural Gas G20 (20mbar)

LPG;Natural Gas

Incoming Cold/hot Water line size: 3/4" Electrolux Professional recommends the use of treated water, based on testing of specific water conditions. Please refer to user manual for detailed water quality information.

16.5 kW

1/2"

1"

### **Key Information:**

Gas

Gas Power:

Gas Inlet:

Water:

Drain "D":

Standard gas delivery:

Gas Type Option:

**Total hardness:** 

Usable well dimensions (width):	300 mm
Usable well dimensions (height):	260 mm
Usable well dimensions (depth):	520 mm
Well Capacity (MAX):	40 lt MAX
Net weight:	62 kg
Shipping weight:	58 kg
Shipping height:	1080 mm
Shipping width:	460 mm
Shipping depth:	1020 mm
Shipping volume:	0.51 m³
Certification group:	N9ECPG

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.