


Ventilation Equipment Condensation hood for 6 on 6 GN 2/1 or 6 on 10 GN 2/1 stacked electric lenghtwise combi ovens



ГЕМ #
10DEL #
IAME #
IS #
IA #

## **Main Features**

- Filtering surface protects against fire hazard.
- No need for an external exhaust pipe, thus eliminating carpentry costs.
- Complete ventilation system which eliminates the need for an exhaust duct with external connection.
- Fan motor with 3 automatic speeds:
  Low speed when door is closed and valve is closed;
- Medium speed when door is closed and valve is open;
- High speed when door is open.
- Frontal labyrinth and condensation filters are easy to remove and cleanable in a dishwasher.
- The cable connection between the hood and the oven makes possible the communication between them. Connection of the hood to the oven's software automatically activates fan power and odour absorption based on real oven activity.
- The hood and the oven are synchronized: the hood switches On/Off when the oven starts/ stops; based on real oven activity the hood automatically activates Hi/Medium/Low fan power for odour absorption.
- Can be used with 6 on 6 GN 2/1 or 6 on 10 GN 2/1 stacked electric LW combi ovens.
- Double step door opening (PNC 922265) is suggested to improve filtering performance.
- Calculate the air exchange rate for the complete kitchen environment and ensure the compliance with ventilation norms (e.g. VDI 2052 Standard for ventilation of commercial kitchens - or any local reference). An insufficient air exchange rate may cause malfunctioning of the hood.

# Construction

- Constructed entirely in 304 AISI stainless steel.
- Automatic door opening activation system.
- Multiple filtration systems:
  prefiltering of exhaust steam through stainless steel labyrinth filters;
- stainless steel labyrinth filters;
  condensation filter and extra droplets separator acting as a steam-liquid separator.
- Developed and produced in ISO 9001, ISO 14001 and ISO 50001 certified factory.
- Must be installed in a space where normal aeration, according to regulations, is present.


## Sustainability

• System guarantees correct suction as well as high energy saving.

Excelence



#### Ventilation Equipment Condensation hood for 6 on 6 GN 2/1 or 6 on 10 GN 2/1 stacked electric lenghtwise combi ovens



Ventilation Equipment Condensation hood for 6 on 6 GN 2/1 or 6 on 10 GN 2/1 stacked electric lengthwise combi ovens The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.



### Electric

Supply voltage:	220-240 V/1 ph/50 Hz
<b>Default Installed Power:</b>	0.4 kW
Koy Information	

#### Key Information:

External dimensions, Width:	1098 mm
External dimensions, Depth:	1266 mm
External dimensions, Height:	450 mm
Net weight:	86 kg
Shipping weight:	86 kg

