

## Hand held Mixers

### Bermixer PRO Turbo 650 W with Stainless Steel Tube (553mm)

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_



600377 (BP6555)

Portable Mixer, variable speed up to 10000 rpm, with stainless steel tube 553 mm, 650W

#### Short Form Specification

##### Item No.

Handheld mixer with stainless steel tube and space saving storing wall support. To be used directly in stew pots, even during cooking. Bayonet system ensures easy removal of accessories. Parts in contact with food - tube, blade, shaft - completely dismantlable without tools for easy cleaning. Bell knife design ensures antispash system and minimum handling during working operations. Flat motor base with ergonomic handle for a convenient grip. Electronic speed variator with speed regulation regardless of the load. Electronic speed adjustment by pulse on + and - buttons. Maximum speed: 10000 rpm. Safety feature requires both hands to start the machine. Design for heavy duty usage: double fan system to cool down the motor. Visible and water proof (IP55) control panel to control speed levels and overload warning light. Shaft locking device avoids release during operation. Whisk accessory available as an option.

#### Main Features

- Parts in contact with food - tube, blade, shaft - can be completely dismantled without tools for easy cleaning.
- Delivered with:
  - flat base motor
  - stainless steel tube
  - space saving storing wall support
- Anti-splash bell knife design.
- Tube, knife and whisks are dishwasher safe.
- Safety feature requires both hands to start the mixer (no volt release system).
- Light weight, ergonomic grip and adjustable speeds make preparation tasks fast and easy.
- Overheating warning red indicator.
- Bayonet system makes fast and simple to exchange tools.
- Productivity suitable for 50 to 300 meals per service.
- Designed to be used directly in stew pots up to 220 lt with the 55 cm tube and 240 lt with the 65 cm tube.

#### Construction

- Power: 650 watts.
- Maximum speed 10000 rpm.
- Motor has an air cooling system and is protected against overheating (in case of long intensive work).
- Smart speed control to ensure the right power according to the work load.
- Water protected motor unit (controls are IP55, IP34 throughout machine).

#### Included Accessories

- 1 of 553 mm stainless steel tube for Bermixer (for 450W, 550W, 650W, 750W) PNC 650134

#### Optional Accessories

- Reinforced whisk for portable Bermixer PNC 650108 ☐
- 353 mm stainless steel tube for portable mixer bermixer PNC 650132 ☐
- 453 mm stainless steel tube for portable mixer bermixer PNC 650133 ☐
- 553 mm stainless steel tube for Bermixer (for 450W, 550W, 650W, 750W) PNC 650134 ☐
- 653 mm stainless steel tube for Bermixer (for 650W, 750W) PNC 650135 ☐
- Adjustable rail for containers diam. 375 mm to 650 mm (to be used with 653294) PNC 653292 ☐

APPROVAL: \_\_\_\_\_

- Holder to support portable mixer in containers (can be used only with tube attachment) PNC 653294 ☐

Front




Side



EI = Electrical inlet (power)

Top



### Electric

|                        |                         |
|------------------------|-------------------------|
| Supply voltage:        | 220-240 V/1 ph/50/60 Hz |
| Electrical power, max: | 0.65 kW                 |
| Total Watts:           | 0.65 kW                 |

### Capacity:

|                   |           |
|-------------------|-----------|
| Capacity (up to): | 220 Litre |
|-------------------|-----------|

### Key Information:

|                              |         |
|------------------------------|---------|
| External dimensions, Width:  | 138 mm  |
| External dimensions, Depth:  | 120 mm  |
| External dimensions, Height: | 865 mm  |
| Shipping weight:             | 5.77 kg |
| Tube length:                 | 55 cm   |