



Simplicity Bubblers Chilled Beverage Dispensers 4x9 L, agitator model with locking lid

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____



CCCRKZ (ECS4E22)

Chilled Beverage Dispenser
with 4x9 liter bowls with
agitator and locking lid,
R290

Short Form Specification

Item No. _____

Chilled beverage dispenser, 4x9lt, with agitation function for fresh juices, coffees, or teas with minimal foaming system. Dispense 4 flavors in (4) 2.4 gallon / 9lt easy-clean bowls with 23 cm cup clearance. Easy-off bowl release system for faster and easier assembly and disassembly. Bowls with locking lid for added safety against tampering. Temperature range from 1.7 - 5° C. Pre-mix dispenser with stainless steel base and clear plastic bowls.

Main Features

- Agitation function for fresh juices, coffees, or teas with minimal foaming system.
- Easy-off bowl release system for faster and easier assembly and disassembly.
- User friendly design enables machine to dispense product till the very last drop.
- Dispense 4 flavors in (4) 9 L easy-clean bowls with 23 cm cup clearance.

Construction

- Temperature range from 1.7 - 5° C.
- Locking lid for added safety against tampering.
- Pre-mix dispenser with stainless steel base and clear plastic bowls.
- Fewer removable parts to simplify cleaning and reduce maintenance.
- The air intakes from the bottom and exhaust to back.
- Refrigerant type: R290.

APPROVAL: _____



Experience the Excellence
www.electroluxprofessional.com



Components

- 1 of **606468** (CS4E2D3D22FCELX) Base for chilled beverage dispenser, capacity 36 liters, R290
 - **Current consumption:** 2.5
 - **Shipping weight:** 38 kg
 - **Shipping height:** 530 mm
 - **Shipping width:** 480 mm
 - **Shipping depth:** 630 mm
 - **Shipping volume:** 0.16 m³
 - **Operating temperature min.:** 0 °C
 - **Operating temperature max.:** 0 °C
 - **Current consumption:** 2.5 Amps
 - **Refrigerant type:** R290
- 1 of **606626** (CS49ABPAFEWLKEX) 4x9 liter bowls for chilled beverage dispenser with agitator and locking lid
 - **Current consumption:** 0
 - **Shipping weight:** ISO 9001; ISO 14001 kg
 - **Shipping height:** 660 mm
 - **Shipping width:** 560 mm
 - **Shipping depth:** 300 mm
 - **Shipping volume:** 0.11 m³
 - **Operating temperature min.:** 0 °C
 - **Operating temperature max.:** 0 °C
 - **Current consumption:** 0 Amps

Electric

Supply voltage:	220-240 V/1N ph/50/60 Hz
Electrical power, max:	0.6 kW

Key Information:

Net weight:	32 kg
Shipping weight:	38 kg
Shipping height:	530 mm
Shipping width:	480 mm
Shipping depth:	630 mm

Sustainability

Refrigerant type:	R290
Refrigerant weight (unit 1):	85 g