



High Productivity Cooking Electric Pressure Braising Pan, 170lt with Backsplash, CTS & Tap

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____



586851 (PUEN17KPEM)

Electric Pressure Braising Pan 170lt (s) with steam condensation function, core temperature sensor and mixing tap, GuideYou panel, backsplash

Short Form Specification

Item No.

AISI 304 stainless steel construction. Pan in AISI 304 stainless steel; 18mm thick pan bottom (15mm mild steel and 3 mm AISI 316 stainless steel). Insulated and counterbalanced lid. Water mixing unit included. Unit to include food tap. The electric heating elements are mounted under the well. Safety thermostat protects the pan from overheating. A precise, electronic control of pan bottom temperature ensures fast reaction and exact adherence to preselected cooking temperatures between 50° and 250°C. The steam condensation function automatically nullifies the steam pressure after cooking is completed at the end of the cooking cycle. It can be used for poaching or steaming (with the lid open); simmering and boiling (with open or closed lid); pressure cooking of multiple produces possible thanks to the use of suspended GN 1/1 containers. TOUCH control panel. SOFT function. PRESSURE function. Possibility to store recipes in single or multiphase cooking process, with different temperature settings. Built in temperature sensors for precise control of cooking process. Core Temperature Sensor provides efficient temperature control. IPX6 water resistant. Configuration: Standing against a wall. Installation options (not included): floor mounted on 100mm high feet or a plinth which can be either steel or masonry construction.

Main Features

- Multifunctional cooking appliance used for roasting, pot-roasting, braising, simmering, boiling, pressure cooking and steaming.
- Square inner kettle allows working with stacked Gastronorm containers, which facilitate loading and unloading operations.
- Thermoblock heating system for optimal temperature distribution and high temperature stability.
- Pan bottom with two individually adjustable heating zones, each with a temperature sensor.
- Large capacity food tap enables safe and effortless discharging of contents.
- Easy to clean cooking surface due to large-radius edges and corners.
- Temperature sensors provides efficient temperature control: the power is supplied as and when required to keep the set temperature value without exceeding it.
- Cooking with a working pressure of 0.45 bar reduces cooking times.
- Optimum heat distribution in the food provides best cooking results in terms of taste, colour and consistency and in terms of vitamin preserving.
- Discharge tap is very easy to disassemble and clean.
- Overnight cooking: saving electricity and time.
- Safety mechanism prevents lid from opening, even in case of voluntary attempt, when cooking under pressure.
- Safety valve on the lid avoids overpressure in the food compartment.
- IPX6 water resistant.
- "Pressure function": once the pressure lid is locked, the system automatically regulates itself.
- Built in temperature sensor to precisely control the cooking process.
- Core Temperature Sensor (CTS): multi-sensor food probe, 6 sensors, 0,5 °C accuracy, provides efficient temperature control. The power is supplied as and when required to keep the set temperature value without exceeding it and once reached, the food is ready to be served.
- No overshooting of cooking temperatures, fast reaction.
- USB connection to easily update the software, upload/download recipes and download HACCP data.

Construction

- Minimised presence of narrow gaps for easier

APPROVAL:



Experience the Excellence
www.electroluxprofessional.com

b
o
il
i
ng

- Pressure mode (in pressure models)
- Stirrer ON/OFF settings (in round boiling models)
- Error codes for quick trouble-shooting
- Maintenance reminders

User Interface & Data Management

- Connectivity ready for real time access to connected appliances from remote and data monitoring (requires optional accessory - contact the Company for more details).

Sustainability


- High-quality thermal insulation of the pan saves energy and keeps operating ambient temperature low.

Optional Accessories

- Strainer for dumplings for all tilting & stationary braising and pressure braising pans (except 80lt) and for all stationary rectangular and 100lt round boiling pans PNC 910053 □
- Scraper for dumpling strainer for boiling and braising pans PNC 910058 □
- Suspension frame GN1/1 for rectangular boiling and braising pans PNC 910191 □
- Base plate 1/1 GN for braising pans PNC 910201 □
- Perforated container with handles 1/1GN (height=100mm) for boiling and braising pans PNC 910211 □
- Perforated container with handles 1/1GN (height 150mm) for boiling and braising pans PNC 910212 □
- Small perforated shovel for braising pans (PFEN/PUEN) PNC 911577 □
- Small shovel for braising pans (PFEN/PUEN) PNC 911578 □
- Scraper with horizontal handle for braising pans (PFEN/PUEN) PNC 911579 □
- Perforated container with handles 1/1GN (height 200mm) for boiling and braising pans PNC 911673 □
- Power Socket, CEE16, built-in, 16A/400V, IP67, red-white - factory fitted PNC 912468 □
- Power Socket, CEE32, built-in, 32A/400V, IP67, red-white - factory fitted PNC 912469 □
- Power Socket, SCHUKO, built-in, 16A/230V, IP68, blue-white - factory fitted PNC 912470 □
- Power Socket, TYP23, built-in, 16A/230V, IP55, black - factory fitted PNC 912471 □
- Power Socket, TYP25, built-in, 16A/400V, IP55, black - factory fitted PNC 912472 □


- Power Socket, SCHUKO, built-in, 16A/230V, IP55, black - factory fitted PNC 912473 □
- Power Socket, CEE16, built-in, 16A/230V, IP67, blue-white - factory fitted PNC 912474 □
- Power Socket, TYP23, built-in, 16A/230V, IP54, blue - factory fitted PNC 912475 □
- Power Socket, SCHUKO, built-in, 16A/230V, IP54, blue - factory fitted PNC 912476 □
- Power Socket, TYP25, built-in, 16A/400V, IP54, red-white - factory fitted PNC 912477 □
- Drain standpipe for 110/170lt stationary braising pans and stationary pressure braising pans PNC 912478 □
- Measuring rod and strainer for 170lt stationary braising pans PNC 912485 □
- Manometer for stationary pressure braising pans and rectangular pressure stationary boiling pans - factory fitted PNC 912492 □
- Connecting rail kit for appliances with backsplash, 900mm PNC 912499 □
- Set of 4 feet for stationary units (height 100mm) - factory fitted PNC 912701 □
- Kit energy optimization and potential free contact - factory fitted PNC 912737 □
- External touch control device for stationary units - factory fitted PNC 912783 □
- Emergency stop button - factory fitted PNC 912784 □
- Wall mounting kit for stationary units - factory fitted PNC 912788 □
- Automatic water filling (hot/cold) for round stationary boiling pans (width 1400-1700mm) - factory fitted PNC 912797 □
- Connecting rail kit for appliances with backsplash: modular 90 (on the left) to ProThermic tilting (on the right), ProThermic stationary (on the left) to ProThermic tilting (on the right) PNC 912981 □
- Connecting rail kit for appliances with backsplash: modular 90 (on the right) to ProThermic tilting (on the left), ProThermic stationary (on the right) to ProThermic tilting (on the left) PNC 912982 □
- Rear closing kit for stationary units with backsplash - factory fitted PNC 912998 □
- Stainless steel plinth for stationary units - against the wall - factory fitted PNC 913304 □
- Kit endrail and side panels, flush-fitting, for installation with backsplash, left - factory fitted PNC 913388 □
- Kit endrail and side panels, flush-fitting, for installation with backsplash, right - factory fitted PNC 913389 □

- Kit endrail and side panel (12.5mm), for installation with backsplash, left - factory fitted PNC 913412
- Kit endrail and side panel (12.5mm), for installation with backsplash, right - factory fitted PNC 913413
- Scraper without handle for braising pans (PFEX/PUEX) PNC 913431
- Scraper with vertical handle for braising pans (PFEX/PUEX) PNC 913432
- Connectivity kit for ProThermic Boiling and Braising Pans ECAP - factory fitted PNC 913577

Recommended Detergents

- C41 HI-TEMP RAPID DEGREASER, 1 pack of six 1 lt. bottles (trigger incl.) PNC 0S2292





CWI = Cold Water inlet 1 (cleaning)
 EI = Electrical inlet (power)
 HWI = Hot water inlet

Electric

Supply voltage: 400 V/3N ph/50/60 Hz
Total Watts: 20.6 kW

Installation:

FS on concrete base;FS on feet;On base;Standing against wall;Wall mounted (with wall-kit)

Type of installation:
Key Information:

Working Temperature MIN:	50 °C
Working Temperature MAX:	250 °C
Vessel (rectangle) width:	1080 mm
Vessel (rectangle) height:	340 mm
Vessel (rectangle) depth:	550 mm
External dimensions, Width:	1400 mm
External dimensions, Depth:	900 mm
External dimensions, Height:	800 mm
Net weight:	310 kg
Configuration:	Rectangular;Fixed;With splashback
Net vessel useful capacity:	170 lt
Double jacketed lid:	✓
Heating type:	Direct