

High Productivity Cooking Electric Rectangular Boiling Pan, 400lt Hygienic Profile, Backsplash + Tap

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____


586571 (PBEN40EJEM)

 Electric Boiling Pan 400lt (h),
 rectangular with mixing tap,
 GuideYou panel, backsplash

Short Form Specification

Item No. _____

AISI 304 stainless steel construction. Deep drawn vessel in AISI 316 stainless steel. Insulated and counterbalanced lid. Water mixing unit included. Unit to include food tap. Food is uniformly heated via the base and the side walls of the pan by an indirect heating system using integrally generated saturated steam at a maximum temperature of 125°C in a jacket with an automatic deaeration system. Safety valve avoids overpressure of the steam in the jacket. Safety thermostat protects against low water level in the double jacket. TOUCH control panel. SOFT function. Possibility to store recipes in single or multiphase cooking process, with different temperature settings. Built in temperature sensors for precise control of cooking process. IPX6 water resistant. Configuration: Standing against a wall. Installation options (not included): floor mounted on 200mm high feet or a plinth which can be either steel or masonry construction.

Main Features

- Kettle is suitable to boil, steam, poach, braise or simmer all kinds of produce.
- Square inner kettle allows working with stacked Gastronorm containers, which facilitate loading and unloading operations.
- Large capacity food tap enables safe and effortless discharging of contents.
- Isolated upper well rim avoids risk of harm for the user.
- Discharge tap is very easy to disassemble and clean.
- IPX6 water resistant.
- Built in temperature sensor to precisely control the cooking process.
- USB connection to easily update the software, upload/download recipes and download HACCP data.

Construction

- Cooking vessel in 1.4435 (AISI 316L) stainless steel. Double-jacket in 1.4404 (AISI 316L) stainless steel designed to operate at a pressure of 1.5 bar.
- External panelling and internal frame made of 1.4301 (AISI 304) stainless steel.
- Safety valve avoids overpressure of the steam in the double jacket.
- 2" diameter discharge tap for rapid emptying of the well.
- Minimised presence of narrow gaps for easier cleaning of the sides to meet the highest hygiene standards.
- Integrated water mixing tap to make water filling and pan cleaning operations easier.
- Can be prearranged for energy optimisation or external surveillance systems (optional).
- GuideYou Panel - activated by the user via settings - to easily follow the multiphase recipes, granting a proper and controlled cooking and a better appliance optimization. The system will provide maintenance reminders, in line with ESSENTIA program, helping the user to properly take care of the product, avoiding downtimes.
- Highly-visible and bright led TOUCH control panel features user-friendly icons and intuitive self-explanatory command options. Display visualizes:
 - Actual and set temperature
 - Set and remaining cooking time
 - Pre-heating phase (if activated)
 - GuideYou Panel (if activated)
 - Deferred start
 - Soft Function to reach the target temperature smoothly

APPROVAL: _____

- 9 PowerControl levels from simmering to fierce boiling
- Pressure mode (in pressure models)
- Stirrer ON/OFF settings (in round boiling models)
- Error codes for quick trouble-shooting
- Maintenance reminders

User Interface & Data Management

- Connectivity ready for real time access to connected appliances from remote and data monitoring (requires optional accessory - contact the Company for more details).

Sustainability




- High-quality thermal insulation of the pan saves energy and keeps operating ambient temperature low.


Optional Accessories

• Strainer for dumplings for all tilting & stationary braising and pressure braising pans (except 80lt) and for all stationary rectangular and 100lt round boiling pans	PNC 910053	☐	• External touch control device for stationary units - factory fitted	PNC 912783	☐
• Scraper for dumpling strainer for boiling and braising pans	PNC 910058	☐	• Wall mounting kit for stationary units - factory fitted	PNC 912789	☐
• Base plate for 400lt rectangular boiling pans	PNC 910184	☐	• Connecting rail kit for appliances with backsplash: modular 80 (on the left), ProThermetic tilting (on the right), ProThermetic stationary (on the left) to ProThermetic tilting (on the right)	PNC 912977	☐
• Suspension frame GN1/1 for rectangular boiling and braising pans	PNC 910191	☐	• Connecting rail kit for appliances with backsplash: modular 80 (on the right), ProThermetic tilting (on the left), ProThermetic stationary (on the right) to ProThermetic tilting (on the left)	PNC 912978	☐
• Manometer kit for stationary boiling pans - long - factory fitted	PNC 912120	☐	• Rear closing kit for stationary units with backsplash - factory fitted	PNC 912993	☐
• Power Socket, CEE16, built-in, 16A/400V, IP67, red-white - factory fitted	PNC 912468	☐	• Stainless steel plinth for stationary units - against the wall - factory fitted	PNC 913347	☐
• Power Socket, CEE32, built-in, 32A/400V, IP67, red-white - factory fitted	PNC 912469	☐	• Kit endrail and side panels, flush-fitting, for installation with backsplash, left - factory fitted	PNC 913378	☐
• Power Socket, SCHUKO, built-in, 16A/230V, IP68, blue-white - factory fitted	PNC 912470	☐	• Kit endrail and side panels, flush-fitting, for installation with backsplash, right - factory fitted	PNC 913379	☐
• Power Socket, TYP23, built-in, 16A/230V, IP55, black - factory fitted	PNC 912471	☐	• Kit endrail and side panel (12.5mm), for installation with backsplash, left - factory fitted	PNC 913402	☐
• Power Socket, TYP25, built-in, 16A/400V, IP55, black - factory fitted	PNC 912472	☐	• Kit endrail and side panel (12.5mm), for installation with backsplash, right - factory fitted	PNC 913403	☐
• Power Socket, SCHUKO, built-in, 16A/230V, IP55, black - factory fitted	PNC 912473	☐	• Drain standpipe for boiling pans (PBEN20/30/40 & PPEN20/30)	PNC 913429	☐
• Power Socket, CEE16, built-in, 16A/230V, IP67, blue-white - factory fitted	PNC 912474	☐	• Connectivity kit for ProThermetic Boiling and Braising Pans ECAP - factory fitted	PNC 913577	☐
• Power Socket, TYP23, built-in, 16A/230V, IP54, blue - factory fitted	PNC 912475	☐			
• Power Socket, SCHUKO, built-in, 16A/230V, IP54, blue - factory fitted	PNC 912476	☐			
• Power Socket, TYP25, built-in, 16A/400V, IP54, red-white - factory fitted	PNC 912477	☐			
• Measuring rod and strainer for 400lt stationary rectangular boiling pans	PNC 912483	☐			
• Connecting rail kit for appliances with backsplash, 800mm	PNC 912497	☐			
• Set of 4 feet for stationary units (height 200mm) - factory fitted	PNC 912732	☐			
• Automatic water filling (hot and cold) for stationary units (width 700-1000mm): rectangular pressure boiling and braising pans - factory fitted	PNC 912736	☐			
• Kit energy optimization and potential free contact - factory fitted	PNC 912737	☐			
• Mainswitch 80A, 16mm ² - factory fitted	PNC 912741	☐			

Front




Side



CWI = Cold Water inlet 1 (cleaning)
 EI = Electrical inlet (power)
 HWI = Hot water inlet

Top



Electric

Supply voltage: 400 V/3N ph/50/60 Hz
 Total Watts: 48.2 kW

Installation:

Type of installation:

FS on concrete base; FS on feet; On base; Standing against wall; Wall mounted (with wall-kit)

Key Information:

Working Temperature MIN: 50 °C

Working Temperature MAX: 110 °C

Vessel (rectangle) width: 1386 mm

Vessel (rectangle) height: 571 mm

Vessel (rectangle) depth: 556 mm

External dimensions, Width: 1700 mm

External dimensions, Depth: 800 mm

External dimensions, Height: 700 mm

Net weight: 355 kg

Configuration:

Rectangular; Fixed; With splashback

Net vessel useful capacity: 400 lt

Double jacketed lid: ✓

Heating type: Indirect