



High Productivity Cooking Electric Tilting Boiling Pan, 200lt , Wall mounted with Stirrer



586033 (PBOT20RWE0)

Electric tilting Boiling Pan
200lt prearranged for stirrer,
GuideYou panel, wall
mounted

Short Form Specification

Item No.

AISI 304 stainless steel construction. Deep drawn vessel in AISI 316 stainless steel. Insulated and counterbalanced lid. Motorized tilting with variable speed control. Pan can be tilted beyond 90° to completely empty the food. Stirring rotation speed 21rpm. Stirrer drive shaft included, stirrer blades to be ordered separately. Food is uniformly heated via the base and the side walls of the pan by an indirect heating system using integrally generated saturated steam at a maximum temperature of 125° C in a jacket with an automatic deaeration system. Safety valve avoids overpressure of the steam in the jacket. Safety thermostat protects against low water level in the double jacket. TOUCH control panel. SOFT function. Possibility to store recipes in single or multiphase cooking process, with different temperature settings. Built in temperature sensors for precise control of cooking process. IPX6 water resistant. Configuration: wall mounted.

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____

Main Features

- Kettle is suitable to boil, steam, poach, braise or simmer all kinds of produce.
- Kettle is jacketed up to 134 mm from upper rim.
- Isolated upper well rim avoids risk of harm for the user.
- Ergonomic vessel dimensions, with a large diameter and shallow depth facilitates stirring and gentle food handling.
- Edge of the large pouring lip can be equipped with a strainer (option).
- Motorized, variable pan tilting with "SOFT STOP". Tilting and pouring speeds can be precisely adjusted. Pan can be tilted over 90° to facilitate pouring and cleaning operations.
- Built in temperature sensor to precisely control the cooking process.
- USB connection to easily update the software, upload/download recipes and download HACCP data.
- IPX6 water resistant.
- Max pressure of inner jacket at 1.7 bar; minimum working pressure at 1 bar. Allows temperature control between 50 and 110°C.

Construction

- Cooking vessel in 1.4435 (AISI 316L) stainless steel featuring directional pouring lip. Double-jacket in 1.4404 (AISI 316L) stainless steel designed to operate at a pressure of 1.5 bar.
- External panelling and internal frame made of 1.4301 (AISI 304) stainless steel.
- Double-lined insulated lid in 1.4301 (AISI 304) stainless steel mounted on the cross beam of the unit, counterbalanced by a hinge that remains open in all positions.
- Safety valve avoids overpressure of the steam in the double jacket.
- Safety thermostat protects against low water level in the double jacket.
- Water mixing tap is available as optional accessory to make water filling and pan cleaning easier.
- Ergonomic and user friendly thanks to the high tilting position and the pouring lip design which allow to easily fill containers.
- Front-mounted inclined led "TOUCH" control panel with recessed deep drawn casing, features self-explanatory display functions which guide operator throughout the cooking process: simultaneous display of actual and set temperature as well as set cooking time and remaining cooking time; real time clock; "SOFT" control for gentle heating up for delicate food; 9 power simmering levels from gentle to heavy boiling; timer for deferred

APPROVAL:



Experience the Excellence
www.electroluxprofessional.com

start; error display for quick trouble-shooting.

- Minimised presence of narrow gaps for easier cleaning of the sides to meet the highest hygiene standards.
- Can be prearranged for energy optimisation or external surveillance systems (optional).
- Possibility to store recipes in single or multiphase cooking process, with different temperature settings.
- 98% recyclable by weight; packaging material free of toxic substances.
- Stirrer with rotation speed of 21 RPMs.
- GuideYou Panel - activated by the user via settings - to easily follow the multiphase recipes, granting a proper and controlled cooking and a better appliance optimization. The system will provide maintenance reminders, in line with ESSENTIA program, helping the user to properly take care of the product, avoiding downtimes.
- Highly-visible and bright led TOUCH control panel features user-friendly icons and intuitive self-explanatory command options. Display visualizes:
 - Actual and set temperature
 - Set and remaining cooking time
 - Pre-heating phase (if activated)
 - GuideYou Panel (if activated)
 - Deferred start
 - Soft Function to reach the target temperature smoothly
 - 9 Power Control levels from simmering to fierce boiling
 - Pressure mode (in pressure models)
 - Stirrer ON/OFF settings (in round boiling models)
 - Error codes for quick trouble-shooting
 - Maintenance reminders

User Interface & Data Management

- Connectivity ready for real time access to connected appliances from remote and data monitoring (requires optional accessory - contact the Company for more details).

Included Accessories

- 1 of Emergency stop button - factory fitted

PNC 912784

Optional Accessories

- Strainer for 200lt round tilting boiling pans
- Measuring rod for 200lt tilting boiling pans
- Grid stirrer for 200lt boiling pans
- Grid stirrer and scraper for 200lt boiling pans
- Food tap strainer rod for stationary round boiling pans
- FOOD TAP STRAINER - PBOT
- C-board (length 1400mm) for tilting units - factory fitted

 PNC 910005

 PNC 910046

 PNC 910065

 PNC 910095

 PNC 910162

 PNC 911966

 PNC 912186

- Power Socket, CEE16, built-in, 16A/400V, IP67, red-white - factory fitted
- Power Socket, CEE32, built-in, 32A/400V, IP67, red-white - factory fitted
- Power Socket, SCHUKO, built-in, 16A/230V, IP68, blue-white - factory fitted
- Power Socket, TYP23, built-in, 16A/230V, IP55, black - factory fitted
- Power Socket, TYP25, built-in, 16A/400V, IP55, black - factory fitted
- Power Socket, SCHUKO, built-in, 16A/230V, IP55, black - factory fitted
- Power Socket, CEE16, built-in, 16A/230V, IP67, blue-white - factory fitted
- Power Socket, TYP23, built-in, 16A/230V, IP54, blue - factory fitted
- Power Socket, SCHUKO, built-in, 16A/230V, IP54, blue - factory fitted
- Power Socket, TYP25, built-in, 16A/400V, IP54, red-white - factory fitted
- Manometer for tilting boiling pans - factory fitted
- Automatic water filling (hot and cold) for tilting units - to be ordered with water mixer - factory fitted
- Kit energy optimization and potential free contact - factory fitted
- Mainswitch 60A, 10mm² - factory fitted
- Spray gun for tilting units - against wall (height 400mm) - factory fitted
- Food tap 2" for tilting boiling pans (PBOT) - factory fitted
- Mixing tap with drip stop, two knobs, 815mm height, 600mm swivelling depth for PBOT/PFET - factory fitted
- Mixing tap with drip stop, two knobs, 815mm height, 450mm swivelling depth for PBOT/PFET - factory fitted
- Mixing tap with drip stop, two knobs, 685mm height, 600mm swivelling depth for PBOT/PFET - factory fitted
- Mixing tap with drip stop, two knobs, 685mm height, 450mm swivelling depth for PBOT/PFET - factory fitted
- Mixing tap with two knobs, 520mm height, 600mm swivelling depth for PXXT- KWC - factory fitted

 PNC 912468

 PNC 912469

 PNC 912470

 PNC 912471

 PNC 912472

 PNC 912473

 PNC 912474

 PNC 912475

 PNC 912476

 PNC 912477

 PNC 912490

 PNC 912735

 PNC 912737

 PNC 912774

 PNC 912775

 PNC 912779

 PNC 913554

 PNC 913555

 PNC 913556

 PNC 913557

 PNC 913567




High Productivity Cooking Electric Tilting Boiling Pan, 200lt , Wall mounted with Stirrer



- Mixing tap with one lever, 564mm height, 450mm swivelling depth for PXXT- KWC - factory fitted PNC 913568 □
- Connectivity kit for ProThermetic Boiling and Braising Pans ECAP - factory fitted PNC 913577 □




High Productivity Cooking
Electric Tilting Boiling Pan, 200lt , Wall mounted with Stirrer

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2026.01.15

Front

Side


CWI = Cold Water inlet 1 (cleaning)
 EI = Electrical inlet (power)
 HWI = Hot water inlet

Top

Electric

Supply voltage: 400 V/3N ph/50/60 Hz
Total Watts: 30.6 kW

Installation:

Type of installation: Wall mounted

Key Information:

Working Temperature MIN: 50 °C
Working Temperature MAX: 110 °C
Vessel (round) diameter: 800 mm
Vessel (round) depth: 490 mm
External dimensions, Width: 1400 mm
External dimensions, Depth: 1000 mm
External dimensions, Height: 400 mm
Net weight: 400 kg

Configuration: Round;Tilting;Pre-arranged for stirrer

Net vessel useful capacity: 200 lt

Tilting mechanism: Automatic

Double jacketed lid: ✓

Heating type: Indirect